



Powering Business Worldwide

pe.eaton.com

General Purpose Power Supply

PSG480E24RM

UPC:786685683560

Dimensions:

- **Height:** 3 IN
- **Length:** 6.5 IN
- **Width:** 6.5 IN

Weight:1.191 LB

Warranties: No Data

Specifications:

- **Operating Temperature:** -20° to 75°C
- **Wattage:** 480W
- **Degree Of Protection:** IP20
- **Enclosure Material:** Aluminum
- **Frequency Rating:** 47-63 Hz
- **Input Voltage:** 100-240 Vac
- **Mounting:** DIN rail
- **Nominal Voltage:** 24 Vdc (± 4.8 Vdc)
- **Output:** 24 Vdc/2.5A
- **Phase:** Single-phase

Supporting documents:

- [Eatons Volume 7-Logic Control, Operator Interface and Connectivity Solutions](#)
- [PSG480E24RM 2D PDF](#)
- [PSG480E24RM 2D Drawing Xchange](#)
- [PSG480E24RM AutoCAD 2D Footprint](#)
- [PSG480E24RM 3D Model Xchange](#)
- [PSG480E24RM 3D Inventor](#)
- [PSG480E24RM AutoCAD 2D Footprint \(mm\)](#)
- [Installation Instructions for PSG480E Power Supply](#)
- [Eatons PSG Series Power Supplies](#)
- [Eaton Specification Sheet - PSG480E24RM](#)

Certifications:



- EN 50178
- PELV (EN 60204)
- EN 61000-406
- EN 61000-4-11
- SELV (EN 60950)
- EN 61000-6-2
- EN 61000-4-2
- UL 508
- CSA Certified
- IEC Rated
- EN 60204
- cULus/UL 60950-1
- EN 61000-6-4
- EN 610003-2

Product compliance:

- German Safety
- CE Marked
- RoHS Compliant
- DIN 57100-410