



Powering Business Worldwide



BC Pro UPS System - Standby UPS System

MODEL NUMBER: **BCPRO850**

Description

Tripp Lite's BCPRO850 standby UPS system offers surge suppression and long lasting battery support for personal computers, internetworking equipment and other sensitive electronics. UPS inverter and auto-transfer circuits maintain battery derived AC output during power failures and brownouts so that connected equipment can be safely shutdown without data loss. Includes 6 battery supported AC outlets. USB monitoring port enables optional unattended system shutdown in the case of extended power failure. PowerAlert UPS monitoring and shutdown software available via free download from www.tripplite.eaton.com. Built-in audible alarm and 5 front panel LEDs indicate line power, battery power, low/high input voltage detected, overload and battery low/replace status. 850VA/600 watt power handling ability supports entry-level PCs, network workstations, point-of-sale equipment, small business phone systems, audio/video equipment and home theater systems. Offers 9 minutes battery runtime with a full load of 850VA and 26 minutes with a half load of 425VA. Offers up to 55 minutes runtime with a single desktop computer and 15 inch monitor. Supports user battery replacement via built-in access panel. 2 year warranty. \$200,000 connected equipment insurance (USA & Canada only).

Features

- BCPRO850 standby UPS system offers battery support during blackouts and brownouts, plus AC line surge suppression
- Maintains user productivity during utility power problems enabling a safe system shutdown without data loss
- Supports a max load of 850VA/600 watts for 9 minutes
- Supports a half load of 425VA/300 watts for 26 minutes
- Offers extended runtime operation of up to 55 minutes when used with a single desktop PC and 15 inch monitor
- Supplies battery derived AC output during brownouts starting at 99 volts
- Attractive gray small footprint upright tower configuration
- Includes 6 battery supported NEMA 5-15R output receptacles, 6 foot AC line cord (NEMA 5-15P input connection)
- Built-in USB port enables unattended shutdown without data loss during extended power failures
- Communications port supports on battery, low battery and power restored messaging - plus additional data regarding AC line voltage and battery charge level
- Supports Tripp Lite's WatchDog software application to restore unresponsive programs by automatically restarting them and rebooting completely locked computers by automatically switching UPS power off and back on again
- PowerAlert UPS monitoring and shutdown software available via free download from <https://tripplite.eaton.com>
- Two front panel switches support power off/on control, alarm cancel and UPS self test functions
- Built-in audible alarm and 5 front panel LEDs indicate line power, battery power, battery low/replace and overload status
- 850VA power handling ability supports a variety of computer, internetworking, telecom and overload status
- Supports hot swappable user battery replacement via built-in access panel
- Compatible with 120V/60Hz applications
- UL1778 listed (USA), cUL (Canada), NOM (Mexico), FCC Class B
- 2 year manufacturers warranty
- \$200,000 connected equipment insurance (USA & Canada only)

Highlights

- 850VA standby, tower UPS system
- Offers battery derived AC output during blackouts and brownouts starting at 99V
- 6 protected AC outlets (NEMA 5-15R)
- USB communications port and cabling for use with free PowerAlert monitoring software
- \$200,000 Ultimate Lifetime Insurance (USA, Puerto Rico & Canada only)

Package Includes

- BCPRO850 UPS System
- USB cable
- Warranty information
- Instruction manual

Specifications



Powering Business Worldwide

TRIPP-LITE
by **EAT•N**

OVERVIEW	
UPC Code	037332033291
INPUT	
UPS Input Cord Length (ft.)	6
UPS Input Cord Length (m)	1.8
Recommended Electrical Service	15A 120V
Maximum Input Amps	5.8
Input Connection Type	NEMA 5-15P
Voltage Compatibility (VAC)	120
OUTPUT	
Frequency Compatibility	60 Hz
Output Nominal Voltage	120V AC
Output Voltage Regulation	BATTERY MODE: PWM sine wave output 115V +/-5%
Output Frequency Regulation	LINE MODE: Passes line frequency of 60Hz +/-10% BATTERY MODE: Inverter output regulated to 60Hz +/-0.5Hz
BATTERY	
Runtime Full Load (min.)	9 min.
Runtime Half Load (min.)	26 min.
DC System Voltage (VDC)	18
Battery Access	Battery access door allows user replacement of UPS batteries
Typical Battery Lifespan	3-6 years, depending on usage
Battery Charge	2-4 hours to 90%
USER INTERFACE, ALERTS & CONTROLS	
Front Panel LEDs	5 front panel LEDs indicate line power status, battery power status, battery low/replace status, low/high input voltage detected and overload status
Switches	Includes 2 front panel switches—one main on/off power switch and one dual function "alarm cancel" / "self test" button
Audible Alarm	Audible alarm with 15 second delay sounds to indicate loss of utility power. Alarm can be silenced by pressing front panel alarm cancel button. Once silenced, alarm will re-sound when approximately 2 minutes runtime remain.
SURGE / NOISE SUPPRESSION	
UPS AC Suppression Joule Rating	1800
EMI / RFI AC Noise Suppression	Yes
AC Suppression Response Time	Instantaneous
PHYSICAL	



Powering Business Worldwide



Material of Construction	Polycarbonate
Cooling Method	Convection
Form Factors Supported	Tower, wall mountable with optional UPSWM ; accessory
Shipping Dimensions (hwd / in.)	13.25 x 16.00 x 10.00
Shipping Dimensions (hwd / cm)	33.66 x 40.64 x 25.40
Shipping Weight (lbs.)	32.60
Shipping Weight (kg)	14.79
Unit Dimensions (hwd / in.)	0.000 x 0.000 x 0.000
Unit Dimensions (hwd / cm)	29.8 x 18.4 x 18.4
Unit Weight (lbs.)	28.6
Unit Weight (kg)	12.97
ENVIRONMENTAL	
Relative Humidity	0 to 95%, non-condensing
COMMUNICATIONS	
WatchDog Compatibility	Compatible with Tripp Lite's Watchdog system service to restore operation to locked equipment through soft reboot of application / OS or hard power off/on reboot of connected equipment - ideal for unattended kiosk applications
Network Monitoring Port	Built-in USB port supports on battery, low battery, power restored, AC line voltage, DC battery voltage and battery capacity messaging.
LINE / BATTERY TRANSFER	
Transfer Time (Line Power to Battery Mode)	2-4 milliseconds
Low Voltage Transfer to Battery Power	Switches to battery power as line voltage decreases to 99 volts or less. Resets back to line power mode as line voltage increases to 104V or higher.
High Voltage Transfer to Battery Power	Yes
FEATURES & SPECIFICATIONS	
Cold Start	Yes, inverter can be "cold started" to enable temporary AC output during a power failure
WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	2-year limited warranty
Optional Coverage	3-5 year warranties, plus next day and on-site warranty coverage available. Contact Tripp Lite for additional information.
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$200,000 Ultimate Lifetime Insurance



Powering Business Worldwide



1000 Eaton Boulevard
Cleveland, OH 44122
United States
<https://tripplite.eaton.com>

© 2024 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.