




Powering Business Worldwide

## 7-Outlet Home/Business Theater Surge Protector, 6-ft. Cord, 1500 Joules, Coaxial Protection

MODEL NUMBER: HT706TV



### Highlights

- 7 outlets / 6 ft. cord
- 1500 joule rating
- 2.2 GHz gold coaxial surge protection

### Package Includes

- HT706TV Home/Business Theater Surge Suppressor
- 6 ft. gold coaxial cable
- Instruction manual with warranty information

### Description

Tripp Lite's HT706TV Home/Business Theater Surge Suppressor provides high-performance protection (1500 joules) stopping damaging surges and filtering disruptive line noise so components perform at their peak! You can see and hear the difference: sharper, crisper video; deeper, fuller audio and longer component life spans. Perfect for small home/business theater installations: high-definition TVs, satellite and A/V receivers, DVD/CD players and more. 7 outlets (with transformer spacing) and 1-line 2.2GHz gold coaxial protection safeguard an entire home/business theater system. \$50,000 Ultimate Lifetime Insurance coverage (U.S., Canada, and Puerto Rico only). Includes two diagnostic LEDs, 6 ft. cord with a right-angle plug and 6 ft. coaxial cable.

### Features

- 1500 joules surge suppression rating with EMI/RFI line noise filtering help components perform at their peak (sharper, crisper video; deeper, fuller audio and longer component life spans)
- \$50,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only) covers connected components against surge damage...for life!
- 7 surge-protected NEMA 5-15R AC outlets safeguard an entire home/business theater system
- Widely-spaced outlets accommodate up to 4 transformers
- 1 set of 2.2 GHz gold coaxial connectors (with included 6 ft. gold coaxial cable) safeguard components on cable, satellite or antenna line
- 6 ft. cord with right-angle NEMA 5-15P plug provides convenient location anywhere within a home/business theater system
- 2 diagnostic LEDs alert user to protection and grounding status
- Keyhole slots provide convenient wall or cabinet mounting
- Illuminated master switch provides one-touch power control over all components. Integrated circuit breaker protects against dangerous system overload
- High-impact plastic housing (black) stands up to the most demanding environments
- UL and CSA listed
- Automatic shutoff permanently cuts power to outlets if protection circuit is incapacitated, preventing



Powering Business Worldwide

equipment damage and indicating replacement is required

## Specifications

| OVERVIEW                           |                                                                                    |
|------------------------------------|------------------------------------------------------------------------------------|
| UPC Code                           | 037332121493                                                                       |
| INPUT                              |                                                                                    |
| Nominal Input Voltage(s) Supported | 120V AC                                                                            |
| Recommended Electrical Service     | 120V (110-125V)                                                                    |
| Input Cord Gauge Type              | 14 gauge; SJT                                                                      |
| Voltage Compatibility (VAC)        | 120                                                                                |
| Maximum Surge Amps                 | 60000                                                                              |
| Input Plug Type                    | NEMA 5-15P                                                                         |
| Input Cord Length (ft.)            | 6                                                                                  |
| Right-Angle Plug                   | Yes                                                                                |
| Input Cord Length (m)              | 1.83                                                                               |
| Integrated Cord Clip               | No                                                                                 |
| OUTPUT                             |                                                                                    |
| Frequency Compatibility            | 50 / 60 Hz                                                                         |
| Output Receptacles                 | (7) 5-15R                                                                          |
| Circuit Breaker (amps)             | 15                                                                                 |
| Transformer Accommodation          | (4) Yes                                                                            |
| Right-Angle Outlets                | Yes                                                                                |
| USER INTERFACE, ALERTS & CONTROLS  |                                                                                    |
| Diagnostic LED(s)                  | Yes                                                                                |
| Switches                           | Combination AC circuit breaker and 2 position red illuminated on/off power switch  |
| Diagnostic LED Details             | Built-in LEDs confirm protection and grounding status                              |
| SURGE / NOISE SUPPRESSION          |                                                                                    |
| AC Suppression Joule Rating        | 1500                                                                               |
| AC Suppression Response Time       | < 1 ns                                                                             |
| Protection Modes                   | Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression |
| UL1449 Let Through Rating          | 400 L-N, 400 L-G, 500 N-G                                                          |
| EMI / RFI Filtering                | Up to 40 dB                                                                        |
| Automatic Shut-Off                 | Yes                                                                                |



Powering Business Worldwide

| DATALINE SURGE SUPPRESSION                                 |                                                                                                                       |
|------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------|
| Cable (Coax) Protection                                    | Yes                                                                                                                   |
| Cable (Coax) Protection Details                            | 1 line                                                                                                                |
| Network (Ethernet) Protection                              | No                                                                                                                    |
| Telephone/DSL Protection                                   | No                                                                                                                    |
| PHYSICAL                                                   |                                                                                                                       |
| Color                                                      | Black                                                                                                                 |
| Material of Construction                                   | Plastic                                                                                                               |
| Power Cord Color                                           | Black                                                                                                                 |
| Housing Color                                              | Black                                                                                                                 |
| Mounting Holes or Slots                                    | Yes                                                                                                                   |
| Slot or Hole Mount Measurement (Center to Center)          | 160mm                                                                                                                 |
| Outlets Measurement (Center to Center)                     | Distance between transformer outlet and standard outlet = 38.10mm; Distance between standard outlets = 25.40mm        |
| Receptacle Color                                           | Black                                                                                                                 |
| Shipping Dimensions (hwd / in.)                            | 14.10 x 1.75 x 5.90                                                                                                   |
| Shipping Dimensions (hwd / cm)                             | 35.81 x 4.44 x 14.99                                                                                                  |
| Shipping Weight (lbs.)                                     | 1.90                                                                                                                  |
| Shipping Weight (kg)                                       | 0.86                                                                                                                  |
| Unit Dimensions (hwd / in.)                                | 1.500 x 14.000 x 3.250                                                                                                |
| Unit Dimensions (hwd / cm)                                 | 3.8 x 35.6 x 7                                                                                                        |
| Unit Weight (lbs.)                                         | 1                                                                                                                     |
| Unit Weight (kg)                                           | 0.45                                                                                                                  |
| FEATURES & SPECIFICATIONS                                  |                                                                                                                       |
| Rotatable Outlets                                          | No                                                                                                                    |
| Antimicrobial                                              | No                                                                                                                    |
| WARRANTY & SUPPORT                                         |                                                                                                                       |
| Product Warranty Period (Worldwide)                        | Lifetime limited warranty                                                                                             |
| Connected Equipment Insurance (U.S., Canada & Puerto Rico) | \$50,000 <a class="insuranceLink" href="//www.tripplite.com/support/insurance-policy">Ultimate Lifetime Insurance</a> |



*Powering Business Worldwide*

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2024 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.