



Powering Business Worldwide

## Power Distribution Unit (PDU) - Accessory adds additional outlet types to dual voltage UPS System

MODEL NUMBER: **PDU6K**

### Description

Tripp Lite's PDU6K AC power distribution unit offers 24 amp, 240/120V capacity in a versatile multi-mount cabinet. Detachable mounting flanges are configurable for wallmount, under-counter or 2U rackmount installation. Detachable flanges allow user configuration in dozens of potential mounting schemes. Includes 8 outlets total (1xL5-30R, 1xL5-20R, 2xL6-30R, 2xL6-20R, 1x6-20R), with NEMA L14-30P input plug. 4 ft. AC input cord.

PLUG/OUTLETS: Input: NEMA L14-30P/Output: 1 L5-30, 1 L5-20, 2 L6-30, 2 L6-20, 2 6-20R

ELECTRICAL: 240V AC input, 240/120V AC output

FORMAT: Supports 19 in. rackmount (2U), wallmount and under-counter

### Features

- Coded AC power distribution unit with 8 output receptacles
- Versatile all-metal cabinet with detachable mounting flanges allows wallmount, under-counter and 19 inch rackmount mounting in 2U format
- 4 120V and 4 240V output receptacles (1xL5-30R, 1xL5-20R, 2xL6-30R, 2xL6-20R, 1x6-20R)
- 4 ft. AC cord with L14-30 plug-in connection
- Removable plug enables hardwire input connection

### Highlights

- 8 outlet PDU system adds 240 and 120V output receptacles to select dual voltage 240/120V UPS systems
- Includes 4 ft. cord with L14-30 plug
- Input plug supports hardwire input connection
- Supports installation in 2U rackmount, wallmount and under-counter applications

### Package Includes

- PDU6K rackmount power strip
- Instruction manual

## Specifications

| OVERVIEW                    |                                                                    |
|-----------------------------|--------------------------------------------------------------------|
| UPC Code                    | 037332119346                                                       |
| INPUT                       |                                                                    |
| Input Phase                 | Single-Phase                                                       |
| Input Connection Type       | Nema L14-30 input plug, removable for 4 wire hardwire installation |
| PDU Plug Type               | Hardwire                                                           |
| Voltage Compatibility (VAC) | 240                                                                |
| Input Cord Length (ft.)     | 4                                                                  |
| Input Cord Length (m)       | 1.22                                                               |
| OUTPUT                      |                                                                    |
| Output Receptacles          | (1) 6-15/20R; (1) L5-20R; (1) L5-30R; (2) L6-20R; (1) L6-30R       |
| Circuit Breaker (amps)      | 20                                                                 |
| Overload Protection         | 20A resettable double pole breaker                                 |
| PHYSICAL                    |                                                                    |
| Material of Construction    | Metal                                                              |



*Powering Business Worldwide*

|                                 |                                          |
|---------------------------------|------------------------------------------|
| Power Cord Color                | Black                                    |
| Form Factors Supported          | 2U rackmount, wallmount, under-counter   |
| Housing Color                   | Black                                    |
| Included Mounting Accessories   | Recessed rackmount installation brackets |
| PDU Form Factor                 | Horizontal (2U)                          |
| Receptacle Color                | Black                                    |
| Shipping Dimensions (hwd / in.) | 6.50 x 18.25 x 8.25                      |
| Shipping Dimensions (hwd / cm)  | 16.51 x 46.36 x 20.96                    |
| Shipping Weight (lbs.)          | 8.00                                     |
| Shipping Weight (kg)            | 3.63                                     |
| Unit Dimensions (hwd / in.)     | 3.500 x 17.250 x 3.750                   |
| Unit Dimensions (hwd / cm)      | 8.9 x 43.8 x 9.5                         |
| Unit Weight (lbs.)              | 6.25                                     |
| Unit Weight (kg)                | 2.83                                     |

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2024 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.