

# 5.5kW Single-Phase Local Metered PDU, 208/230V Outlets (16 C13 & 2 C19), L6-30P, 12 ft. (3.66 m) Cord, 2U Rack-Mount, TAA

MODEL NUMBER: PDUMH30HV



## Highlights

- Local metered single phase 24A 208/230V 2U horizontal rackmount PDU
- Two built-in meters report output current in amps for each load bank
- Attached 12-ft. (3.66 m) cord with NEMA L6-30P input plug
- 18 total outlets (16 C13, 2 C19)
- Reversible housing, 2U 208/230V rackmount local metered PDU
- TAA Compliant

## Package Includes

- 2U rack PDU
- Mounting brackets
- Plug retention plates
- User manual

## Features

- 30A single phase 208/230V Local Metered Power Distribution Unit / rack PDU (rPDU) (Agency derated to 24A continuous)
- Set of two lighted meters report PDU output current in amps for each 9 outlet load bank
- Attached NEMA L6-30P 30A 208/230V input plug and 12-ft. (3.66 m) cord
- 2U horizontal rackmount format installs in two rack spaces
- 18 output receptacles (16 C13, 2 C19)
- Outlets are arranged in two 9 outlet load banks, each with separate 20A breaker and current metering
- Mounting flanges support installation in 2 and 4 post racks, with additional support for wall-mount and under-counter installation formats
- Mounting ears are reversible for front or rear facing rackmount installation
- Cord retention brackets keep vital equipment plugs connected
- Grounding lug
- Compliant with the Federal Trade Agreements Act(TAA) for GSA Schedule purchases

## Specifications

| OVERVIEW          |               |
|-------------------|---------------|
| UPC Code          | 037332159021  |
| PDU Type          | Local Metered |
| INPUT             |               |
| Input Phase       | Single-Phase  |
| PDU Input Voltage | 208; 230      |



Powering Business Worldwide

**TRIPP-LITE**  
by **EATON**

|  |   |
|--|---|
| Recommended Electrical Service               | Single-phase 30A 208/230V service   |
| Maximum Input Amps                           | 24  |
| Maximum Input Amps Details                   | Agency de-rated to 24A continuous   |
| PDU Plug Type                                | NEMA L6-30P   |
| Input Cord Length (ft.)                      | 12  |
| Input Cord Length (m)                        | 3.66  |
| <b>OUTPUT</b>                                |   |
| Output Capacity Details                      | 5.5kW (230V), 5kW (208V) total capacity / 30A max (Agency de-rated to 24A), 20A max per breakered outlet bank; 16A max per C19 outlet; 12A max per C13 outlet |
| Frequency Compatibility                      | 50 / 60 Hz  |
| Output Receptacles                           | (16) C13; (2) C19   |
| Output Nominal Voltage                       | 208/230V  |
| Overload Protection                          | Two 20A breakers protect 9 outlets each   |
| <b>USER INTERFACE, ALERTS &amp; CONTROLS</b> |   |
| Front Panel LCD Display                      | Set of 2 digital meters continuously report output current for breakered load banks 1 & 2 (Bank 1: upper row of 9 outlets / Bank 2: lower row of 9 outlets)   |
| <b>SURGE / NOISE SUPPRESSION</b>             |   |
| Automatic Shut-Off                           | No  |
| <b>PHYSICAL</b>                              |   |
| Material of Construction                     | Metal   |
| Form Factors Supported                       | 2U rackmount; mounting accessories included   |
| Minimum Required Rack Depth (cm)             | 40.64   |
| Minimum Required Rack Depth (inches)         | 16  |
| PDU Form Factor                              | Horizontal (2U)   |
| Shipping Dimensions (hwd / in.)              | 7.80 x 16.70 x 19.80  |
| Shipping Dimensions (hwd / cm)               | 19.81 x 42.42 x 50.29   |
| Shipping Weight (lbs.)                       | 15.80   |
| Shipping Weight (kg)                         | 7.17  |
| Unit Dimensions (hwd / in.)                  | 3.500 x 17.500 x 12.500   |
| Unit Dimensions (hwd / cm)                   | 8.8 x 44.4 x 31.8   |
| Unit Weight (lbs.)                           | 13.7  |
| Unit Weight (kg)                             | 6.21  |
| <b>ENVIRONMENTAL</b>                         |   |
| Operating Temperature Range                  | 32° to 104°F (0° to 40°C)   |

|                                     |   |
|-------------------------------------|---|
| Storage Temperature Range           | -22° to 122°F (-30° to 50°C)                                      |
| Relative Humidity                   | 5% to 95% non-condensing  |
| Operating Elevation                 | 0-10000 ft. (0-3000 m)  |
| FEATURES & SPECIFICATIONS           |   |
| Grounding                           | Grounding lug   |
| STANDARDS & COMPLIANCE              |   |
| Product Certifications              | NOM (Mexico); UL 62368-1  |
| Product Compliance                  | RoHS; FCC Part 15 Class A (USA); UKCA; Trade Agreements Act (TAA) |
| WARRANTY & SUPPORT                  |   |
| Product Warranty Period (Worldwide) | 2-year limited warranty   |

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2024 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.