

Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234

www.tripplite.com

TAA-Compliant 7.4kW Single-Phase Metered PDU, 230V Outlets (2-C19, 16-C13), IEC-309 230V 32A Blue 12ft Cord, 2U Rack-Mount

MODEL NUMBER: PDUMH32HVTAA











Description

Tripp Lite Metered Power Distribution Units / PDU systems continuously report output load level in amps to help network managers prevent overloads and plan for future growth. Supplies equipment with continuous power

Highlights

- Federal Trade Agreements Act / TAA Compliant for GSA Schedule purchases
- Metered single phase 32A 230V
 2U horizontal rackmount PDU
- Set of 2 current meters reports current in amps for each output load bank
- Attached 12 ft. / 3.6m cord with IEC-309 32A (2P+E) input plug
- 18 total 230V outlets (2 C19, 16 C13)
- Reversible housing, 12.5 in. / 31.75cm depth

Package Includes

- TAA Compliant version of Tripp Lite PDUMH32HV
- · Mounting brackets
- Plug retention brackets
- User manual

from any protected UPS, generator or mains input power source. Highly reliable design includes rugged all-metal housing and secure rackmount installation with included mounting accessories.

Features

- Federal Trade Agreements Act / TAA Compliant for GSA Schedule purchases
- 32A single phase 230V Metered Power Distribution Unit / PDU
- Set of two lighted current meters separately report power consumption in amps for each output load bank
- Attached IEC-309 32A (2P+E) input plug with 12 ft. / 3.6m line cord
- 2U horizontal rackmount format installs in two rack spaces
- 18 total 230V outlets (2 C19, 16 C13)
- Outlets are arranged in two separately breakered and metered 16A load banks (each with 8 C13 and 1 C19 outlet)
- . Mounting flanges support installation in 2 and 4 post racks, with additional support for wall-mount and under-counter installation formats
- Front-panel grounding lug
- · Included cord retention brackets

Specifications

OVERVIEW	
PDU Type	Metered
ОИТРИТ	



Output Capacity Details	7.4kW (230V) / 32A total capacity / 16A max per breakered outlet bank; 16A max per C19 outlet; 10A max per C13 outlet	
Frequency Compatibility	50 / 60 Hz	
Output Receptacles	(16) C13; (2) C19	
Output Nominal Voltage	230	
Overload Protection	Two 20A circuit breakers protect 9 outlets each	
INPUT		
Nominal Input Voltage(s) Supported	230V AC	
PDU Input Voltage	230	
Maximum Input Amps	32	
PDU Plug Type	IEC-309 32A BLUE (2P+E)	
Input Cord Length (ft.)	12	
Input Cord Length (m)	3.65	
Input Phase	Single-Phase	
USER INTERFACE, ALERTS & CONT	TROLS	
Front Panel LCD Display	Set of 2 digital meters continuously report output current for breakered load bank; Bank 1 (Upper row of 9 outlets), Bank 2 (Lower row of 9 outlets)	
Switches	n/a	
PHYSICAL		
Minimum Required Rack Depth (inches)	16	
Minimum Required Rack Depth (cm)	40.6	
Shipping Dimensions (hwd / in.)	5.5 x 20.5 x 17	
Shipping Dimensions (hwd / cm)	14 x 113 x 80.6	
Shipping Weight (lbs.)	16.2	
Shipping Weight (kg)	7.4	
Unit Dimensions (hwd / in.)	3.5 x 17.5 x 12.5	
Unit Dimensions (hwd / cm)	8.9 x 44.5 x 31.75	
Unit Weight (lbs.)	13.7	
Unit Weight (kg)	6.2	
Material of Construction	Steel	
Form Factors Supported	2U rackmount	
PDU Form Factor	2U; Horizontal	
ENVIRONMENTAL 2/3		



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Relative Humidity	0-95% non-condensing	
CERTIFICATIONS		
CERTIFICATIONS		
Certifications	Tested to CE (IEC 60950-1), UL, CSA, Class A, RoHS compliant, TAA Compliant	
WARRANTY		
Product Warranty Period (Worldwide)	2-year limited warranty	

© 2017 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies