



Powering Business Worldwide

pe.eaton.com

Eaton 9130 UPS

PW9130I2000T-XL

UPC:790341052829

Dimensions:

- **Height:** 12.8 IN
- **Length:** 16.1 IN
- **Width:** 8.4 IN

Weight:76.1 LB

Notes:Allows UPS operation without utility input

Warranties:

- 2 year limited factory

Specifications:

- **Type:** UPS
- **Topology:** Online/Double-conversion
- **Form Factor:** Tower
- **Color:** Black
- **VA Rating:** 2000 VA
- **Wattage:** 1800 W
- **Package Contents:** 1 ready-to-go UPS|Software suite CD|USB cable|User guide|Quick start instructions|Cord-retention brackets|(2) IEC to IEC power cords
- **Efficiency:** >88% with resistive load
- **Input Connection:** C14
- **Input Nominal Voltage:** 230V default (200/208/220/230/240V)
- **Input Voltage Range:** 50/60 Hz
- **Nominal Frequency:** 160-276V
- **Input Frequency Range:** 45-65 Hz
- **Input Power Factor:** 0.90
- **Receptacle:** (8) C13, (1) C19
- **Output Power Factor:** .9
- **Output Waveform:** Sine wave
- **Output Voltage Range:** $\pm 2\%$ steady-state



- **[ETIM] Number of Output Connections C13:**
8
- **[ETIM] Number of Output Connections C19:**
1
- **[ETIM] Max Volt Dist Output(Linear Load):**
<3%
- **Battery Management:** ABM technology
- **Batteries Replacement:** Hot-swappable
internal batteries and extended battery modules
(EBMs)
- **Battery Rating:** (8) 12V, 9 Ah
- **Battery Type:** 96 Vdc, (8) 12V, 9 Ah
- **Communication:** (1) USB, (1) RS-232 serial
- **Expansion Slots:** BD slot optional
- **User Interface:** Graphical display, 4-button
programmable menu
- **Altitude:** 3000m
- **BTU Rating:** Online: 838, Battery: 1348
- **Noise Level:** <50 dB
- **Relative Humidity:** 5-90% non-condensing
- **Temperature Range:** 0° to 40°C (32° to 104°F)

Supporting documents:

- [Product and Service Catalog](#)
- [Product Data Sheet - PW9130I2000T-XL](#)

Certifications:

- IEC Rated
- EN 62040-2:2006

Product compliance:

- Fulfills all EMC immunity requirements
- CE Marked
- GS