



Powering Business Worldwide

pe.eaton.com

Eaton 9130 UPS

PW9130L1500T-XL

UPC:790341052737

Dimensions:

- **Height:** 9.1 IN
- **Length:** 16.9 IN
- **Width:** 6.3 IN

Weight:41.9 LB

Notes:Thermal protection switches load to bypass in case of overheating, Allows UPS operation without utility input

Warranties:

- 2 year limited factory

Specifications:

- **Type:** UPS
- **Topology:** Online/Double-conversion
- **Form Factor:** Tower
- **Color:** Black
- **VA Rating:** 1500 VA
- **Wattage:** 1350 W
- **Package Contents:** 1 ready-to-go UPS|Software suite CD|USB cable|User guide|Quick start instructions|Cord-retention brackets
- **Efficiency:** 86
- **Input Connection:** 5-15P
- **Input Cord Length:** 6 ft
- **Input Nominal Voltage:** 120V default (100/110/120/127V)
- **Input Frequency Range:** 45-65 Hz
- **Input Power Factor:** 0.9
- **Receptacle:** (6) 5-15R
- **Output Waveform:** Sine wave
- **Voltage:** 120V
- **Output Voltage Range:** $\pm 2\%$ steady-state



- **Output Frequency:** 50/60 Hz
- **Runtime Graph:** View runtime graph
- **Max Number of Battery Packs:** 4
- **Battery Management:** ABM technology (3-stage charging extends battery service life by 50% and provides advance warning for battery replacement)
- **Batteries Replacement:** Hot-swappable internal batteries and extended battery modules (EBMs)
- **Battery Rating:** (4) 12V, 9 Ah
- **Battery Type:** Sealed, lead-acid
- **Extended Battery Capability:** Add up to 4 extended battery modules (EBM). Part number PW9130N1500T-EBM
- **Standard Factory Warranty:** 2-YEAR FACTORY WARRANTY|-2 years|-Parts, electronics, and batteries coverage|-Standard ground shipping|-Technical support
- **Extended Service Plans:** ADVANCED DEPOT EXCHANGE|-5-year depot repair: 9SW5Y-1000UC|-Expedited parts coverage for 5 years|-Parts, electronics and UPS batteries coverage|-Next business day shipping|-Technical support||ON-SITE 24X7, NEXT DAY RESPONSE|2 YEAR UPGRADE: WUN72XXX-2509UC|-On-site expedited parts and labor coverage for first 2 years|-Parts, electronics and UPS batteries coverage|-Eaton on-site labor coverage|-24x7 coverage, next day response|-Next day shipping|-Technical support||3 YEAR FLEX PLAN: FLN73XXX-2509UC|-On-site parts and labor coverage for years 3 to 5|-Parts, electronics and UPS batteries coverage|-24x7 on-site labor coverage, next day response|-Next day shipping|-Technical support
- **Communication:** Best Dock Slot + 1 USB port + 1 serial RS232 port + 1 mini-terminal block for remote power off + 1 mini-terminal block for output relay Communication slot
- **Expansion Slots:** Yes
- **User Interface:** Graphical display, 4-button programmable menu
- **Altitude:** <3000m for nominal power, -5°C temp derating every 500m
- **BTU Rating:** Online: 750, Battery: 1011
- **Noise Level:** <50 dB at 1 meter

- **Relative Humidity:** 5-90% non-condensing
- **Temperature Range:** 0° to 40°C (32° to 104°F)

Supporting documents:

- [Eaton 9130 UPS tower brochure](#)
- [Eaton 9130 tower UPS end-of-life announcement](#)
- [Eaton 9130 700-3000 VA UPS user guide](#)

Certifications:

- VCCI
- UL Listed
- EN 55022
- cUL Listed
- cULus Listed
- NOM

Product compliance:

- FCC Class B
- EN55022 Class B