

## 9130 Rackmount UPS

PW9130L700R-XL2U

UPC:790341052508

**Dimensions:** 

Height: 3.4 INLength: 17.7 INWidth: 17.2 IN

Weight:35.3 LB

Notes: Allows UPS operation without utility input

Warranties:

· 2 year limited factory

**Specifications:** 

 Accessories: User Guide, Quick Start Instructions, Cord-Retention Brackets

 Battery Type: VRLA, Hot-swappable internal, EBM

• Efficiency: >95% in high-efficiency mode, >86% in online mode

• Frequency Rating: 50-60 Hz

• Humidity: 5-90% non-condensing

• Input: (1) 5-15P

• Operating Temperature: 0° to 40°C

• Output: 5-15R

Topology: Online Double Conversion
User Interface: Graphical LCD with blue backlight and text in English, French, German, Russian and Spanish

• Volt Ampere Rating: 700 KVA

• Cable Type: USB Cable

• Color: Black

• Runtime: 32 min full load, 14 min half load

• Wattage: 630W

Battery Rating: 12V/9 AhConfiguration: Rackmount



• Nominal Ac Current: 5.8A

• Orientation: 2U

• Serial Interface: RS-232, USB

• Software: Intelligent Power Software Suite

## **Supporting documents:**

- Product and Service Catalog
- Product Data Sheet PW9130L700R-XL2U

## **Certifications:**

- VCCI
- cUL Listed
- UL Listed
- EN 55022

## **Product compliance:**

• FCC Class B

\_\_\_\_\_

© 2016 Eaton. All rights reserved.