

SmartPro 120V 1.05kVA 705W Line-Interactive UPS, Tower, USB, 6 Outlets

SUPPORT

RUNTIMES

SOFTWARE

PDF

Protects connected mission-critical equipment against damage, downtime and data loss due to blackouts, brownouts, power surges and line noise. Ideal solution for data centers, VoIP systems, points of sale and network closets.

- Corrects under- and overvoltages from 75V to 147V
- 6 NEMA 5-15R outlets
- Front-panel LEDs indicate load, power and battery statuses
- Monitoring of power conditions via PowerAlert®
- 23 min. runtime at half load; 8 min. at full load
- 2-year warranty, 3 year with registration. Note: [Registration is required](#) for 3-year warranty.
- [Ultimate Lifetime Insurance](#)

[View Full Product Details](#)

Tripp Lite Part Number

SMART1050

1 Review

Extended Warranty Options

- 1-Year ([WEXT1D](#))
- 2-Year ([WEXT2D](#))

[Add to Compare](#)
[Add to List](#)


Have a Question?

[Contact Us](#)

[SEE ALL IMAGES](#)

Customers Who Viewed This Product Also Considered



BCPRO1050

BC Pro 120V
1050VA 705W
Standby UPS, T...

(4)



BCPRO600

BC Pro 120V 600VA
345W Standby
UPS, To...



INTERNETOFFICE500

Internet Office
120V 500VA 280W
Standb...

(5)



INTERNETOFFICE700

Internet Office
120V 700VA 425W
Standb...

(6)



OMNISMART500

OmniSmart 120V
500VA 300W Line-
Interac...

(1)



SMART550USB

SmartPro 120V
550VA 300W Line-
Interact...

(6)



SMART750USB

SmartPro 120V
750VA 450W Line-
Interact...

(4)

[Features](#)
[Specifications](#)
[Accessories](#)
[Resources & Downloads](#)
[Technical Support](#)

Overview

The SMART1050 SmartPro 120V 1.05kVA 705W Line-Interactive UPS provides battery backup and AC power protection against blackouts, brownouts, power surges and line noise that can damage electronics or destroy data. Ideal for backing up data centers, VoIP systems, points of sale and network closets, the SMART1050 switches to 1.05kVA/705W battery mode in milliseconds to keep your connected equipment running long enough to save files and shut down safely with no data loss.

Featuring six NEMA 5-15R outlets and a six-foot power cord with 120V NEMA 5-15P input, the SMART1050 has an internal battery that provides 23 minutes of support at half load and eight minutes at full load. Front-panel LEDs indicate line power, battery power, overload, voltage regulation and battery

status. An alarm sounds to indicate power failure or a low battery.

Automatic voltage regulation (AVR) maintains 120V nominal output over an input range of 75V to 147V without using battery power. EMI/RFI noise filtering improves your equipment's performance and prevents damage. A 480-joule surge suppression rating protects your equipment from harmful power surges. With Tripp Lite's PowerAlert software, available via free download, the SMART1050 enables safe unattended system shutdown and file saves in case of a prolonged power failure.

Features

Protects Mission-Critical Equipment

- Provides fully regulated AC output for servers, network storage devices and telecom hardware
- Audible alarm signals loss of utility power or low battery
- 6 NEMA 5-15R outlets
- 6 ft. power cord with 120V NEMA 5-15P input
- 480-joule surge suppression rating

Reliable Battery Backup

- Supports half load up to 23 min. and full load up to 8 min.
- Internal batteries designed for hot-swap field replacement
- 96% line-power efficiency rating saves money in energy costs
- Cold-start capability enables turn-on in battery mode during blackouts

Automatic Voltage Regulation (AVR)

- Maintains 120V nominal output over input range of 75V–147V without using battery power

EMI/RFI Line Noise Filtering

- Removes electromagnetic and radio frequency interference that can disrupt or damage equipment's performance

LED Indicators

- Front-panel LEDs signal indicate line power, battery power, overload, voltage regulation and battery status

USB Communication Port

- USB port combines with PowerAlert software (available via free download at www.tripplite.com/poweralert) to enable safe unattended system shutdown and file saves in case of a prolonged power failure
- Supports messaging of UPS and line power status, including voltage and battery capacity

Small-Footprint Tower Housing

- Uses less than 53 sq. in. of floor or desktop space
- Mounts on wall with optional UPSWM accessory

Package Includes

- SMART1050 SmartPro 120V 1.05kVA 705W Line-Interactive UPS
- USB cable
- Owner's manual



Specifications

OVERVIEW

| | |
|----------|------------------|
| UPC Code | 037332033802 |
| UPS Type | Line-Interactive |

INPUT

| | |
|------------------------------------|---------------------|
| Rated input current (Maximum Load) | 6.7A |
| Nominal Input Voltage(s) Supported | 120V AC |
| UPS Input Connection Type | 5-15P; Right-Angled |
| Input Circuit Breakers | 12A |
| UPS Input Cord Length (ft.) | 6 |
| Recommended Electrical Service | 15A 120V |
| Input Phase | Single-Phase |
| Input Cord Length (ft.) | 6 |

OUTPUT

| | |
|--|-------------------------------------|
| Output Volt Amp Capacity (VA) | 1050 |
| Output kVA Capacity (kVA) | 1.05 |
| Output Watt Capacity (Watts) | 705 |
| Nominal Voltage Details | 120v nominal output in battery mode |
| Frequency Compatibility | 60 Hz |
| Output Voltage Regulation (Line Mode) | -18%, +8% |
| Output Voltage Regulation (Battery Mode) | +/- 5% |
| Output AC Waveform (AC Mode) | Sine wave |
| Output AC Waveform (Battery Mode) | PWM sine wave |
| Nominal Output Voltage(s) Supported | 110V; 115V; 120V |
| Output Receptacles | (6) 5-15R |
| Individually Controllable Load Banks | No |

| | |
|--------------------------|----------------|
| Full Load Runtime (min.) | 8 min. (705w) |
| Half Load Runtime (min.) | 23 min. (355w) |
| | |

| | |
|---|---------------|
| UPS AC Suppression Joule Rating | 480 |
| UPS AC Suppression Response Time | Instantaneous |
| EMI / RFI AC Noise Suppression | Yes |
| What protects against radio frequency on Joule | 480 |
| can stop. from surge protector. sion for the...time | Instantaneous |
| react to a surge, for the response time, deal. | |

| | |
|---|---|
| Installation Form Factors Supported with Included Accessories | Tower |
| Installation Form Factors Supported with Optional Accessories | Wallmount (UPSWM - tower mounting kit) |
| Primary Form Factor | Tower |
| Primary UPS Depth (mm) | 183 |
| Primary UPS Height (mm) | 300 |
| Primary UPS Width (mm) | 183 |
| Shipping Dimensions (hwd / in.) | 15.60 x 10.60 x 10.70 |
| Shipping Weight (lbs.) | 33.00 |
| UPS Housing Material | Polycarbonate |
| UPS Power Module Dimensions (hwd, in.) | 11.8 x 7.2 x 7.2 |
| UPS Power Module Weight (kg) | 13.15 |
| UPS Power Module Weight (lbs.) | 29 |

ENVIRONMENTAL

| | |
|---------------------------------------|--|
| Operating Temperature Range | +32 to +104 degrees Fahrenheit / 0 to +40 degrees Celsius |
| Storage Temperature Range | +5 to +122 degrees Fahrenheit / -15 to +50 degrees Celsius |
| Relative Humidity | 0 to 95%, non-condensing |
| AC Mode Efficiency Rating (100% Load) | 96% |

COMMUNICATIONS

| | |
|-------------------------------------|---|
| Network Monitoring Port Description | Supports detailed monitoring of UPS and site power conditions |
| PowerAlert Software | For local monitoring via the UPS's built-in USB port, download PowerAlert Local software at http://www.tripplite.com/poweralert |

| | |
|--|--|
| DC System Voltage (VDC) | 18 |
| Battery Recharge Rate (Included Batteries) | Less than 4 hours from 10% to 90% (typical, full load discharge) |
| Internal UPS Replacement Battery Cartridge | RBC52 (quantity 3) |
| Battery Access | Battery access door |
| Battery Replacement Description | Hot-swappable, user replaceable batteries |
| Expandable Runtime | No |

VOLTAGE REGULATION

| | |
|---|--|
| Voltage Regulation Description | Automatic voltage regulation (AVR) maintains line power operation with an input voltage range of 75 to 147 |
| Overvoltage Correction ? | Input voltages between 128 and 147 are reduced by 12% |
| Undervoltage Correction ? | Input voltages between 93 and 107 are boosted by 14% |
| Low Voltage Correction ? | Input voltages between 75 and 92 are boosted by 30% |

USER INTERFACE, ALERTS & CONTROLS

| | |
|------------------------|---|
| Switches | 2 Switches control off/on power status and alarm-cancel/self-test operation |
| Alarm Cancel Operation | Power-fail alarm can be silenced using alarm-cancel switch; once silenced, alarm will re-sound to indicate low-battery status |
| Audible Alarm | Audible alarm indicates power-failure and low-battery conditions |
| LED Indicators | 5 LEDs indicate line power, battery power, overload, voltage regulation and battery low/replace status |

SURGE / NOISE SUPPRESSION

| | |
|--|--|
| | |
|--|--|

| | |
|--------------------------|---|
| Communications Cable | USB cable included |
| WatchDog Compatibility | Supports Watchdog application, OS and hard-reboot restart options for remote applications |
| Communications Interface | USB |

LINE / BATTERY TRANSFER

| | |
|---|------------------|
| Transfer Time ? | 2-4 milliseconds |
| Transfer to Battery Power (Setpoint) | 75 |
| High Voltage Transfer to Battery Power (Setpoint) | 147 |

SPECIAL FEATURES

| | |
|---|---|
| Cold Start (Startup in Battery Mode During a Power Failure) | Cold-start operation supported |
| High Availability UPS Features ? | Hot swappable batteries |
| Energy Saving | Greater than 95% efficiency - GREEN UPS |

STANDARDS & COMPLIANCE

| | |
|--------------------|--|
| UPS Certifications | Tested to UL1778 (USA); Tested to CSA (Canada); Tested to NOM (Mexico); Meets FCC Part 15 Category B (EMI) |
|--------------------|--|

WARRANTY

| | |
|--|--|
| Product Warranty Period (Worldwide) | 2-year warranty, 3 year with registration. Note: Registration is required for 3-year warranty. |
| Connected Equipment Insurance (U.S., Canada & Puerto Rico) | Ultimate Lifetime Insurance |

Review Snapshot by PowerReviews

★★★★★ 1 Review [Write a Review](#)

Reviewed by 1 customer Most Recent

★★★★★ **GREAT PRODUCT**

THIS WAS A GREAT PURCHASE RECOMMENDED TO ALL COLLEAGUES!

Bottom Line Yes, I would recommend to a friend

Was this review helpful to you?

1 0

Submitted 7 years ago
By shahine1
From Undisclosed

Services

Installation

[Compare](#)

| Part Number | Description |
|-----------------------|---|
| W01-INSTAL-B50 | On-Site UPS Installation Service, Select 1-3 kVA UPS, Under 50 lb., USA, Normal Business Hours |
| W01-INSTAL-E50 | On-Site UPS Installation Service, Select 1-3 kVA UPS, Under 50 lb., USA, Outside Business Hours |




Extended Warranty

[Compare](#)





| Part Number | Description |
|---------------|---|
| WEXT1D | 1-Year Extended Warranty and Technical Support for Select Tripp Lite Products – Includes UPS Battery Coverage if Applicable |
| WEXT2D | 2-Year Extended Warranty and Technical Support for Select Tripp Lite Products – Includes UPS Battery Coverage if Applicable |

Resources & Downloads






DOCUMENTATION

- [SMART1050 runtime chart](#) 
- [Free 1-Year Warranty Extension with Registration](#) 
- [Owner's Manual for SmartPro/SmartPro XL UPS](#) 


PRODUCT LITERATURE

- [UPS Systems 120V Brochure \(English\)](#) 
- [Integrated Solutions Brochure \(English\)](#) 
- [Common Power Problems and Power Protection Solutions White Paper 120v \(English\)](#) 
- [Common Power Problems and Power Protection Solutions White Paper 230v \(English\)](#) 

USEFUL WEB PAGES

- [UPS Systems Buying Guide](#) 
- [Custom Products from Tripp Lite Are One Call Away](#) 
- [Economy Mode Explained](#) 
- [Top 12 Questions to Consider When Choosing UPS Systems for Network/Server Applications](#) 
- [UPS Sizing](#) 

PRODUCT IMAGES

- [Download images for this product](#) 



Do you own a
SMART1050

Get support for your product all in
one place!

[GO TO MODEL SUPPORT](#) 

Recently Viewed



How can we improve the information on this page?

Is an important specification missing? Did you spot an error? Please [let us know](#) how we can make this information more useful to you.

| COMPANY | PRODUCTS | APPLICATIONS | WHERE TO BUY | SUPPORT | RESELLERS |
|--|------------------------------------|---------------------------------|------------------------------------|--------------------------------------|----------------------------------|
| Company Overview | Current Promotions | Healthcare | Find a Reseller | Product Support | Reseller Support |
| Company History | Product Catalog | Education | Find a Distributor | Downloads | Cross Reference |
| Careers | Products A-Z | Government/TAA | | Product Warranties | Partner Program |
| Newsroom | New Products | Digital Signage | | Product Registration | Online Training |
| Media Relations | Buying Tools | | | Returns | |
| Blog | Buying Guides | | | Support Contact | |
| Feedback & Inquiries | Resource Center | | | | |



TRIPP LITE
1111 West 35th Street
Chicago, Illinois 60609
United States

☎ [+1 \(773\) 869-1111](#)
(main)
☎ [+1 \(773\) 869-1774](#)
(sales)
☎ [+1 \(773\) 869-1234](#)
(support)
✉ [Email Us](#)

ABOUT TRIPP LITE

From desktop to critical infrastructure, Tripp Lite products and solutions power and connect the computers, networking equipment and electronic devices that form the foundation of our digital world. Headquartered in Chicago since 1922, Tripp Lite has offices and partners worldwide.

[NEWSLETTER SIGN-UP](#)



This Site Uses Cookies

We use cookies to personalize content and to analyze our traffic. We also share information about your use of our site with advertising and analytics partners. To find out more about how we use cookies, see our [cookie policy](#).

[I Accept Cookies](#)

[More Information](#)

