


# Detachable redundant PDU option for select SmartOnline UPS - Hardwired input / L6-30R, C19 output

MODEL NUMBER: SUPDMB20K



## Description

SUPDMB20K combines the output of two compatible SU8000RT3UPM or SU10000RT3UPM UPS power modules for fault-tolerant N+1 or increased capacity configurations. Manual bypass feature enables hot-swappable replacement of both power modules with no disruption in power to connected equipment. (IMPORTANT > compatible only with SU8000RT3UPM and SU10000RT3UPM power modules built after 6/2010 with built-in USB and PARALLEL back panel data connections).

## Features

<p> </p>

## Specifications

OVERVIEW	
UPC Code	037332153975
Accessory Type	PDU Module
Accessory Class	UPS Accessories
INPUT	
Nominal Input Voltage(s) Supported	200V AC; 208V AC; 230V AC; 240V AC; 220V AC
Input Connection Type	Hardwire
Voltage Compatibility (VAC)	200; 208; 230; 240; 220
OUTPUT	
Frequency Compatibility	50 / 60 Hz

## Highlights

- Converts compatible SmartOnline 8 and 10kVA high-voltage UPS configurations for N+1 redundancy or increased capacity when used along with a 2nd compatible UPS power module
- Manual bypass feature enables hot-swappable replacement of both power modules while connected equipment runs uninterrupted
- Hardwired input / L6-30R and C19 output connections

## System Requirements

- For use only with configurations involving two compatible SU8000RT3UPM or SU10000RT3UPM power modules (requires two of the same model power module built after 6/2010 originally shipping with built-in USB and PARALLEL back panel data connections)

## Package Includes

- SUPDMB20K parallel PDU
- Parallel cable
- Owner's Manual



Powering Business Worldwide



Output Receptacles	(8) C19; (2) L6-30R
Output Nominal Voltage	200-240VAC
Overload Protection	2 double pole 30A breakers, 8 double pole 20A breakers
<b>PHYSICAL</b>	
Material of Construction	Metal
Shipping Dimensions (hwd / in.)	11.10 x 12.80 x 23.50
Shipping Dimensions (hwd / cm)	28.19 x 32.51 x 59.69
Shipping Weight (lbs.)	20.00
Shipping Weight (kg)	9.07
Unit Dimensions (hwd / in.)	20.540 x 6.960 x 4.490
Unit Dimensions (hwd / cm)	52.1 x 17.8 x 11.4
Unit Weight (lbs.)	14.52
Unit Weight (kg)	6.59
<b>FEATURES &amp; SPECIFICATIONS</b>	
IP68 Rated	No
IP20 Rated	No
<b>STANDARDS &amp; COMPLIANCE</b>	
Product Certifications	CSA (Canada); IEC/EN 62040; UL 1778
Product Compliance	RoHS; CE (Europe); REACH; FCC (USA)
<b>WARRANTY &amp; SUPPORT</b>	
Product Warranty Period (Worldwide)	2-year limited warranty

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2024 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.