



# **UPS Maintenance Bypass Panel for SUT20K - 3 Breakers**

MODEL NUMBER: SUT20KMBP









This bypass panel isolates an SUT20K 3-Phase UPS system from connected loads during maintenance.

### **Features**

Bypass an SUT20K UPS to Perform MaintenanceFor use with the SUT20K 3-phase UPS system, the SUT20KMBP maintenance bypass panel (MBP) maintains total continuity of power to connected load circuits when bypass of the UPS is required for regular service and maintenance. This UPS maintenance bypass panel has three 4-pole circuit breakers for Input, Bypass and Output. The breakers have removable handles to allow the panel's trim cover to be removed for internal access. The short circuit rating is 10 kAIC. Maximum current capacity is 80A.

**Convenient Wall-Mount Installation**Made of galvanized steel, the service bypass panel has rear mounting holes for installation on a smooth and solid wall (mounting hardware not included).

**One-Year Warranty**The SUT20KMBP is backed by a one-year limited warranty, ensuring reliability and performance.

## **Highlights**

- Isolates a SUT20K UPS from connected loads to permit maintenance
- Allows connected loads to remain continuously powered
- Three built-in 4-pole circuit breakers for Input, Bypass and Output
- Mounting holes for convenient wall installation
- Maximum current capacity is 80A

# **Applications**

 Bypass an SUT20K UPS system to perform maintenance

#### Package Includes

- SUT20KMBP UPS Maintenance Bypass Panel for SUT20K
- Installation and Operation Manual

# **Specifications**

OVERVIEW		
UPC Code	037332222343	
Accessory Type	Bypass Panel	
Accessory Class	UPS Accessories	
INPUT		
Nominal Input Voltage Description	208Y/120 VAC 3 phase, 4 wire (3P+N+E)	
ОИТРИТ		
Output Capacity Details	80A maximum	





PHYSICAL		
Form Factors Supported	Wallmount	
Shipping Dimensions (hwd / in.)	10.00 x 22.00 x 25.00	
Shipping Weight (kg)	12.70	
Unit Dimensions (hwd / in.)	17.500 x 20.000 x 4.600	
Unit Dimensions (hwd / cm)	44.45 x 50.8 x 11.68	
Unit Weight (lbs.)	28	
Unit Weight (kg)	12.70	
STANDARDS & COMPLIANCE		
Product Compliance	RoHS	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	1-year limited warranty	

1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark. All other trademarks

are the property of their respective owners.