

# TAA-Compliant Protect It! 6-Outlet Surge Protector, 6-ft. Cord, 1080 Joules, Ethernet Protection, Safety Covers

MODEL NUMBER: TLP66NETAA



## Highlights

- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases
- 6 outlets / 6-ft cord
- 1080 joule rating
- Ethernet Surge protection

## Package Includes

- TLP66NETAA
- 6-ft. network cable
- Instruction manual with warranty information

## Description

Tripp Lite's TLP66NETAA is compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases. It has 6 outlets, a 6-ft. cord and diagnostic LEDs. The TLP66NETAA has a surge suppression rating of 1080 joules to handle the strongest surges. Built-in RJ45 jacks prevent surges from damaging your network equipment (6ft network cable included). \$25,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only).

## Features

- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases
- 6 outlets with integrated child safety covers
- 6ft cord
- Built-in RJ45 jacks prevent surges from damaging your network equipment (6ft. network cable included)
- Surge suppression rating: 1080 joules
- EMI/RFI noise filtering
- Can accommodate up to 2 transformers without blocking remaining outlets
- Diagnostic LEDs indicate protection present & ground present
- Keyhole supports for wall mounting
- Lighted power switch
- \$25,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only)

## Specifications

| OVERVIEW |              |
|----------|--------------|
| UPC Code | 037332161123 |



Powering Business Worldwide

**TRIPP-LITE**  
by **EAT•N**

| INPUT                              |                                                                                           |
|------------------------------------|-------------------------------------------------------------------------------------------|
| Nominal Input Voltage(s) Supported | 120V AC                                                                                   |
| Recommended Electrical Service     | 120V (110-125V)                                                                           |
| Input Cord Gauge Type              | 14 gauge; SJT                                                                             |
| Voltage Compatibility (VAC)        | 120                                                                                       |
| Input Plug Type                    | NEMA 5-15P                                                                                |
| Input Cord Length (ft.)            | 6                                                                                         |
| Right-Angle Plug                   | No                                                                                        |
| Input Cord Length (m)              | 1.83                                                                                      |
| Integrated Cord Clip               | No                                                                                        |
| OUTPUT                             |                                                                                           |
| Frequency Compatibility            | 60 Hz                                                                                     |
| Output Receptacles                 | (6) 5-15R                                                                                 |
| Circuit Breaker (amps)             | 15                                                                                        |
| Overload Protection                | 15A resettable illuminated combo switch / circuit breaker                                 |
| Transformer Accommodation          | (4) Yes                                                                                   |
| Outlet Orientation                 | Block style with two rows of 3 outlets                                                    |
| Right-Angle Outlets                | Yes                                                                                       |
| USER INTERFACE, ALERTS & CONTROLS  |                                                                                           |
| Diagnostic LED(s)                  | Yes                                                                                       |
| Switches                           | Combination AC circuit breaker and 2-position red illuminated on/off power switch         |
| Diagnostic LED Details             | Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status |
| SURGE / NOISE SUPPRESSION          |                                                                                           |
| AC Suppression Joule Rating        | 1080                                                                                      |
| AC Suppression Response Time       | < 1 ns                                                                                    |
| Protection Modes                   | Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression        |
| UL1449 Let Through Rating          | 400v                                                                                      |
| EMI / RFI Filtering                | Up to 40 dB                                                                               |
| Automatic Shut-Off                 | No                                                                                        |
| DATALINE SURGE SUPPRESSION         |                                                                                           |
| Cable (Coax) Protection            | No                                                                                        |
| Network (Ethernet) Protection      | Yes                                                                                       |
| Telephone/DSL Protection           | No                                                                                        |



Powering Business Worldwide



| PHYSICAL                                                   |                                                                                                                                  |
|------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| Color                                                      | Light Gray                                                                                                                       |
| Material of Construction                                   | Plastic                                                                                                                          |
| Power Cord Color                                           | Light Gray                                                                                                                       |
| Mounting Holes or Slots                                    | Yes                                                                                                                              |
| Receptacle Color                                           | Gray                                                                                                                             |
| Shipping Dimensions (hwd / in.)                            | 6.90 x 2.00 x 11.10                                                                                                              |
| Shipping Dimensions (hwd / cm)                             | 17.53 x 5.08 x 28.19                                                                                                             |
| Shipping Weight (lbs.)                                     | 1.80                                                                                                                             |
| Shipping Weight (kg)                                       | 0.82                                                                                                                             |
| Unit Dimensions (hwd / in.)                                | 1.500 x 4.230 x 8.290                                                                                                            |
| Unit Dimensions (hwd / cm)                                 | 3.81 x 10.74 x 21.06                                                                                                             |
| Unit Weight (lbs.)                                         | 1.32                                                                                                                             |
| Unit Weight (kg)                                           | 0.60                                                                                                                             |
| FEATURES & SPECIFICATIONS                                  |                                                                                                                                  |
| Rotatable Outlets                                          | No                                                                                                                               |
| Antimicrobial                                              | No                                                                                                                               |
| WARRANTY & SUPPORT                                         |                                                                                                                                  |
| Product Warranty Period (Worldwide)                        | Lifetime limited warranty                                                                                                        |
| Connected Equipment Insurance (U.S., Canada & Puerto Rico) | \$25,000&nbsp;<a class="insuranceLink" href="//www.tripplite.com/support/insurance-policy">Ultimate Lifetime Insurance</a>&nbsp; |

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2024 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.