

Wide input range 1:2
Case style: 2" x 1"

COMMERCIAL DC/DC Converters PWM - regulated

10 Watt / 15 Watt
Series: EW2

Electrical specifications:


Input voltage: wide 1:2
Input Pi-Filter: .
Output voltage accuracy: +/- 2%
Line regulation: +/- 1%
Load regulation: 10% to 100% FL Single +/-0,5%
Dual +/-1%

Efficiency: min. 75%
Output Ripple & Noise: typ. 100mVp-p
Short circuit protection: continuous
Operating temperature: -25°C to +85°C
Isolation voltage: min. 1600V DC
Five-sided metal shield

CAUTION: NO INPUT POLARITY CHANGE ALLOWED!

			10 Watt	15 Watt				10 Watt	15 Watt
Part - No. Single	Input Voltage	Output Voltage	Output Current	Output Current	Part - No. Dual	Input Voltage	Output Voltage	Output Current	Output Current
EW2-1205	12V DC	5V	2000mA	3000mA	EW2-1205D	12V DC	+/- 5V	+/-1000mA	+/-1500mA
EW2-1212	(9-18V)	12V	830mA	1250mA	EW2-1212D	(9-18V)	+/-12V	+/- 416mA	+/- 625mA
EW2-1215		15V	670mA	1000mA	EW2-1215D		+/-15V	+/- 333mA	+/- 500mA
EW2-2405	24V DC	5V	2000mA	3000mA	EW2-2405D	24V DC	+/- 5V	+/-1000mA	+/-1500mA
EW2-2412	(18-36V)	12V	830mA	1250mA	EW2-2412D	(18-36V)	+/-12V	+/- 416mA	+/- 625mA
EW2-2415		15V	670mA	1000mA	EW2-2415D		+/-15V	+/- 333mA	+/- 500mA
EW2-4805	48V DC	5V	2000mA	3000mA	EW2-4805D	48V DC	+/- 5V	+/-1000mA	+/-1500mA
EW2-4812	(36-72V)	12V	830mA	1250mA	EW2-4812D	(36-72V)	+/-12V	+/- 416mA	+/- 625mA
EW2-4815		15V	670mA	1000mA	EW2-4815D		+/-15V	+/- 333mA	+/- 500mA

Any other output voltages available



PIN CONNECTION:		
PIN	Single	Dual
1	+ Input	+ Input
2	- Input	- Input
3	+ Output	+ Output
4	NO PIN	Common
5	- Output	- Output

ALL DIMENSIONS IN MM (INCHES)
MILLIMETERS +/-0,5mm
(INCHES +/- 0,02")

Specification may be changed without notice
please contact office for verification

We can offer EMC - Filter
according to EN55011/22 Class B.