

TECHNICAL DATA

## 4x Telephoto Infrared Smart Lens RSE





## Product overview: 4x Telephoto Infrared Smart Lens RSE

View your target magnified 4 times more than a standard lens while staying on the ground or a safe distance away. A 4x telephoto lens can help identify a potential issue in your equipment, even when your target is as tiny and distant as a failed splice on a high electrical line or an overheated refractory on a tall flare stack.

- Avoid the hassle of sending in your camera to calibrate with the lens - with smart lenses you can just attach the lens to any compatible camera and start taking images.
- This lens includes a patent-pending lens attachment system that holds the lens securely in place, reducing lens wobble.
- Made of 100 % diamond-turned germanium with an engineered coating, the most efficient available material to transmit energy to the detector.

Compatible with RSE300, and RSE600.

## Specifications: 4x Telephoto Infrared Smart Lens RSE

Description		
IFOV (spatial resolution)	RSE600	0.24 mRad
	RSE300	0.48 mRad
Field of view	6.0° H x 4.5° V	
Focus distance	1.5 m (approximately 5 ft)	



**Fluke.** *Keeping your world up and running.®*

**Fluke Corporation**  
PO Box 9090, Everett, WA 98206 U.S.A.

**For more information call:**  
In the U.S.A. (800) 443-5853  
In Canada (800) 36-FLUKE  
From other countries +1 (425) 446-5500  
[www.fluke.com](http://www.fluke.com)

©2025 Fluke Corporation.  
Specifications subject to change without notice.  
02/2025

**Modification of this document is not permitted  
without written permission from Fluke  
Corporation.**