



Search...



My account

€0.00 *



FOX30-XM

9V / 3300mA, worldwide

Output voltage

9

Current

3300

Prices plus VAT **plus shipping costs**

Order number: 1898163

Availability:



Delivery time: Germany 2 - 3 working days, Europe 4 - 5 working days, worldwide 10 working days

1 Stück

Add to shopping cart >

> Do you have any questions concerning this product?

Compare Remember

Description

Accessories

32

Required Accessories

For the operation of this device you need a primary adapter and a secondary adapter . This can be found here:
[Primary adapters](#) and [Secondary adapters](#)

Product information "FOX30-XM"

FOX30-XM

IEC 60601-1 approved, ≤ 10µA leakage current, Protection class 2xMOPP, DOE 2016 ready, IP42 approved exchangeable plug system as additional accessories, Double Safety: Housing snapped & welded

Additional information

- **Output voltage:** 9
- **Family :** FOX30 medical
- **Current:** 3300
- **Means of Protection:** Input Output 2xMOPP, Input - Ground 1xMOPP
- **Gehäuse / Housing:** FOX30 medical
- **Output voltage tolerance:** ± 5%
- **Frequency:** 50 / 60
- **AC Input:** FRIWO interchangeable mains plug system: see Primary Adapters
- **Humidity:** 10% bis 95%
- **Working temperature:** 0°C - 45°C
- **MTBF:** 200.000h acc. MIL217F (based on calculations at 120Vac/60Hz & 230Vac/50Hz, ambient 25°C and 100% load) (The MTBF are theoretically determined values, which does not guarantee the lifetime of the product or of the electrolytic) h
- **Standard:** IEC/EN/UL60601-1 3.1 Edition
- **DC output:** Universal output plug system
- **Input voltage:** 100-240 V
- **Protection Class:** A
- **Spec.0 cover sheet FW-Type:** FW8030M/09
- **color:** black
- **Storage temperature**
: -40-70°C
- **leakage current:** ≤10 µA
- **Overload protection:** Yes
- **Over Voltage Protection:** Yes
- **Short Circuit protection:** Yes
- **Operating Altitude:** 3.000 m
- **Dimension:** 90x55x34 mm
- **Length:** 1830 mm
- **material:** PC-ABS
- **Inrush current:** <50
- **Storage Humidity:** 10-95%
- **Atmospheric pressure:** 70-106 kPa
- **Line Regulation:** ±1
- **Load Regulation:** ±4
- **Hold up Zeit:** >10ms(120V), >50ms (230V)
- **Approbations:** Europe, USA, Australia, Japan
- **Housing Flame Class:** UL 94 V0
- **IP Rotection rating:** IP40
- **Conducted and Radiated Emmisions:** EN55022, EN55011, FCC15, Class B, EN60601-1-2
- **Immunity**
: EN55024, EN60601-1-2
- **Harmonics:** EN61000-3-2
- **Flicker noise:** EN61000-3-3
- **ESD (contact/ air):** EN61000-4-2
- **Immunity against radiated field:** EN61000-4-3
- **ETF/ Burst:** EN61000-4-4
- **Surge:** EN61000-4-5
- **Immunity against conducted disturbances:** EN61000-4-6
- **Voltage dips:** EN61000-4-11
- **Immunity against magnetic field:** EN61000-4-8
- **Vibration:** Standard: IEC 60068-2-6, Frequency range : 10 – 500 Hz, Cross- over-frequency : 58 – 62 Hz, Displacement amplitude : 0.2mm, Peak acceleration : 3 g, Number of cycles: 10 per axis

Documents

Document	Action
Gebrauchsanleitung Medizingeräte Deutsch	
Instrucciones de uso Adaptadores de red DT150M,...	
Instruction Manual Power Supplies DT150M, FW...	
Istruzioni d'uso Alimentatori elettrici DT150M,...	
Liefervorschrift 1898163	
MANUAL DE INSTRUÇÕES Fontes de alimentação...	
Manuel d'utilisatio Blocs d'alimentation...	
Productinformation FOX 30 Medizin	
取扱説明書 電源装置 DT150M FW 7333SM, 7362M, 7401M,...	

Similar products

Customers also bought

Customers also viewed

Service hotline

Telephone assistance and advice at:

+49 2532 81-0

Mo-Fr, 9:00am - 5:00pm

Shop service

Contact
General Terms and Conditions
Payment / Dispatch
Return
Defective product

Information

About us
Data protection statement
Imprint
Newsletter
Site Map

Newsletter

Subscribe to the free Firwo newsletter and ensure that you will no longer miss any of our Firwo Onlineshop offers or news.

Zur Anmeldung

