



Adapter FSP025-DHAN2

DESCRIPTION

This product is a 25 watts AC to DC power supply intended for use in IPC systems that has a small wattage demands. This adapter operates at 90 to 264 VAC input voltage. The unit meets EN55022, EN55024 and FCC class B emission limits, and is designed for ITE application.

APPLICATION

Industrial Application

FEATURES

- Meet Energy Star EPS2.0/ErP lot 7
- Meet DOE Level VI
- High Altitude 5,000M
- High Reliability
- EMC Standard: EN55022 CLASS B / EN55024 CLASS B
- Over Current Protection
- Over Temperature Protection
- Over Voltage Protection

WATTAGE

Wattage: 25W

PRODUCT HIGHLIGHT

V-Output: 12V
O/P Current: 2.08A
Socket Type: C14

INPUT ELECTRICAL

Input Voltage: 90 ~ 264 V
Input Frequency: 47 ~ 63 Hz

OUTPUT ELECTRICAL

Single Output: 12 V/ 2.08 A



SAFETY STANDARD APPAOVAL



NO LOAD AND EFFICIENCY

No Load: 0.1 Watts

PROTECTION

Protection: OVP,OCP,OTP

ENVIRONMENTAL REQUIREMENTS

TEMP. Range: Storage : -25 to + 80 °C
Altitude : 5000 M
MTBF: 200,000 hours at typical load at 25°C ambient base on SR332

MECHANICAL

Dimension: 94mm(L) x 38.4mm(W) x 29.6mm(H)
LED Indicator: No
On/ Off Switch: No

This content is subject to change, please refer to specification for more detail.
FSP reserve the right to change the content without prior notice