



Adapter FSP060-D1BR4

DESCRIPTION

New thin, flexible 60W USB-C power supplies provide up to 20V at 3A

APPLICATION

Mobile Phones, Tablets, Automotive convenience ports, TV, Mass Storage, Expansion Ports, Laptops, Monitors, Payment terminal, Set-top boxes, Workstations

FEATURES

AC Input 100 to 240V AC, at 2A 47-63 Hz
Wide range of output voltages, up to 20V at 3A
Able to power devices up to 60 watts
The thinnest C6 adapter available today, only 92 x 77.3 x 25.4mm
Includes ground wire for safety
High power output density of up to 6.01 W/in³
Meets DoE level 6 standard for energy efficiency
C14 and C6 AC socket versions available
Full thermal and electrical safety protection
Elegant, simple, compact design

WATTAGE

Wattage: 60W

PRODUCT HIGHLIGHT

V-Output: 5, 9, 12, 15, 20
O/P Current: 3A
Socket Type: C6

INPUT ELECTRICAL

Input Voltage: 100 ~ 240 V
Input Frequency: 47 ~ 63 Hz
Input Current: 2A

OUTPUT ELECTRICAL

Single Output: 5 V / 3 A
Second Output: 9V / 3A
Third Output: 12V / 3A
Fourth Output: 15V / 3A
Output Accuracy: +/- 5%
Line Regulation: +/- 5%
Load Regulation: +/- 5%



SAFETY STANDARD APPROVAL



NO LOAD AND EFFICIENCY

No Load: 0.21 Watts
Efficiency: 88 %

PROTECTION

Protection: OVP, OCP, OTP, OPP

ENVIRONMENTAL REQUIREMENTS

MTBF: 300,000Hrs Min. Telcordia SR-332 Issue2 (25°C)

MECHANICAL

Dimension: 92mm(L) x 77.3mm(W) x 25.4mm(H)
LED Indicator: No
On/ Off Switch: No

This content is subject to change, please refer to specification for more detail.
FSP reserve the right to change the content without prior notice