



Pushing Performance
Since 1945

har-SAB M12/8/5p PAC 10m PVC



Image is for illustration purposes only. Please refer to product description.

| | |
|--------------------|---|
| Part number | 09 07 001 2225 0 |
| Specification | har-SAB M12/8/5p PAC 10m PVC |
| HARTING eCatalogue | https://b2b.harting.com/090700122250 |

Identification

| | |
|---------------|---|
| Series | Circular connectors M12 |
| Element | Distribution boxes |
| Specification | Pre-assembled master cable With LED green/yellow |

Version

| | |
|-----------------------|------------------------|
| Cable length | 10 m |
| Core structure | 3x AWG 18 + 16x AWG 22 |
| Total number of ports | 8 |
| Number of contacts | 5 |

Technical characteristics

| | |
|--|--------------------|
| Rated current | 9 A |
| Rated voltage | 10 V DC 30 V DC |
| Limiting temperature | -30 ... +85 °C |
| Degree of protection acc. to IEC 60529 | IP67 |
| Number of channels per port | 2 |
| Circuit logic | PNP |

Material properties

| | |
|------------------|-----------|
| Material (cable) | PVC |
| RoHS | compliant |
| ELV status | compliant |



Pushing Performance
Since 1945

Material properties

| | |
|--------------------------------------|---------------|
| China RoHS | e |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Not contained |
| California Proposition 65 substances | Yes |
| California Proposition 65 substances | Nickel |

Specifications and approvals

| | |
|----------|-------------------------|
| UL / CSA | UL 2238 CYJV.E500416 |
| | CSA-C22.2 CYJV7.E500416 |

Commercial data

| | |
|--------------------------------|---|
| Packaging size | 1 |
| Country of origin | China |
| European customs tariff number | 85371098 |
| GTIN | 5713140277328 |
| ETIM | EC002585 |
| eCl@ss | 27440108 Passive Sensor-Actuator-Interface (with cable) |