

# har-SAB M12/8/5p PAC 2m PVC



Part number	09 07 001 2225 3
Specification	har-SAB M12/8/5p PAC 2m PVC
HARTING eCatalogue	https://b2b.harting.com/090700122253

Image is for illustration purposes only. Please refer to product description.

#### Identification

Series	Circular connectors M12
Element	Distribution boxes
Specification	Pre-assembled master cable With LED green/yellow

#### Version

Cable length	2 m
Core structure	3x AWG 18 + 16x AWG 22
Total number of ports	8
Number of contacts	5

# **Technical characteristics**

Rated current	9 A
Rated voltage	10 V DC 30 V DC
Limiting temperature	-30 +85 °C
Degree of protection acc. to IEC 60529	IP67
Number of channels per port	2
Circuit logic	PNP

# Material properties

Material (cable)	PVC
RoHS	compliant
ELV status	compliant

Page 1 / 2 | Creation date 2024-07-05 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Customised Solutions GmbH & Co. KG | In der Tütenbeke 22 | 32339 Espelkamp | Germany Phone +49 5772 47-0 | info@HARTING.com | www.HARTING.com Product data sheet 09 07 001 2225 3 har-SAB M12/8/5p PAC 2m PVC



### Material properties

China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Yes
California Proposition 65 substances	Nickel

## Specifications and approvals

UL / CSA	UL 2238 CYJV.E500416 CSA-C22.2 CYJV7.E500416
Commercial data	
Packaging size	1
Country of origin	China
European customs tariff number	85444290
GTIN	5713140277366
ETIM	EC002585
eCl@ss	27440108 Passive Sensor-Actuator-Interface (with cable)