
Overview


HP ProLiant DL320e Generation 8 (Gen8) v2

Do you need an entry-level short-depth server utilizing the latest technology to keep you competitive?

The HP ProLiant DL320e Gen8 v2 Server is an entry-level single processor 1U short depth rack server specifically designed to give you the competitive edge you need. The server supports the latest Intel Xeon E3-1200 v3, PCIe 3.0 slots, DDR3 1600 MHz memory, and up to 8 TB internal storage, plus the state of the art HP iLO Management Engine.

It is ideal for small businesses, chain stores, telecommunications firms, or others that require a low-cost, compact server. The DL320e Gen8 v2 is versatile enough to handle a variety of workloads, including single/dedicated IT services such as networking, security, file/print, and web serving/hosting.





Front View:

- 1. Access Panel
- 2. Power Supply
- 3. Fan Assembly
- 4. PCI Riser Cage
- 5. Processor
- 6. DIMMS
- 7. Fan Assembly
- 8. Power On/Standby button and LED
- 9. UID LED button
- 10. Health LED
- 11. NIC status LED
- 12. 2 USB Connectors
- 13. Serial number/iLO information pull tab
- 14. Hard Drive Bays
- 15. Optical drive

Rear View:

- 1. Expansion slot 2, PCIe x8
- 2. Expansion slot 1, PCIe x16
- 3. Integrated Power Supply
- 4. T-10/T-15 Torx screwdriver
- 5. NIC1/shared iLO connector
- 6. Video Connector
- 7. NIC Connector 2
- 8. USB 3.0 Connector
- 9. iLO4 Connector
- 10. USB 3.0 Connector
- 11. NIC link LED
- 12. USB2.0 Connectors

What's New

- Latest 6G SATA Drives, 12G SAS Drives, and 6G SATA Solid State Drives
- New DirectFlow Three Phase UPS, Rack and Tower G4 models, and LCD8500 1U Rackmount SKU's

Standard Features

NOTE: For the Standard Features shipped in the "Factory Integrated Models", please see the "Configuration Information - Factory Integrated Models" section.

Processor

Entry Processors

One of the following depending on model

Intel® Pentium® G3240 (3.1GHz/2-core/3MB/54W) Processor Intel® Pentium® G3220 (3.0GHz/2-core/3MB/54W) Processor

NOTE: Intel ®Pentium® G3220 processor, performance for 1600MHz memory is clocked down to

1333MHz.

Intel® Pentium® G3420 (3.2GHz/2-core/3MB/54W) Processor

NOTE: Intel® Pentium® G3420 Processor supports up to 1600MHz DDR3 memory speeds.

Base Processors

NOTE: All support up to 1600MHz DDR3 memory speeds.

Intel® Core™ i3-4150 (3.5GHz/2-core/3MB/54W, HT) Processor Intel® Core™ i3-4130 (3.4GHz/2-core/3MB/54W, HT) Processor Intel® Core™ i3-4130T (2.9GHz/2-core/3MB/35W, HT) Processor

Performance Processors

NOTE: All support up to 1600MHz DDR3 memory speeds.

Intel® Xeon® E3-1220v3 (3.1GHz/4-core/8MB/80W)

Intel® Xeon® E3-1231v3 (3.4GHz/4-core/8MB/80W, HT)

Intel® Xeon® E3-1241v3 (3.5GHz/4-core/8MB/80W, HT)

Intel® Xeon® E3-1271v3 (3.6GHz/4-core/8MB/80W, HT)

Intel® Xeon® E3-1281v3 (3.7GHz/4-core/8MB/82W, HT)

Intel® Xeon® E3-1230v3 (3.3GHz/4-core/8MB/80W, HT)

Intel® Xeon® E3-1230Lv3 (1.8GHz/4-core/8MB/25W, HT)

Intel® Xeon® E3-1240v3 (3.4GHz/4-core/8MB/80W, HT)

Intel® Xeon® E3-1265Lv3 (2.5GHz/4-core/8MB/45W, HT)

Intel® Xeon® E3-1270v3 (3.5GHz/4-core/8MB/80W, HT)

Intel® Xeon® E3-1280v3 (3.6GHz/4-core/8MB/82W, HT)

NOTE: HT indicates that the processor model supports Intel® /Hyper-Threading Technology (depends on the processor).

NOTE: DDR3 speed is the maximum memory speed of the processor. Actual memory speed may depend on the quantity and type of DIMMs and CPU installed (options for 1600MHz, 1333MHz).

Cache Memory

One of the following depending on model 8MB (1x8MB) Level 3

NOTE: For Quad-core processors.

Chipset

Intel® C222 Series Chipset

NOTE: For more information regarding Intel® chipsets, please see the following URL:

http://www.intel.com/products/server/chipsets/.

Upgradeability

Up to 4 DIMM slots available for higher Memory capacity

Up to 4 bay SFF Hot plug Drive Cage; Or 2 bay LFF Hot plug or Non hot plug Drive Cages

2 PCIe 3.0 expansion slots

Optical Drive Bay

On System Management HP iLO (Firmware: HP iLO 4) **Processor**

NOTE: For more information, visit: http://www.hp.com/go/ilo.



Standard Features

| Memory Protection | ECC | | | | | |
|---------------------------------------|--|---|---|---|---|--------------|
| Memory | Туре | HP Sma | ırtMemory | | | |
| One of the following | | Unbuffe | ered (UDIMM) | | | |
| depending on model | DIMM Slots Avail | able 4 DIMM | s (2 Channels/ 2 | 2 DIMMs per chan | nel) | |
| | Maximum Capaci (UDIMM) | ity 32GB (4 | x 8GB@1600M | IHz) | | |
| | DL320e Gen8 Sei NOTE: To realize | the performance r | • | | document, HP Smar | tMemory is |
| | NOTE: Depending 1600MHz, or 133 | ww1.hp.com/prod g on the memory c | ucts/quickspec onfiguration an Memory Popula | s/14225_div/142 d processor mod ation Table or the | | • |
| Network Controller | http://h18000.w NOTE: Depending 1600MHz, or 133 at: http://www.h HP Ethernet 1Gb NOTE: The HP Pr | ww1.hp.com/prod g on the memory c 33MHz. Please see pp.com/go/ddr3me 2-port NC332i Ad | ucts/quickspec onfiguration an Memory Popula mory-configura apter 18 v2 server has | s/14225_div/142 d processor mod ation Table or the ator. | 25_div.html el, the memory spee | iguration To |
| | http://h18000.w NOTE: Depending 1600MHz, or 133 at: http://www.h HP Ethernet 1Gb NOTE: The HP Pr | yww1.hp.com/prod g on the memory c 33MHz. Please see ap.com/go/ddr3me o 2-port NC332i Ada roLiant DL320e Gei | ucts/quickspec onfiguration an Memory Popula mory-configura apter 18 v2 server has | s/14225_div/142 d processor mod ation Table or the ator. | 225_div.html el, the memory speed Online Memory Conf | iguration To |
| Network Controller Expansion Slots | http://h18000.w NOTE: Depending 1600MHz, or 133 at: http://www.h HP Ethernet 1Gb NOTE: The HP Pr server can be fur Expansion | ww1.hp.com/prod g on the memory c 33MHz. Please see p.com/go/ddr3me o 2-port NC332i Ad- roLiant DL320e Ger rther upgraded wit | ucts/quickspec onfiguration an Memory Popula mory-configura apter n8 v2 server has h various netwo | s/14225_div/142 d processor mod ation Table or the ator. s an embedded de orking products Connector | el, the memory speed Online Memory Conf | iguration To |
| | http://h18000.w NOTE: Depending 1600MHz, or 133 at: http://www.h HP Ethernet 1Gb NOTE: The HP Pr server can be fur Expansion Slots # | yww1.hp.com/prod g on the memory c 33MHz. Please see ap.com/go/ddr3me o 2-port NC332i Ad- roLiant DL320e Ger rther upgraded wit | ucts/quickspec onfiguration an Memory Popula mory-configura apter n8 v2 server has h various netwo Bus Width* | s/14225_div/142 d processor mod ation Table or the ator. s an embedded de orking products Connector Width | el, the memory speed Online Memory Confuel Memory Confuel Memory Confuel Form Factor Half-length, | iguration To |

HP ROM (Read Only Memory) is now digitally signed using HP's Corporate Signing Service. This signature is verified before the flash process starts, reducing accidental programming and preventing malicious efforts to corrupt system ROM.

HP ROM provides for essential initialization and validation of hardware components before control is passed to the customer-installed operating system. The ROM also provides the capability of booting from various fixed media (HDD, CD-ROM) and removable media (USB), to continue operation to the operating system.

HP ROM performs very early configuration of the video controller, to allow monitoring of initialization progress via an attached monitor. If configuration or hardware errors are discovered during this early phase of hardware initialization, suitable messages are now displayed on the connected monitor. Additionally, these configuration or hardware errors are logged to the Integrated Management Log (IML) to assist in diagnosis.

HP's ProLiant ROM is used to configure the following:

- Processor and chipset status registers
- System memory, memory map, and memory initialization
- System hardware configuration (Integrated PCI devices and optional PCIe cards).
- Customer-specific BIOS configuration (using the HP ROM-Based Setup Utility (RBSU).

NOTE: For further information, please refer to HP's RBSU (ROM based setup utility) user guide: http://www.hp.com/support/rbsu.



Standard Features

| Storage Control | ler |
|-------------------|------|
| One of the follow | ving |
| depending on mo | odel |

Base Models HP Dynamic Smart Array B120i Controller

NOTE: B120i has the following performance with regards to drive speed: 6Gb/s - in 2LFF and 4SFF only with port 0 & 1 installed; 3Gb/s - in 4SFF with more than 2 drives installed. For full 6 Gb.0/s speed a stand up card/smart

array controller must be used.

NOTE: B120i supports RAID 0/1/10 only. It does not have FBWC support so cannot support advanced RAID (5 onwards). For FBWC, a standup Smart

Array Controller card must be configured.

Performance Models HP Smart Array P222/512MB FBWC controller

NOTE: P222 can support RAID 0/1/10/5/50. More advanced options available

with Smart Array Advanced Pack 2.0.

NOTE: The DL320e Gen8 v2 can support other advanced controllers as well, depending on model and configuration

NOTE: For set up instructions for HP Smart Array B120i SATA Controller please refer to the HP ProLiant DL300 series server user quide.

NOTE: For general information about HP Smart Array B120i SATA RAID Controller, please visit: http://h18004.www1.hp.com/products/servers/proliantstorage/arraycontrollers/dynamicsmartarray

/index.html

Internal Storage Devices Diskette Drive

ette Drive None

Optical Drive Optional

DVD-RW

NOTE: Slim-type (9.5mm)

Hard Drives None ship standard (Base Models and Performance Models)

Hard Drive Bays 4 SFF drive bays or 2 LFF Non hot plug/Hot plug

NOTE: HP ProLiant DL320e Series servers offer both SFF, and LFF versions

in CTO. The Optical Drive bay is available with both models.

NOTE: LFF versions are not an upgradeable option from SFF models, or vice

versa, also between Non Hot Plug LFF and Hot Plug LFF.

NOTE: All Pre-configured Models come populated with some hard drive blanks installed. Should the customer need additional hard drive blanks, they can order more using either P/N 666987-B21: HP SFF Gen8 Hard Drive Blank Kit or P/N 666986-B21: HP LFF Gen8 Hard Drive Blank Kit. These part numbers for single HDD blanks below are also provided should the

customer require replacement HDD blanks for their server.

Maximum Internal Storage

| Hot Plug SFF SAS | 4.8TB | 4 x 1.2TB |
|-----------------------|--------|-----------|
| Hot Plug SFF SATA | 4.0TB | 4 x 1TB |
| Hot Plug LFF SAS | 8.0TB | 2 x 4TB |
| Hot Plug LFF SATA | 8.0TB | 2 x 4TB |
| Hot Plug SFF SAS SSD | 3.2 TB | 4 x 800GB |
| Hot Plug SFF SATA SSD | 3.2 TB | 4 x 800GB |
| Hot Plug LFF SATA SSD | 1.6 TB | 2 x 800GB |
| Non-Hot Plug LFF SATA | 6ТВ | 2 x 3TB |

Interfaces

Video 1 Rear standard video
HP iLO Remote 1Gb Dedicated

Port

Micro SD slot 1 Inter

Management Network

NOTE: The Micro SD slot is not a hot-pluggable device. Customers should



Standard Features

not attempt to plug a Micro SD card into the slot while the server is

powered

USB 2.0 Ports 5 total: 2 rear, 2 front, 1 internal (Optional)

USB 3.0 Ports 2 total: 2 rear

Industry Standard Compliance **ACPI 2.0b Compliant**

PCIe 3.0
PXE Support
WOL Support
USB 2.0 Compliant
USB 3.0 Compliant

Server Power Cords

All Pre-configured Models servers ship with a high voltage server to PDU power cord.

NOTE: HP ProLiant DL servers no longer ship standard with a 12-foot NEMA 5-15P to C13 power cords (227099-001) that allow connection to 110V US wall outlets in a home or office. ProLiant DL servers are primarily connected to PDU's in data center racks so they now ship standard with only a PDU 6-foot C-14 to C13 power cord (142258-001). If a user wishes to power a ProLiant DL server using a110V receptacle (NEMA-15), the 12-foot NEMA 5-15 to C13 power cord must be ordered separately. See Power Cords section for Worldwide Power Cord options.

Power Specifications

To review typical system power ratings use the HP Power Advisor which is available via the online tool located at URL: http://www.hp.com/go/proliant-energy-efficient or

http://www.hp.com/go/hppoweradvisor.

NOTE: Power Specification and Technical Content for supported power supplies can be found at:

http://h18000.www1.hp.com/products/quickspecs/14209_div/14209_div.html

Common Slot Power Supply

NOTE: The default power supply for DL320e Gen8 v2 server is a 250W Non Hot Plug, Non Redundant (ATX) power supply for all regions A Common Slot 48V DC power supply (750W, 94% efficiency) supporting NEBS compliance is available only for the 4 SFF configuration.

NOTE: Selecting the 750W power supply requires the HP DL320e Gen8 v2 CS FIO Enablement Kit

NOTE: Power Specification and Technical Content for supported power supplies can be found at: http://h18000.www1.hp.com/products/quickspecs/14209_div/14209_div.html

System Fans

2 front fan assemblies and 1 center fan assembly ship standard, non-redundant

Operating Systems and Virtualization Software Support for ProLiant Servers Microsoft Windows Server Canonical Ubuntu Server

Red Hat Enterprise Linux (RHEL)
SUSE Linux Enterprise Server (SLES)

VMware

NOTE: For more information on HP's Certified and Supported ProLiant Servers for OS and Virtualization Software and latest listing of software drivers available for your server including how to purchase from HP, please visit our OS Support Site at: http://www.hp.com/go/ossupport and our driver download page: http://www.hp.com/support/DL320eGen8v2.

Graphics

Integrated Matrox G200 video standard

1280 x 1024 (32 bpp)



Standard Features

1920 x 1200 (16 bpp)

HP iLO 4 On System Management Memory

- 16 MB Flash
- 256 MB DDR 3 with ECC (112 MB after ECC and video)

Form Factor

One of the following depending on model 1U Rack form factor 4 SFF Drive Bay Version:

1.7" (4.32cm) Height x 17.11" (43.46cm) Width x 15.07" (38.30cm) Length

2 LFF Drive Bay Version:

1.7" (4.32cm) Height x 17.11" (43.46cm) Width x 15.07" (38.30cm) Length

On System Management HP iLO Management

Engine

HP iLO Management Engine is a comprehensive set of embedded management features supporting the complete lifecycle of the server, from initial deployment, through ongoing management, to service alerting and remote support. HP iLO Management Engine comes standard on all HP ProLiant Gen8 servers. The HP iLO Management Engine portfolio includes:

- HP iLO: The HP iLO (Integrated Lights-Out) management processor is the core foundation for the HP iLO Management Engine
- HP Agentless Management: Provides built in server health monitoring and alerting capability without OS agents, that starts working the moment a power cord and an Ethernet cable are connected.
- **HP Active Health System:** Always on, continuous monitoring for increased stability and shorter downtimes; 100% configuration history; Health and service alerts and easy export and upload to Service and Support.
- HP Intelligent Provisioning: Lets customers provision and configure a single server without any separate media. No more SmartStart CDs or Smart Update Firmware DVD are needed.
 - To start Intelligent Provisioning:
 - Press the F10 key during the ProLiant Gen8 server boot process (also known as power on self-test or POST).
 - Please go to the Intelligent Provisioning website at http://www.hp.com/go/intelligentprovisioning for additional information and to view usage videos.
 - Use the Service Pack for ProLiant (SPP) at http://www.hp.com/go/spp to get firmware and software updates.
- HP iLO Mobile App: Enables the ability to access, deploy, and manage your server anytime from anywhere from select smartphones and mobile devices. For additional information please visit: http://www.hp.com/go/ilo/mobileapp

NOTE: For more information, visit: http://www.hp.com/go/ilo or HP iLO Management Engine technologies whitepaper

HP Insight Management HP Service Pack for

HP Service Pack for ProLiant (SPP) and HP Smart Update Manager (HP SUM)



Standard Features

ProLiant (SPP)

version 5 provide a new, comprehensive approach to firmware and system software maintenance. Together they provide better operating stability and ensure maximum uptime. The SPP will be updated at a predictable cadence, typically coinciding with new HP server hardware launches. By enabling all firmware to be updated online and integrating firmware and system software updates in one operation HP SUM and the SPP offer faster updates of individual servers and dramatically faster updates of entire BladeSystem enclosures. Further improving system uptime and stability is the fact that HP provides 12 months of support on each Service Pack for ProLiant.

The user experience around HP SUM and the SPP has been improved in several ways, starting with the web download. A single web page provides access to a single download containing both the latest version of HP SUM version 5 and the latest SPP. Optional smaller subsets with only specific types of servers or specific operating systems are offered to save on download time. The HP SUM application has been re-written to provide a more straightforward, intuitive user interface that guides the user through the steps of discovery, analyses and update, providing comprehensive information on available updates, criticality and interdependencies. This information is also available in reports. By providing the option of multiple local or shared repositories which can be easily updated from hp.com, HP SUM provides the tools to optimize stability and consistency throughout the company. While HP SUM and the SPP will recommend the combinations of firmware and system software that HP has found to be the best practice, the application gives customers the flexibility to set their own specific baseline.

The Service Pack for ProLiant has been rigorously tested with specific attention for interaction between firmware, drivers and agents both within the server as well as in interaction with the BladeSystem enclosure components (Onboard Administrator and Virtual Connect). This testing ensures the highest quality as well as providing the input for HP SUM to deploy updates taking into account all interdependencies, when determining the correct updates and order of update deployment.

NOTE: The Service Pack for ProLiant (which includes HP SUM 5) can be downloaded from http://www.hp.com/go/spp/download. More information can be found: http://www.hp.com/go/spp and http://www.hp.com/go/hpsum

Security

Power-on password Administrator's password

Warranty

This product is covered by a global limited warranty and supported by HP Services and a worldwide network of HP Authorized Channel Partners resellers. Hardware diagnostic support and repair is available for three years from date of purchase. Support for software and initial setup is available for 90 days from date of purchase. Enhancements to warranty services are available through HP Care Pack services or customized service agreements. Hard drives have either a one year or three year warranty; refer to the specific hard drive QuickSpecs for details.

NOTE: Server Warranty includes 1-Year Parts, 1-Year Labor, 1-Year Onsite support with next business day response. Warranty repairs may be accomplished through the use of Customer Self Repair (CSR) parts. These parts fall into two categories: 1) Mandatory CSR parts are designed for easy replacement. A travel and labor charge will result when customers decline to replace a Mandatory CSR part; 2)

Standard Features

Optional CSR parts are also designed for easy replacement but may involve added complexity. Customers may choose to have HP replace Optional CSR parts at no charge. Additional information regarding worldwide limited warranty and technical support is available at: http://h18004.www1.hp.com/products/servers/platforms/warranty/index.html



Optional Features

HP Insight management HP Insight Control software

HP Insight Control, a product option, delivers essential infrastructure management that can help save time and money by making it easy to deploy, migrate, monitor, remote control, and optimize your IT infrastructure through a single, simple management console. HP Insight Control also supports Location and Power Discovery Services to automate many configuration, asset tracking, and power management tasks to speed implementation and prevent downtime. For more information, see http://www.hp.com/go/insightcontrol.

HP Insight Control includes one year of 24 x 7 HP Software Technical Support and Update Service ensuring rapid access to HP support staff and proactive delivery of software updates. For more information about this service, see: http://www.hp.com/services/insight.

HP iLO Essentials

HP iLO Essentials license ideal for small and medium business customers. The specially created HP iLO Essentials (a subset of iLO Advanced functionality) saves SMB customers time and money, by ease of remote server set up through the interactive virtual media, lowering operational costs with remote access via the Integrated Remote Console, and faster time to resolution with email-based proactive notifications. With this newly designed HP iLO Essentials license SMB customers now have the option of a server management package solely design and priced just right for their IT environments. HP iLO Essentials is available on all HP ProLiant Gen8 eseries making this an ideal solution for small business owners. For more information, see: http://www.hp.com/go/iLO/essentials

HP iLO Advanced

HP Integrated Lights-Out Advanced License a product option, providing smart remote server management without compromise. iLO Advanced unlocks the full set of remote administration functionality for all HP ProLiant servers by activating the full Virtual Keyboard Video and Mouse remote console, multi-user collaboration, console record and replay, GUIbased and scripted virtual media and virtual folders, and enhanced security and power management functionality. For more information, see: http://www.hp.com/go/iloadvanced

Storage Software

Whether you need to solve a specific data protection, archiving, or storage command and control challenge, or deliver on strategic consolidation, compliance, or continuity initiatives, look no further than HP storage software. Our storage software helps you reduce costs, simplify storage infrastructure, protect vital assets and respond faster to business opportunities. Storage software that gets the job done:

Data Protection and Recovery Software

Whether you're a large enterprise or a smaller business, HP data protection and recovery software will cost-effectively protect you against disaster and ensure business continuity.

Data Archive and Migration Software

HP's storage software enables you to comply with data retention and retrieval requirements, improve application performance, and reduce costs by efficiently migrating infrequently accessed or less valuable data to lower cost storage.

Storage Resource Management Software (SRM)

HP's storage resource management software reduces operational costs and provides the command and control foundation you need to efficiently manage and visualize your physical and virtual environments.

Data Replication Software

HP offers array-based and host-based replication software for use in disaster recovery. testing, application development and reporting.



Optional Features

Storage Device Management Software

Maximize your investment in HP storage and networking with software that enables hardware-specific configuration, performance tuning and connectivity management.

HP StoreVirtual VSA

With HP StoreVirtual VSA you can use the power of virtualization to turn a set of heterogeneous and disconnected physical disk drives in your servers and storage devices into a single pool of logical storage capacity.

NOTE: For more information available Storage Software including QuickSpecs, please see: http://www.hp.com/go/storage/software.

HP Insight Online

HP Insight Online is a new addition to the HP Support Center for one stop, secure access to product and HP support information personalized to your IT environment. Insight Online can automatically display devices remotely monitored by HP Insight Remote Support. With Insight Online's easy navigation you can efficiently track your IT support contracts and device status from anywhere and at anytime. http://www.hp.com/go/insightonline

HP Proactive Insight experience

Prevent problems with innovative, automated monitoring tools and proactive services. The HP Proactive Insight experience consist of using Insight Online, Insight Remote Support, and Proactive Care Support Service as one integrated solution. The Proactive Insight experience provides you with expert advice and personalized, cloud-based automated IT support, helping to prevent unplanned down time and solve problems quickly. For more information, visit: http://www.hp.com/go/proactiveinsightexperience

for Servers and Storage

Factory Express Portfolio HP Factory Express offers configuration, customization, integration and deployment services for HP servers and storage products. Customers can choose how their factory solutions are built, tested, integrated, shipped and deployed.

> Factory Express offers service packages for simple configuration, racking, installation, complex configuration and design services as well as individual factory services, such as image loading, asset tagging, and custom packaging. HP products supported through Factory Express include a wide array of servers and storage: HP Integrity, HP ProLiant, HP ProLiant Server Blades, HP BladeSystem, HP 9000 servers as well as the MSAxxxx, VA7xxx, EVA, XP, rackable tape libraries and configurable network switches.

> For more information on Factory Express services for your specific server model please contact your sales representative or go to: http://www.hp.com/go/factory-express.

HP Simple Configurator

SCE is a guided self service tool to help sales and non technical people provide customers with initial configurations in 3 to 5 minutes. You may then send the configuration on for configuration help, or use in your existing ordering processes. If you require "custom" rack configuration or configuration for products not available in SCE, please contact HP's Customer Business Center or an Authorized Partner for assistance. http://www.hp.com/products/configurator



Service and Support

Service and Support

HP Technology Services for Industry Standard Servers and BladeSystem

HP Technology Services delivers confidence, reduces risk and helps customers realize agility and stability. Connect to HP to help prevent problems and solve issues faster. Our support technology lets you to tap into the knowledge of millions of devices and thousands of experts to stay informed and in control, anywhere, any time.

Protect your business beyond warranty with HP Care Pack Services

HP Care Pack Services enable you to order the right service level, length of coverage and response time as you purchase your new server, giving you full entitlement for the term you select.

Optimized Care

Supports maintaining servers at optimum performance availability

HP Proactive Care with 24x7 coverage, three year Care Pack Service

HP Proactive Care helps prevent problems and stabilize IT by utilizing secure, real-time, predictive analytics and proactive consultations when your products are connected to HP. This Care Pack Service combines three years' proactive reporting and advice with our 24x7 coverage and enhanced escalation management, four hour hardware response time and two hour call back for software questions on leading industry standard software running on your HP ProLiant server.

http://h20195.www2.hp.com/v2/GetPDF.aspx/4AA3-8855ENW.pdf

Standard Care

Supports maintaining high level of server availability

Foundation Care 24x7, three-year Care Pack Service

HP Foundation Care 24x7 connects you to HP 24 hours a day, seven days a week for assistance on resolving issues. Hardware onsite response within four hours if needed; collaborative software included in this Care Pack service provides troubleshooting assistance on industry leading software running on your HP server. Simplify your support experience and make HP your first call for hardware or software questions.

http://h20195.www2.hp.com/V2/GetDocument.aspx?docname=4AA4-8876ENW&cc=us&lc=en

Related Services

HP ProLiant Server Hardware Installation

Provides for the basic hardware installation of HP branded servers, storage devices and networking options to assist you in bringing your new hardware into operation in a timely and professional manner.

http://h20195.www2.hp.com/V2/GetPDF.aspx/5981-9356EN.pdf

Factory Express for Servers and storage

HP Factory Express offers configuration, customization, integration and deployment services for HP servers and storage products. Customers can choose how their factory solutions are built, tested, integrated, shipped and deployed. For more information on Factory Express services for your specific server model please contact your sales representative or go to: http://www.hp.com/go/factory-express.

Data Privacy Services

Protect your data through better media management. HP Data privacy services help manage and protect sensitive data to reduce the risk of unauthorized access to private information and help meet compliance requirements. Our retention services allow you to keep drives and other devices upon failure, our removal services provide convenient data sanitization and our recovery services allow you to safely retire IT assets and capture any remaining value from the hardware. http://www.hp.com/services/dataprivacy

Additional HP Care Pack services can be found at: http://www.hp.com/go/cpc



Service and Support

Get connected to HP to improve your support experience

Connecting products to HP will help prevent problems with 24x7monitoring, prefailure alerts, automatic call logging, and parts dispatch. With Connected products, you can have a dashboard to manage your IT anywhere, anytime, from any device.

HP Support Center

Personalized online support portal with access to information, tools and experts to support HP business products. Submit support cases online, chat with HP experts, access support resources or collaborate with peers. Learn more http://www.hp.com/qo/hpsc

HP's Support Center Mobile App* allows you to resolve issues yourself or quickly connect to an agent for live support. Now, you can get access to personalized IT support anywhere, anytime. HP Insight Remote Support and HP Support Center are available at no additional cost with a HP warranty, HP Care Pack or HP contractual support agreement.

*HP' Support Center Mobile App is subject to local availability

Parts and Materials

HP will provide HP-supported replacement parts and materials necessary to maintain the covered hardware product in operating condition, including parts and materials for available and recommended engineering improvements.

Parts and components that have reached their maximum supported lifetime and/or the maximum usage limitations as set forth in the manufacturer's operating manual, product quick-specs, or the technical product data sheet will not be provided, repaired, or replaced as part of these services.

The defective media retention service feature option applies only to Disk or eligible SSD/Flash Drives replaced by HP due to malfunction.

For more information

To learn more on HP ProLiant servers and HP BladeSystem servers, please contact your HP sales representative or HP Authorized Channel Partner. Or visit: http://www.hp.com/services/proliant



Pre-configured Models

NOTE: For the Standard Features shipped in the "Factory Integrated Models", please see the "Configuration Information - Factory Integrated Models" section.

NOTE: Pre-configured models ship with the configurations below. Options can be selected from the Core or Additional options section of this QuickSpecs.

NOTE: HP does not allow factory integration of options into pre-configured models. Any additional options purchased will be shipped separately.

NOTE: If you desire a custom configuration please see "Configuration Information - Factory Integrated Models" section of this QuickSpecs.

NOTE: Maximum speed supported depends on the CPU installed. Entry model will support maximum speed of 1600 MHz. Please see Memory Population Table or the Online Memory Configuration Tool at: http://www.hp.com/go/ddr3memoryconfigurator.

NOTE: All Pre-configured Models come populated with some hard drive blanks installed. Should the customer need additional hard drive blanks, they can order more using either P/N 666987-B21: HP SFF Gen8 Hard Drive Blank Kit or P/N 666986-B21: HP LFF Gen8 Hard Drive Blank Kit.

NOTE: Not all models are available in all regions. Check with your local country HP offices for availability.

Entry Models

HP ProLiant DL320e Gen8 Processor(s) v2 G3240 1P 2GB-U Nonhot Plug 2 LFF Entry Server 768638-xx1

Cache Memory Memory

(1) Intel® Pentium® G3240 (3.1 GHz/2-core/3MB/54W) Processor

8MB (1x8MB) Level3

2GB (1 x 2GB) Unbuffered DIMMs PC3-12800E (1600MHz)

Network Controller Storage Controller

HP Ethernet 1Gb 2-port NC332i Adapter HP Dynamic Smart Array B120i Controller

NOTE: B120i has the following performance with regards to drive speed: 6Gb/s - in 2LFF and 4SFF only with port 0 & 1 installed; 3Gb/s - in 4SFF with more than 2 drives installed. For full 6 Gb.0/s speed a stand up card/smart

array controller must be used.

NOTE: B120i supports RAID 0/1/10 only. It does not have FBWC support so cannot support advanced RAID (5 onwards). For FBWC, a standup Smart

Array Controller card must be configured.

Hard Drive None ship standard

Internal Storage 2 bay LFF Non Hot Plug Drive Cage; includes 2LFF Hard Drive blanks

Optical Drive Bay None ships standard **PCI-Express Slots** 1 PCle3 x16 and 1 PCle3 x8

250 Watts Non-Hot Plug, Non redundant Power Supply for all regions **Power Supply Fans** 2 front fan assemblies and 1 center fan assembly ship standard, non-

redundant

Management HP iLO Management Engine (standard)

Optional: HP iLO Essentials or HP Insight Control

Form Factor 1U

Warranty Server Warranty includes 1-Year Parts, 1-Year Labor, 1-Year Onsite

support with next business day response.

NOTE: No rail kits are included with the server. They must be ordered

separately.

HP ProLiant DL320e Gen8 Processor(s) v2 G3220 1P 2GB-U NHP 2 Cache Memory **LFF Server**

Memory

(1) Intel® Pentium® G3220 (3.0 GHz/2-core/3MB/54W) Processor

8MB (1x8MB) Level3

2GB (1 x 2GB) Unbuffered DIMMs PC3-12800E (1600MHz)

Network Controller HP Ethernet 1Gb 2-port NC332i Adapter Storage Controller HP Dynamic Smart Array B120i Controller

NOTE: B120i has the following performance with regards to drive speed:



743490-xx1

Pre-configured Models

6Gb/s - in 2LFF and 4SFF only with port 0 & 1 installed; 3Gb/s - in 4SFF with more than 2 drives installed. For full 6 Gb.0/s speed a stand up card/smart

array controller must be used.

NOTE: B120i supports RAID 0/1/10 only. It does not have FBWC support so cannot support advanced RAID (5 onwards). For FBWC, a standup Smart

Array Controller card must be configured.

Hard Drive None ship standard

2 bay LFF Non Hot Plug Drive Cage; includes 2LFF Hard Drive blanks **Internal Storage**

Optical Drive Bay None ships standard **PCI-Express Slots** 1 PCle3 x16 and 1 PCle3 x8

250 Watts Non-Hot Plug, Non redundant Power Supply for all regions Power Supply

Fans 2 front fan assemblies and 1 center fan assembly ship standard, non-

redundant

Management HP iLO Management Engine (standard)

Optional: HP iLO Essentials or HP Insight Control

Form Factor

Warranty Server Warranty includes 1-Year Parts, 1-Year Labor, 1-Year Onsite

support with next business day response.

NOTE: No rail kits are included with the server. They must be ordered

separately.

Base Models

HP ProLiant DL320e Gen8 Processor(s) v2 E3-1220v3 1P 4GB-U **B120i Server**

717170-xx1

Cache Memory

Memory

Network Controller Storage Controller

(1) Intel® Xeon® E3-1220v3 (3.1GHz/4-core/8MB/80W, HT) Processor

8MB (1x8MB) Level3

4GB (1 x 4GB) Unbuffered DIMMs PC3-12800E (1600MHz)

HP Ethernet 1Gb 2-port NC332i Adapter HP Dynamic Smart Array B120i Controller

> **NOTE:** B120i has the following performance with regards to drive speed: 6Gb/s - in 2LFF and 4SFF only with port 0 & 1 installed; 3Gb/s - in 4SFF with more than 2 drives installed. For full 6 Gb.0/s speed a stand up

card/smart array controller must be used.

NOTE: B120i supports RAID 0/1/10 only. It does not have FBWC support so cannot support advanced RAID (5 onwards). For FBWC, a standup Smart

Array Controller card must be configured.

Hard Drive None ship standard

Internal Storage 2 bay LFF Hot Plug Drive Cage; includes 1 LFF hard drive blank

Optical Drive Bav None ships standard **PCI-Express Slots** 1 PCle3 x16 and 1 PCle3 x8

Power Supply 250 Watts Non-Hot Plug, Non redundant Power Supply for all regions Fans

2 front fan assemblies and 1 center fan assembly ship standard, non-

redundant

HP iLO Management Engine (standard) Management

Optional: HP iLO Essentials or HP Insight Control

Form Factor 1U

Warranty Server Warranty includes 1-Year Parts, 1-Year Labor, 1-Year Onsite

support with next business day response.

NOTE: No rail kits are included with the server. They must be ordered

separately.

Pre-configured Models

Performance Models

HP ProLiant DL320e Gen8 Processor(s) v2 E3-1241v3 1P 8GB-U P222 Hot Plug 4 SFF Perf

768645-xx1

Cache Memory

Memory

8MB (1x8MB) Level3

8GB (1 x 8GB) Unbuffered DIMMs PC3-12800E (1600MHz)

Network Controller HP Ethernet 1Gb 2-port NC332i Adapter Storage Controller HP Smart Array P222/512MB FBWC Controller

Hard Drive None ship standard

4 bay SFF Hot Plug Drive Cage; includes 3 SFF hard drive blanks **Internal Storage**

Optical Drive Bay None ships standard **PCI-Express Slots** 1 PCle3 x16 and 1 PCle3 x8

Power Supply 250 Watts Non-Hot Plug, Non redundant Power Supply for all regions Fans 2 front fan assemblies and 1 center fan assembly ship standard, non-

redundant

Management HP iLO Management Engine (standard)

Optional: HP iLO Essentials or HP Insight Control

Form Factor 1U

Warranty Server Warranty includes 1-Year Parts, 1-Year Labor, 1-Year Onsite

support with next business day response.

NOTE: No rail kits are included with the server. They must be ordered

(1) Intel® Xeon® E3-1240v3 (3.4GHz/4-core/8MB/80W, HT) Processor

(1) Intel® Xeon® E3-1241v3 (3.5GHz/4-core/8MB/80W, HT) Processor

separately.

HP ProLiant DL320e Gen8 Processor(s) v2 E3-1240v3 1P 8GB-U **P222 Server**

722547-xx1

Cache Memory

8MB (1x8MB) Level3

8GB (1 x 8GB) Unbuffered DIMMs PC3-12800E (1600MHz) Memory

Network Controller HP Ethernet 1Gb 2-port NC332i Adapter Storage Controller HP Smart Array P222/512MB FBWC Controller

Hard Drive None ship standard

Internal Storage 4 bay SFF Hot Plug Drive Cage; includes 3 SFF hard drive blanks

None ships standard **Optical Drive Bay PCI-Express Slots** 1 PCle3 x16 and 1 PCle3 x8

Power Supply 250 Watts Non-Hot Plug, Non redundant Power Supply for all regions

Fans 2 front fan assemblies and 1 center fan assembly ship standard, non-

redundant

Management HP iLO Management Engine (standard)

Optional: HP iLO Essentials or HP Insight Control

Form Factor

Warranty Server Warranty includes 1-Year Parts, 1-Year Labor, 1-Year Onsite

support with next business day response.

NOTE: No rail kits are included with the server. They must be ordered

separately.

Country Code Key

U.S. xx = 00xx = 20Brazil xx = 29Japan xx = 37APD xx = 42Europe xx = AA**PRC**



Configuration Information - Factory Integrated Models

NOTE: This section lists some of the steps required to configure a Factory Integrated Model. To ensure only valid configurations are ordered, HP recommends the use of an HP approved configurator. Contact your local sales representative for information on configurable product offerings and requirements.

NOTE: Factory Integrated Models must start with a CTO Server.

NOTE: FIO indicates that this option is only available as a factory installable option.

NOTE: All Factory Integrated Models will be populated with sufficient hard drive blanks based on the number of initial hard drives ordered with the server.

Step 1: Base Configuration (choose one of the following configurable models)

HP Models HP ProLiant DL320e Gen8 v2 Non-hot Plug 2 LFF Configure-to-order Server

722313-B21

Factory Integrated Model ships with:

1U Chassis with 2 LFF Non-Hot Plug Drive Cage HP Ethernet 1Gb 2-port NC332i Adapter HP iLO Management Engine (standard)

HP 250W power supply

NOTE: The default power supply for DL320e Gen8v2 server is either a 250W Non Hot

Plug, Non Redundant (ATX) power supply for all regions HP Dynamic Smart Array B120i SATA Controller (RAID 0/1/10)

NOTE: For set up instructions for HP Dynamic Smart Array B120i SATA Controller

please refer to the HP ProLiant DL300 series server user guide

NOTE: For general information about HP Dynamic Smart Array B120i SATA

Controller, please visit:

http://h18004.www1.hp.com/products/servers/proliantstorage/arraycontrollers/smartarrayb120i/index.html

HP ProLiant DL320e Gen8 v2 Hot Plug 2 LFF Configure-to-order Server

722314-B21

Factory Integrated Model ships with:

1U Chassis with 2 LFF Hot Plug Drive Cage HP Ethernet 1Gb 2-port NC332i Adapter HP iLO Management Engine (standard)

HP Dynamic Smart Array B120i SATA Controller (RAID 0/1/10)

NOTE: For set up instructions for HP Dynamic Smart Array B120i SATA Controller

please refer to the HP ProLiant DL300 series server user guide

NOTE: For general information about HP Dynamic Smart Array B120i SATA

Controller, please visit:

http://h18004.www1.hp.com/products/servers/proliantstorage/arraycontrollers/smartarrayb120i/index.html

HP ProLiant DL320e Gen8 v2 Hot Plug 4 SFF Configure-to-order Server

722315-B21

Factory Integrated Model ships with:

1U Chassis with 4 SFF Hot plug Drive Cage HP Ethernet 1Gb 2-port NC332i Adapter HP iLO Management Engine (standard)

HP Dynamic Smart Array B120i SATA Controller (RAID 0/1/10)

NOTE: For set up instructions for HP Dynamic Smart Array B120i SATA Controller

please refer to the HP ProLiant DL300 series server user guide

NOTE: For general information about HP Dynamic Smart Array B120i SATA

Controller, please visit:

http://h18004.www1.hp.com/products/servers/proliantstorage/arraycontrollers/smartarrayb120i/index.html

Step 2: Choose Required Options (only one of the following from each list unless otherwise noted)



Configuration Information - Factory Integrated Models

| HP Processors | Entry Processors NOTE: G3220 supports up to 1333MHz DDR3 memory speeds. G3420 supports up to 1600MHz DDR3 memory speeds. | |
|---------------|---|------------|
| | HP DL320e Gen8 v2 Intel® Pentium® G3220 (3.0GHz/2-core/3MB/54W) FIO Processor Kit | 741417-L21 |
| | HP DL320e Gen8 v2 Intel® Pentium® G3420 (3.2GHz/2-core/3MB/54W) FIO Processor Kit | 741419-L21 |
| | HP DL320e Gen8 v2 Intel® Pentium® G3420 (3.2GHz/2-core/3MB/54W) FIO Processor Kit | 741419-L21 |
| | Base Processors NOTE: All support up to 1600MHz memory speeds. | |
| | HP DL320e Gen8 v2 Intel® Core™ i3-4130 (3.4GHz/2-core/3MB/54W) FIO Processor Kit | 741413-L21 |
| | HP DL320e Gen8 v2 Intel® Core™ i3-4130T (2.9GHz/2-core/3MB/35W) FIO Processor Kit | 741415-L21 |
| | HP DL320e Gen8 v2 Intel® Core™ i3-4150 (3.5GHz/2-core/3MB/54W) FIO Processor Kit | 768916-L21 |
| | Performance Processors NOTE: All support up to 1600MHz DDR3 memory speeds. | |
| | HP DL320e Gen8 v2 Intel® Xeon® E3-1281v3 (3.7GHz/4-core/8MB/82W) FIO Processor Kit | 768917-L21 |
| | HP DL320e Gen8 v2 Intel® Xeon® E3-1271v3 (3.6GHz/4-core/8MB/80W) FIO Processor Kit | 768918-L21 |
| | HP DL320e Gen8 v2 Intel® Xeon® E3-1241v3 (3.5GHz/4-core/8MB/80W) FIO Processor Kit | 768914-L21 |
| | HP DL320e Gen8 v2 Intel® Xeon® E3-1231v3 (3.4GHz/4-core/8MB/80W) FIO Processor Kit | 768915-L21 |
| | HP DL320e Gen8 v2 Intel® Xeon® E3-1280v3 (3.6GHz/4-core/8MB/95W) FIO Processor Kit | 718249-L21 |
| | HP DL320e Gen8 v2 Intel® Xeon® E3-1270v3 (3.5GHz/4-core/8MB/80W) FIO Processor Kit | 718251-L21 |
| | HP DL320e Gen8 v2 Intel® Xeon® E3-1240v3 (3.4GHz/4-core/8MB/80W) FIO Processor Kit | 718253-L21 |
| | HP DL320e Gen8 v2 Intel® Xeon® E3-1230Lv3 (1.8GHz/4-core/8MB/25W) FIO Processor Kit | 741411-L21 |
| | HP DL320e Gen8 v2 Intel® Xeon® E3-1230v3 (3.3GHz/4-core/8MB/80W) FIO Processor Kit | 718255-L21 |
| | HP DL320e Gen8 v2 Intel® Xeon® E3-1220v3 (3.1GHz/4-core/8MB/80W) FIO Processor Kit | 718257-L21 |
| | HP DL320e Gen8 v2 Intel® Xeon® E3-1265Lv3 (2.5GHz/4-core/8MB/45W) FIO Processor Kit | 718261-L21 |
| HP Memory | NOTE: To realize the performance memory capabilities listed in this document, HP SmartMemory is required. For additional information, please see the HP SmartMemory QuickSpecs at: | |
| | http://h18000.www1.hp.com/products/quickspecs/14225_div/14225_div.html (Worldwide) NOTE: HP memory from previous generation servers are not fully compatible with | |
| | new Active Health features on the DL320e Gen8 v2 Server. | |
| | Unbuffered with ECC DIMMs (UDIMMs) | |
| | HP 2GB (1x2GB) Single Rank x8 PC3L-12800E (DDR3-1600) Unbuffered CAS-11 Low | 713975-B21 |

Configuration Information - Factory Integrated Models

| Configuration Info | ormation - Factory Integrated Models | |
|--------------------|---|------------|
| | Voltage Memory Kit | |
| | HP 4GB (1x4GB) Dual Rank x8 PC3L-12800E (DDR3-1600) Unbuffered CAS-11 Low Voltage Memory Kit | 713977-B21 |
| | HP 8GB (1x8GB) Dual Rank x8 PC3L-12800E (DDR3-1600) Unbuffered CAS-11 Low Voltage Memory Kit | 713979-B21 |
| | Unbuffered with ECC DIMMs (UDIMMs) | |
| | HP 2GB (1x2GB) Single Rank x8 PC3-12800E (DDR3-1600) Unbuffered CAS-11 Memory Kit | 669320-B21 |
| | HP 2GB (1x2GB) Single Rank x8 PC3L-10600E (DDR3-1333) Unbuffered CAS-9 Low Voltage Memory Kit | 647905-B21 |
| | HP 4GB (1x4GB) Dual Rank x8 PC3-12800E (DDR3-1600) Unbuffered CAS-11 Memory Kit | 669322-B21 |
| | HP 4GB (1x4GB) Dual Rank x8 PC3L-10600E (DDR3-1333) Unbuffered CAS-9 Low Voltage Memory Kit | 647907-B21 |
| | HP 8GB (1x8GB) Dual Rank x8 PC3-12800E (DDR3-1600) Unbuffered CAS-11 Memory Kit | 669324-B21 |
| | HP 8GB (1x8GB) Dual Rank x8 PC3L-10600E (DDR3-1333) Unbuffered CAS-9 Low Voltage Memory Kit | 647909-B21 |
| | NOTE: All DDR3 memory option kits consist of one DIMM per kit. For detailed memory configuration rules and guidelines, please use the Online DDR3 Memory Configuration Tool: http://www.hp.com/go/ddr3memory-configurator. NOTE: Depending on the memory configuration and processor model, 1600MHz and 1333MHz memory may operate at a lower speed. Please see the see the "Memory" section later in this document and the Online Memory Configuration Tool for details at http://www.hp.com/go/ddr3memory-configurator. NOTE: For additional memory rules and guidelines, see the "Memory" section later in this document. NOTE: For more information on ProLiant Energy Efficient Features, see: http://www.hp.com/go/proliant-energy-efficient NOTE: PC3L is a low voltage memory. | |
| HP Power Supplies | NOTE: Prior to making a power supply selection it is highly recommended that the HP Power Advisor is run to determine the right size power supply for your server configuration. The HP Power Advisor is located at: http://www.hp.com/go/hppoweradvisor. | |
| | HP DL320e Gen8 v2 250W FIO Power Supply Unit Kit | 748334-B21 |
| | NOTE: Non redundant Power Supply for all regions | |
| | HP 750W Common Slot -48VDC Hot Plug Power Supply Kit NOTE: Selecting the 750W power supply requires the HP DL320e Gen8 v2 CS FIO Enablement Kit | 636673-B21 |
| Cton 2. Chanca A | dditional Factory Internatable Oations | |
| - | Additional Factory Integratable Options | _ |
| HP USB Cable Kit | HP Gen8 FIO Internal USB Kit NOTE: Required only if USB Flash Media Drive Key is selected. | 662961-B21 |
| HP Security | HP DL320eGen8 v2 Entry Rack Ear FIO Kit NOTE: DL320e Gen8 v2 ships with thumbscrew ear attachments (BTO and CTO) as standard. The Entry Rack Ear FIO Kit is a Quick Release Ear kit, it also needs to be purchased if you want to have a security bezel installed. HP Insight Control including 1yr 24x7 Support ProLiant ML/DL/BL-bundle Single | 723903-B21 |



NOTE: For more rail kit options see "Additional Options" section of this QuickSpecs.

Server FIO License.

Configuration Information - Factory Integrated Models

| HP Insight Software | HP Insight Control including 1yr 24x7 Support ProLiant ML/DL/BL-bundle Single Server FIO License | C6N36A |
|---|---|----------|
| | HP Insight Control including 1yr 24x7 Support ProLiant ML/DL/BL-bundle FIO Electronic License NOTE: The Electronic software license is available in EMEA only. | C6N36ABE |
| Converged Infrastructure Management Software | HP OneView with iLO Advanced - Server hardware required on same purchase order | |
| | HP OneView for ProLiant DL Server incl 3yr 24x7 Supp FIO Bundle Physical 1 Svr Lic | E5Y43A |
| | HP OneView incl 3yr 24x7 Supp Bundle 1 Svr E-LTU | E5Y43AAE |

Step 4: Choose Additional Options for Factory Integration

NOTE: For additional options, please refer to the "Core Options" and "Additional Options" section below.



Core Options

NOTE: Some options may not be integrated at the factory. To ensure only valid configurations are ordered, HP recommends the use of an HP approved configurator. Contact your local sales representative for additional information.

HP Memory

NOTE: To realize the performance memory capabilities listed in this document, HP SmartMemory is required. For additional information, please see the HP SmartMemory QuickSpecs at:

http://h18000.www1.hp.com/products/quickspecs/14225 div/14225 div.html (Worldwide)

NOTE: HP memory from previous generation servers are not fully compatible with SmartMemory features in Gen8 Servers.

Unbuffered with ECC DIMMs (UDIMMs)

| HP 2GB (1x2GB) Single Rank x8 PC3L-12800E (DDR3-1600) Unbuffered CAS-11 Low Voltage Memory Kit | 713975-B21 |
|---|------------|
| HP 4GB (1x4GB) Dual Rank x8 PC3L-12800E (DDR3-1600) Unbuffered CAS-11 Low Voltage Memory Kit | 713977-B21 |
| HP 8GB (1x8GB) Dual Rank x8 PC3L-12800E (DDR3-1600) Unbuffered CAS-11 Low Voltage Memory Kit | 713979-B21 |

| Unbuffered with ECC DIMMs (UDIMMs) | |
|--|------------|
| HP 2GB (1x2GB) Single Rank x8 PC3-12800E (DDR3-1600) Unbuffered CAS-11 Memory Kit | 669320-B21 |
| HP 2GB (1x2GB) Single Rank x8 PC3L-10600E (DDR3-1333) Unbuffered CAS-9 Low Voltage Memory Kit | 647905-B21 |
| HP 4GB (1x4GB) Dual Rank x8 PC3-12800E (DDR3-1600) Unbuffered CAS-11 Memory Kit | 669322-B21 |
| HP 4GB (1x4GB) Dual Rank x8 PC3L-10600E (DDR3-1333) Unbuffered CAS-9 Low Voltage Memory Kit | 647907-B21 |
| HP 8GB (1x8GB) Dual Rank x8 PC3-12800E (DDR3-1600) Unbuffered CAS-11 Memory Kit | 669324-B21 |
| HP 8GB (1x8GB) Dual Rank x8 PC3L-10600E (DDR3-1333) Unbuffered CAS-9 Low | 647909-B21 |

NOTE: All DDR3 memory option kits consist of one DIMM per kit. For detailed memory configuration rules and guidelines, please use the Online DDR3 Memory Configuration Tool: http://www.hp.com/go/ddr3memory-configurator. **NOTE:** Kits described as LP include Low Power DIMMs. For more information on

ProLiant Energy Efficient Features, see: http://www.hp.com/go/proliant-energyefficient.

NOTE: PC3L is a low voltage memory.

Voltage Memory Kit

| | A | |
|----|--------|----------|
| HΡ | Optica | l Drives |

HP 9.5mm SATA DVD-RW JackBlack Optical Drive

652241-B21

HP Hard Drives

NOTE: The components of a storage subsystem (e.g. the drive, the HBA/controller. firmware, and the server backplane) should operate at the same data transfer rate or the system bandwidth will be negotiated down to an acceptable level for all components.

NOTE: Hard drives have either a one year or three year warranty; refer to the specific hard drive QuickSpecs for details.

12G SAS Hot Plug SmartDrive LFF (3.5-inch) Converter Enterprise Drives

| HP 600GB 12G SAS 15K rpm LFF (3.5-inch) SC Converter Enterprise 3yr Warranty Hard Drive | 765424-B21 |
|--|------------|
| HP 450GB 12G SAS 15K rpm LFF (3.5-inch) SC Converter Enterprise 3yr Warranty | 737394-B21 |

Hard Drive



| HP 300GB 12G SAS 15K rpm LFF (3.5-inch) SC Converter Enterprise 3yr Warranty Hard Drive | 737261-B21 |
|---|------------|
| 12G SAS Hot Plug with SmartDrive SFF (2.5-inch) Enterprise Drives | |
| HP 600GB 12G SAS 15K rpm SFF (2.5-inch) SC Enterprise 3yr Warranty Hard Drive | 759212-B21 |
| HP 450GB 12G SAS 15K rpm SFF (2.5-inch) SC Enterprise 3yr Warranty Hard Drive | 759210-B21 |
| HP 300GB 12G SAS 15K rpm SFF (2.5-inch) SC Enterprise 3yr Warranty Hard Drive | 759208-B21 |
| 6G SAS Hot Plug with SmartDrive SFF (2.5-inch) Enterprise Drives | |
| HP 1.2TB 6G SAS 10K rpm SFF (2.5-inch) SC Dual Port Enterprise 3yr Warranty Hard Drive | 718162-B21 |
| HP 900GB 6G SAS 10K rpm SFF (2.5-inch) SC Enterprise 3yr Warranty Hard Drive | 652589-B21 |
| HP 600GB 6G SAS 10K rpm SFF (2.5-inch) SC Enterprise 3yr Warranty Hard Drive | 652583-B21 |
| HP 450GB 6G SAS 10K rpm SFF (2.5-inch) SC Enterprise 3yr Warranty Hard Drive | 652572-B21 |
| HP 300GB 6G SAS 10K rpm SFF (2.5-inch) SC Enterprise 3yr Warranty Hard Drive | 652564-B21 |
| HP 300GB 6G SAS 15K rpm SFF (2.5-inch) SC Enterprise 3yr Warranty Hard Drive | 652611-B21 |
| HP 146GB 6G SAS 15K rpm SFF (2.5-inch) SC Enterprise 3yr Warranty Hard Drive | 652605-B21 |
| 6G SAS Hot Plug SmartDrive LFF (3.5-inch) Enterprise Drives | |
| HP 450GB 6G SAS 15K rpm LFF (3.5-inch) SC Enterprise 3yr Warranty Hard Drive | 652615-B21 |
| 6G SAS Hot Plug SmartDrive SFF (2.5-inch) Midline Drives | |
| HP 1TB 6G SAS 7.2K rpm SFF (2.5-inch) SC Midline 1yr Warranty Hard Drive | 652749-B21 |
| HP 500GB 6G SAS 7.2K rpm SFF (2.5-inch) SC Midline 1yr Warranty Hard Drive | 652745-B21 |
| 6G SAS Hot Plug SmartDrive LFF (3.5-inch) Midline Drives | |
| HP 4TB 6G SAS 7.2K rpm LFF (3.5-inch) SC Midline 1yr Warranty Hard Drive | 695510-B21 |
| HP 3TB 6G SAS 7.2K rpm LFF (3.5-inch) SC Midline 1yr Warranty Hard Drive | 652766-B21 |
| HP 2TB 6G SAS 7.2K rpm LFF (3.5-inch) SC Midline 1yr Warranty Hard Drive | 652757-B21 |
| HP 1TB 6G SAS 7.2K rpm LFF (3.5-inch) SC Midline 1yr Warranty Hard Drive | 652753-B21 |
| NOTE: Please see the QuickSpecs for Technical Specifications and additional information: | |
| http://h18000.www1.hp.com/products/quickspecs/12244_div/12244_div.html (Worldwide) | |
| 6G SATA Hot Plug with SmartDrive SFF (2.5-inch) Midline (MDL) Drives | |
| HP 1TB 6G SATA 7.2K rpm SFF (2.5-inch) SC Midline 1yr Warranty Hard Drive | 655710-B21 |
| HP 500GB 6G SATA 7.2K rpm SFF (2.5-inch) SC Midline 1yr Warranty Hard Drive | 655708-B21 |
| 6G SATA Hot Plug with SmartDrive LFF (3.5-inch) Midline (MDL) Drives | |
| HP 4TB 6G SATA 7.2k rpm LFF (3.5-inch) SC Midline 1yr Warranty Hard Drive | 693687-B21 |
| HP 3TB 6G SATA 7.2K rpm LFF (3.5-inch) SC Midline 1yr Warranty Hard Drive | 628061-B21 |
| HP 2TB 6G SATA 7.2K rpm LFF (3.5-inch) SC Midline 1yr Warranty Hard Drive | 658079-B21 |
| HP 1TB 6G SATA 7.2K rpm LFF (3.5-inch) SC Midline 1yr Warranty Hard Drive | 657750-B21 |
| HP 500GB 6G SATA 7.2K rpm LFF (3.5-inch) SC Midline 1yr Warranty Hard Drive | 658071-B21 |
| 6G SATA Hot Plug LFF (3.5-inch) Midline (MDL) 512e Drives | |
| HP 6TB 6G SATA 7.2K rpm LFF (3.5-inch) SC Midline 512e 1yr Warranty Hard Drive | 765255-B21 |
| HP 4TB 6G SATA 7.2K rpm LFF (3.5-inch) SC Midline 512e 1yr Warranty Hard Drive | 765253-B21 |
| 6G SATA Non-Hot Plug LFF (3.5-inch) Midline (MDL) Drives | |
| HP 3TB 6G SATA 7.2K rpm LFF (3.5-inch) Non-hot plug Midline 1yr Warranty Hard Drive | 628065-B21 |
| HP 2TB 6G SATA 7.2K rpm LFF (3.5-inch) Non-hot plug Midline 1yr Warranty Hard Drive | 659339-B21 |



| HP 1TB 6G SATA 7.2K rpm LFF (3.5-inch) Non-hot plug Midline 1yr Warranty Hard Drive | 659337-B21 |
|--|-------------|
| HP 500GB 6G SATA 7.2K rpm LFF (3.5-inch) Non-hot plug Midline 1yr Warranty Hard Drive | 659341-B21 |
| NOTE: Please see the QuickSpecs for Technical Specifications and additional information: | |
| http://h18000.www1.hp.com/products/quickspecs/13021_div/13021_div.html (Worldwide) | |
| 12G SAS Hot Plug SFF (2.5-inch) Enterprise Drives | |
| HP 1.2TB 12G SAS 10K rpm SFF (2.5-inch) SC Enterprise 3yr Warranty Hard Drive | 781518-B21 |
| HP 900GB 12G SAS 10K rpm SFF (2.5-inch) SC Enterprise 3yr Warranty Hard Drive | 785069-B21 |
| HP 600GB 12G SAS 10K rpm SFF (2.5-inch) SC Enterprise 3yr Warranty Hard Drive | 781516-B21 |
| HP 300GB 12G SAS 10K rpm SFF (2.5-inch) SC Enterprise 3yr Warranty Hard Drive | 785067-B21 |
| 12G SAS Hot Plug LFF (3.5-inch) Midline (MDL) 512e Drives | |
| HP 6TB 12G SAS 7.2K rpm LFF (3.5-inch) SC Midline 512e 1yr Warranty Hard Drive | 765259-B21 |
| HP 4TB 12G SAS 7.2K rpm LFF (3.5-inch) SC Midline 512e 1yr Warranty Hard Drive | 765257-B21 |
| NOTE: Please see the QuickSpecs for Technical Specifications and additional | |
| information: | |
| http://h18000.www1.hp.com/products/quickspecs/12244_div/12244_div.html (Worldwide) | |
| 12G SAS High Endurance Hot Plug SFF (2.5-inch) Enterprise Performance Solid State Drives | |
| HP 800GB 12G SAS High Endurance SFF 2.5-in SC Enterprise Performance 3yr Wty | 741159-B21 |
| Solid State Drive NOTE: This drive supports Gen8 servers only. | |
| HP 400GB 12G SAS High Endurance SFF 2.5-in SC Enterprise Performance 3yr Wty | 741155-B21 |
| Solid State Drive | 741133-621 |
| NOTE: This drive supports Gen8 servers only. | |
| HP 200GB 12G SAS High Endurance SFF 2.5-in SC Enterprise Performance 3yr Wty | 741151-B21 |
| Solid State Drive | |
| NOTE: This drive supports Gen8 servers only. | |
| 12G SAS Mainstream Endurance Hot Plug SFF (2.5-inch) Enterprise Mainstream Solid State Drives | |
| HP 800GB 12G SAS Mainstream Endurance SFF 2.5-in SC Enterprise Mainstream 3yr | 7/11//6 DO1 |
| Wty Solid State Drive | 741146-B21 |
| NOTE: This drive supports Gen8 servers only. | |
| HP 400GB 12G SAS Mainstream Endurance SFF 2.5-in SC Enterprise Mainstream 3yr | 741142-B21 |
| Wty Solid State Drive | |
| NOTE: This drive supports Gen8 servers only. | |
| HP 200GB 12G SAS Mainstream Endurance SFF 2.5-in SC Enterprise Mainstream 3yr | 741138-B21 |
| Wty Solid State Drive NOTE: This drive supports Gen8 servers only. | |
| 12G SAS Mainstream Endurance Hot Plug SFF (2.5-inch) Enterprise Mainstream H2 | |
| Solid State Drives | |
| HP 1.6TB 12G SAS Mainstream Endurance SFF 2.5-in ENT Mainstream SC 3yr Wty H2 | 779176-B21 |
| Solid State Drive | 770440 77: |
| HP 400GB 12G SAS Mainstream Endurance SFF 2.5-in ENT Mainstream SC 3yr Wty H2 Solid State Drive | 779168-B21 |
| HP 200GB 12G SAS Mainstream Endurance SFF 2.5-in ENT Mainstream SC 3yr Wty H2 | 779164-B21 |
| Solid State Drive | |



| 6G SATA Value Endurance Hot Plug LFF (3.5-inch) Enterprise Boot Solid State Drives | |
|---|------------|
| HP 120GB 6G SATA Value Endurance LFF 3.5-in SC Enterprise Boot 3yr Wty Solid State Drive | 718171-B21 |
| HP 80GB 6G SATA VE 3.5in SCC EB SSD | 734362-B21 |
| 6G SATA Value Endurance Hot Plug SFF (2.5-inch) Enterprise Boot Solid State Drives | |
| HP 120GB 6G SATA VE 2.5in SC EB SSD | 717965-B21 |
| HP 80GB 6G SATA VE 2.5in SC EB SSD | 734360-B21 |
| 6G SATA Value Endurance Hot Plug SFF (2.5-inch) EV Solid State Drives | |
| HP 480GB 6G SATA VE 2.5in SC EV SSD | 717971-B21 |
| HP 240GB 6G SATA VE 2.5in SC EV SSD | 717969-B21 |
| 6G SATA Value Endurance Hot Plug LFF (3.5-inch) SCC EV Solid State Drives | |
| HP 600GB 6G SATA VE 3.5in SCC EV SSD | 739900-B21 |
| HP 300GB 6G SATA VE 3.5in SCC EV SSD | 739890-B21 |
| 6G SATA Value Endurance Hot Plug SFF (2.5-inch) SC EV Solid State Drives | |
| HP 600GB 6G SATA VE 2.5in SC EV SSD | 739898-B21 |
| HP 300GB 6G SATA VE 2.5in SC EV SSD | 739888-B21 |
| 6G SATA Hot Plug LFF Value Endurance (3.5-inch) Converter Enterprise Value G1 Solid State Drives | |
| HP 480GB 6G SATA Value Endurance LFF 3.5-in SC Converter ENT Value 3yr Wty G1 Solid State Drive | 756660-B21 |
| HP 240GB 6G SATA Value Endurance LFF 3.5-in SC Converter ENT Value 3yr Wty G1 Solid State Drive | 756639-B21 |
| HP 120GB 6G SATA Value Endurance LFF 3.5-in SC Converter ENT Value 3yr Wty G1 Solid State Drive | 756624-B21 |
| 6G SATA Hot Plug LFF Value Endurance (3.5-inch) SCC Enterprise Value Solid State Drives | |
| HP 1.6TB 6G SATA VE 3.5in SCC EV SSD | 757342-B21 |
| 6G SATA Hot Plug SFF Value Endurance (2.5-inch) SC Enterprise Value Solid State Drives | |
| HP 1.6TB 6G SATA VE 2.5in SC EV SSD | 757339-B21 |
| 6G SATA Hot Plug SFF Value Endurance (2.5-inch) Enterprise Value G1 Solid State Drives | |
| HP 480GB 6G SATA Value Endurance SFF 2.5-in SC Enterprise Value 3yr Wty G1 Solid State Drive | 756657-B21 |
| HP 240GB 6G SATA Value Endurance SFF 2.5-in SC Enterprise Value 3yr Wty G1 Solid State Drive | 756636-B21 |
| HP 120GB 6G SATA Value Endurance SFF 2.5-in SC Enterprise Value 3yr Wty G1 Solid State Drive | 756621-B21 |
| 6G SATA Value Endurance Hot Plug LFF (3.5-inch) Enterprise Value Solid State Drives | |
| HP 480GB 6G SATA Value Endurance LFF 3.5-in SC Enterprise Value 3yr Wty Solid State Drive | 718183-B21 |
| HP 240GB 6G SATA Value Endurance LFF 3.5-in SC Enterprise Value 3yr Wty Solid State Drive | 718177-B21 |
| 6G SATA Hot Plug SFF Light Endurance (2.5-inch) Enterprise Light G1 Solid State Drives | |



Core Options

| HP 960GB 6G SATA Light Endurance SFF 2.5-in SC Enterprise Light 3yr Wty G1 Solid State Drive | 756601-B21 |
|--|------------|
| 6G SATA Hot Plug LFF Light Endurance (3.5-inch) Enterprise Light G1 Solid State Drives | |
| HP 960GB 6G SATA Light Endurance LFF 3.5-in SC Enterprise Light 3yr Wty G1 Solid State Drive | 756604-B21 |
| 6G SATA Value Endurance Hot Plug SFF (2.5-inch) Enterprise Value M1 Solid State Drive | |
| HP 480GB 6G SATA Value Endurance SFF 2.5-in SC Enterprise Value 3yr Wty M1 Solid State Drive | 764927-B21 |
| HP 240GB 6G SATA Value Endurance SFF 2.5-in SC Enterprise Value 3yr Wty M1 Solid State Drive | 764925-B21 |
| HP 120GB 6G SATA Value Endurance SFF 2.5-in SC Enterprise Value 3yr Wty M1 Solid State Drive | 764923-B21 |
| 6G SATA Mainstream Endurance Hot Plug SFF (2.5-inch) Enterprise Mainstream Solid State Drives | |
| HP 800GB 6G SATA Mainstream Endurance SFF 2.5-in SC Enterprise Mainstream 3yr Wty Solid State Drive | 691868-B21 |
| HP 400GB 6G SATA Mainstream Endurance SFF 2.5-in SC Enterprise Mainstream 3yr Wty Solid State Drive | 691866-B21 |
| HP 200GB 6G SATA Mainstream Endurance SFF 2.5-in SC Enterprise Mainstream 3yr Wty Solid State Drive | 691864-B21 |
| HP 100GB 6G SATA Mainstream Endurance SFF 2.5-in SC Enterprise Mainstream 3yr Wty Solid State Drive | 691862-B21 |
| 6G SATA Mainstream Endurance Hot Plug LFF (3.5-inch) Enterprise Mainstream Solid State Drives | |
| HP 800GB 6G SATA Mainstream Endurance LFF 3.5-in SC Enterprise Mainstream 3yr Wty Solid State Drive | 691860-B21 |
| HP 400GB 6G SATA Mainstream Endurance LFF 3.5-in SC Enterprise Mainstream 3yr Wty Solid State Drive | 691856-B21 |
| HP 200GB 6G SATA Mainstream Endurance LFF 3.5-in SC Enterprise Mainstream 3yr Wty Solid State Drive | 691854-B21 |
| HP 100GB 6G SATA Mainstream Endurance LFF 3.5-in SC Enterprise Mainstream 3yr Wty Solid State Drive | 691852-B21 |
| 6G SAS Mainstream Endurance Hot Plug SFF (2.5-inch) Enterprise Mainstream Solid State Drives | |
| HP 400GB 6G SAS Mainstream Endurance SFF 2.5-in SC Enterprise Mainstream 3yr Wty Solid State Drive | 690827-B21 |
| NOTE: Please see the QuickSpecs for Technical Specifications and additional information: | |
| http://h18000.www1.hp.com/products/quickspecs/14038_div/14038_div.html (Worldwide) | |
| Hard Drive Kits | |

NOTE: All Factory Integrated Models will be populated with sufficient hard drive blanks based on the number of initial hard drives ordered with the server. **NOTE:** The part numbers for single HDD blanks below are provided should the customer require replacement HDD blanks for their server.

NOTE: The mixing of standard SAS drives with SAS SSD drives is supported within the server, but limits the RAID configuration to two separate RAID 0 volumes. Mixing of other drives types is not supported.



| Core options | | |
|---------------|---|------------|
| | HP Large Form Factor Hard Drive Blank Kit | 666986-B21 |
| | HP Small Form Factor Hard Drive Blank Kit | 666987-B21 |
| HP Networking | Gigabit Ethernet Adapters | |
| | HP NC112T PCI Express Gigabit Server Adapter | 503746-B21 |
| | HP NC365T 4-port Ethernet Server Adapter | 593722-B21 |
| | HP Ethernet 1Gb 2-port 332T Adapter | 615732-B21 |
| | HP Ethernet 1Gb 2-port 361T Adapter | 652497-B21 |
| | 10 Gigabit Ethernet Adapters NOTE: A minimum of two Gigabytes (2 GB) of server memory is required per each adapter. NOTE: Direct Attach Cable (DAC) for copper environments or fiber transceivers and cables for fiber-optic environments must be purchased separately. | |
| | HP NC523SFP 10Gb 2-port Server Adapter | 593717-B21 |
| | HP NC552SFP 10Gb 2-port Ethernet Server Adapter | 614203-B21 |
| | HP Ethernet 10Gb 2-port 560SFP+ Adapter | 665249-B21 |
| | NOTE: Please see the QuickSpecs for Technical Specifications and additional information: http://www.hp.com/go/ProLiantNICs. | |
| | Switches | |
| | HP PS1810-24G Switch | J9834A |
| | NOTE: Please see the QuickSpecs for Technical Specifications and additional information: http://h18004.www1.hp.com/products/quickspecs/14586_div/14586_div.html (Worldwide) | |



Additional Options

NOTE: Some options may not be integrated at the factory. To ensure only valid configurations are ordered, HP recommends the use of an HP approved configurator. Contact your local sales representative for additional information. HP Insight Software HP Insight Control

| HP Insight Software | HP Insight Control |
|------------------------|---------------------------|
| iii iiisigiit soitwait | iii iiisigiit contiot |

HP Insight Control including 1yr 24x7 Technical Support and Updates Single Server C6N27A License

HP Insight Control including 1yr 24x7 Technical Support and Updates Electronic C6N28ABE License

License

NOTE: The Electronic software license is available in EMEA only.

HP Insight Control Server Provisioning Media Kit BD883A
HP Insight Management Media Kit C6N31A

NOTE: Electronic and Flexible-Quantity licenses can be used to purchase multiple licenses with a single activation key.

NOTE: Customer will receive a license entitlement certificate. The license entitlement certificate must be redeemed online or via fax in order to obtain the license activation key(s). Includes one year of 24 x 7 HP Software Technical Support and Update Service.

NOTE: Licenses ship without media. The HP Insight Control Media Kit can be ordered separately, or can be downloaded at: http://www.hp.com/go/insightupdates.

NOTE: For additional license options please see the QuickSpecs at: http://h18000.www1.hp.com/products/quickspecs/12631_div/12631_div.html

HP Integrated Lights-Out (iLO)

HP Integrated Lights-Out (iLO) Advanced for ProLiant

HP iLO Advanced including 1yr 24x7 Technical Support and Updates E-LTU

NOTE: The Electronic software license is available in EMEA only.

HP iLO Advanced including 3yr 24x7 Technical Support and Updates E-LTU

NOTE: The Electronic software license is available in EMEA only.

E6U64ABE

HP iLO Advanced including 1yr 24x7 Technical Support and Updates Single Server 512485-B21 License

HP iLO Advanced 1 Server License with 3yr 24x7 Tech Support and Updates

HP iLO Essentials

HP Integrated Lights-Out Essentials including 3yr 24x7 Technical Support and Updates E-LTU

NOTE: The Electronic software license is available in EMEA only.

HP Integrated Lights-Out Essentials including 1yr 24x7 Technical Support and Updates E-LTU

NOTE: The Electronic software license is available in EMEA only.

HP Integrated Lights-Out Essentials including 3yr 24x7 Tech Support and Updates

BD774A
Single Svr License

HP Integrated Lights-Out Essentials including 1yr 24x7 Tech Support and Updates Single Svr License

NOTE: For additional license options please see the QuickSpecs at:

http://h18004.www1.hp.com/products/quickspecs/14276 div/14276 div.html

NOTE: For more information, visit: http://www.hp.com/go/ilo.

Converged Infrastructure Management Software

HP OneView

HP OneView with iLO Advanced

HP OneView Media Kit Phys No Lic E5Y37A
HP OneView incl 3yr 24x7 Supp Phys 1 Svr Lic E5Y34A



BD505A

E6U61ABE

E6U62ABE

BD775A

Additional Options

| E5Y s and additional liv/14621_div.html | /35AAE E5Y38A /39AAE |
|--|--|
| E5Y s and additional liv/14621_div.html nse Q nse B | /39AAE |
| and additional liv/14621_div.html nse Q nse B | |
| liv/14621_div.html nse Q nse B | |
| nse Q | |
| nse B | |
| nse B | |
| | QL803B |
| e is for one node eement and license itlement certificate stomer also will receive | BD476A |
| В | 3D477A |
| t | |
| liv/12612_div.html. | |
| 48806 | 69-B21 |
| nelp protect user data s not been tampered ut TPM, including a tition required for TPM and must be retained. 66491 | 18-B21 |
| | |
| | |
| S Controller 63166 | 67-B21 |
| | |
| | 73-B21 |
| ler 63167 | 74-B21 |
| | |
| | |
| | 32-B21 |
| | 32-B21 31-B21 |
| 1 t = | o be purchased if a AS Controller 63166 |



Additional Options

| | HP SmartCache No Media 24x7 Technical Support 1 Svr License | D7S26A |
|------------------------|--|------------|
| | HP SmartCache No Media 24x7 Technical Support Flexible License | D7S27A |
| | HP SmartCache No Media 24x7 Technical Support Electronic License | D7S27AAE |
| | NOTE: Please see the QuickSpecs for Technical Specifications and additional information: | |
| | http://h18000.www1.hp.com/products/quickspecs/14227_div/14227_div.html (Smart Array P222 Controller) | |
| | http://h18000.www1.hp.com/products/quickspecs/14229_div/14229_div.html (Smart Array P421 Controller) | |
| | http://h18000.www1.hp.com/products/quickspecs/14625_div/14625_div.html (Smart Array P431 Controller) | |
| | Host Bus Adapter | |
| | HP H221 PCIe 3.0 SAS Host Bus Adapter | 729552-B21 |
| | HP H222 Host Bus Adapter | 650926-B21 |
| | NOTE: Please see the QuickSpecs for Technical Specifications and additional information: | |
| | http://h18004.www1.hp.com/products/quickspecs/14336_div/14336_div.html (HBA 220) | |
| | http://h18004.www1.hp.com/products/quickspecs/14222_div/14222_div.html (HBA 221) | |
| | http://h18004.www1.hp.com/products/quickspecs/14337_div/14337_div.html (HBA 222) | |
| HP Networking Switches | HP PS1810-24G Switch | J9834A |
| | NOTE: Please see the QuickSpecs for Technical Specifications and additional information: | |
| | http://h18004.www1.hp.com/products/quickspecs/14586_div/14586_div.html (Worldwide) | |
| HP Tape Backup | NOTE: For the complete range of tape drives, autoloaders, libraries and media see: http://www.hp.com/go/tape. For hardware and software compatibility of HP tape backup products see: http://www.hp.com/storage/SPOCK and http://www.hp.com/go/ebs. NOTE: For Internal drives to be connected to DL servers please make sure that you | |
| | order rack mount kit as well. | |
| | HP StoreEver LTO-6 Ultrium 6250 Tape Drive in 1U Rack-mount Kit | COL99A |
| | HP StoreEver LTO-6 Ultrium 6650 SAS Internal Tape Drive | EH963A |
| | HP StoreEver LTO-6 Ultrium 6650 SAS External Tape Drive | EH964A |
| | HP StoreEver LTO-6 Ultrium 6250 Internal Tape Drive | EH969A |
| | HP StoreEver LTO-6 Ultrium 6250 External Tape Drive | EH970A |
| | HP StoreEver 1/8 G2 LTO-6 Ultrium 6250 FC Tape Autoloader | COH19A |
| HP Tape Storage | HP StoreEver MSL6480 | |
| Systems | HP StoreEver MSL6480 Scalable Base Module | QU625A |
| | NOTE: Please see the QuickSpecs for Technical Specifications and additional | |
| | information: http://h18000.www1.hp.com/products/quickspecs/14604_div/14604_div.html (Worldwide) | |
| HP Disk Backup | NOTE: For the complete range of RDX drives and media see: http://www.hp.com/go/rdx. For hardware and software compatibility of HP disk | |
| | | |



| Additional Options | | |
|-------------------------|---|--------|
| | backup products see: http://www.hp.com/storage/SPOCK. | |
| | HP RDX Removable Disk Backup System | |
| | HP RDX320 USB3.0 External Disk Backup System | B7B63A |
| | HP RDX500 USB3.0 Internal Disk Backup System | B7B64A |
| | HP RDX500 USB3.0 External Disk Backup System | B7B66A |
| | HP RDX1000 USB3.0 Internal Disk Backup System | B7B67A |
| | HP RDX1000 USB3.0 External Disk Backup System | B7B69A |
| | NOTE: Please see the QuickSpecs for additional part numbers, Technical Specifications, and additional information: http://h18000.www1.hp.com/products/quickspecs/13036_div/13036_div.html (Worldwide) | |
| HP Disk Storage Systems | Disk Enclosures | |
| | HP D2600 w/12 4TB 6G SAS 7.2K LFF Dual Port MDL HDD 48TB Bundle | E7W32A |
| | HP D2600 Disk Enclosure | AJ940A |
| | HP D2700 Disk Enclosure | AJ941A |
| | NOTE: Please see the QuickSpecs for Technical Specifications and additional information: | |
| | http://h18000.www1.hp.com/products/quickspecs/13404_div/13404_div.html (Worldwide) | |
| HP Uninterruptible | HP DirectFlow Three Phase UPS | |
| Power Systems | Power Unit (1U UPS) | |
| | NOTE: #0D1 will appear after the part number on the sales order if HP factory integration is indicated. | |
| | HP R12000 DirectFlow - 1U Rackmount Uninterruptible Power System | G9Y75A |
| | HP R12000 DirectFlow - POD 1U Rackmount Uninterruptible Power System | AF478A |
| | Input/Output Module Options for 1U UPS | |
| | NOTE: Choose one I/O Module per UPS. NOTE: #0D1 will appear after the part number on the sales order if HP factory integration is indicated. | |
| | HP 32A 400-415 Volt Three Phase INTL R12000 DirectFlow UPS IEC309 Input/Output Module | AF488A |
| | HP 30A 400-415 Volt Three Phase NA R10000 DirectFlow UPS IEC309 Input/Output Module | AF489A |
| | HP 32A 380 Volt Three Phase China R12000 DirectFlow UPS Unterminated Input/Output Module | AF490A |
| | HP 30A 480 Volt Three Phase NA R12000 DirectFlow UPS L22-30 Input/Output Module | AF491A |
| | HP 30A 480 Volt Three Phase NA R12000 DirectFlow UPS IEC309 Input/Output Module | AF492A |
| | HP 30A 400-415 Volt Three Phase NA R12000 DirectFlow UPS IEC309 Input/Output Module | G9Y76A |
| | NOTE: All Input/Output Modules support dual output outlets except the AF484A. Power Unit (2U UPS) | |
| | NOTE: #0D1 will appear after the part number on the sales order if HP factory integration is indicated. | |
| | HP R18000 DirectFlow - 2U Rackmount Uninterruptible Power System | AF479A |



Additional Options

| Input/Output Module Options for 2U UPS | |
|---|--------|
| NOTE: Choose one I/O Module per UPS. | |
| NOTE: #0D1 will appear after the part number on the sales order if HP factory integration is indicated. | |
| HP 32A 400-415 Volt Three Phase INTL R18000 DirectFlow UPS IEC309 Input/Output Module | AF483A |
| HP 30A 380 Volt Three Phase China R18000 DirectFlow UPS Unterminated Input/Output Module | AF485A |
| HP 30A 480 Volt Three Phase NA R18000 DirectFlow UPS IEC309 Input/Output Module | AF486A |
| HP 30A 480 Volt Three Phase NA R18000 DirectFlow UPS IEC309 Input/Output Module | AF487A |
| HP 30A 400 Volt Three Phase NA R18000 DirectFlow UPS IEC309 Input/Output Module | D9Q02A |
| HP 30A 400-415V Three Phase NA R18000 DirectFlow UPS 1:1 IEC309 Input/Output Module | AF484A |
| NOTE: All Input/Output Modules support dual output outlets except the AF484A. | |
| Battery Pack Options | |
| NOTE: Choose up to two Battery Packs per UPS (must be the same). NOTE: #0D1 will appear after the part number on the sales order if HP factory integration is indicated. | |
| HP DirectFlow UPS - 1U Rackmount Lithium-ion Battery Pack | AF480A |
| HP DirectFlow UPS - 3U Rackmount VRLA Battery Pack | AF482A |
| NOTE: Please see the QuickSpecs for additional information: http://www8.hp.com/h20195/v2/GetHtml.aspx?docname=c04376695 (Worldwide) | |
| HP Rack/Tower UPS | |
| HP R/T2200 G4 UPS Models | |
| HP R/T2200 G4 NA/JP Uninterruptible Power System | J2R00A |
| HP R/T3000 G4 UPS Models | |
| HP R/T3000 G4 Low Voltage NA/JP Uninterruptible Power System | J2R01A |
| HP R/T3000 G4 High Voltage NA/JP Uninterruptible Power System | J2R02A |
| HP R/T3000 G4 High Voltage INTL Uninterruptible Power System | J2R04A |
| HP R/T3000 G2 Uninterruptible Power System (UPS) | |
| HP R/T3000 G2 2U L530 Low Voltage NA/JP Uninterruptible Power System | AF466A |
| HP R/T3000 G2 2U L620 High Voltage NA/JP Uninterruptible Power System | AF467A |
| HP R/T3000 G2 2U Detachable Cord High Voltage INTL Uninterruptible Power System | AF468A |
| HP Rack Models | |
| R1500 G4 Models | |
| HP R1500 G4 NA Uninterruptible Power System | J2Q99A |
| HP R1500 G4 JP/TWN Uninterruptible Power System | J2R05A |
| HP R1500 G4 INTL Uninterruptible Power System | J2R03A |
| R1.5kVA G3 Models | |
| HP R1.5kVA G3 1U NA Uninterruptible Power System | AF469A |
| HP R1.5kVA G3 1U JP/TW Uninterruptible Power System | AF470A |
| HP R1.5kVA G3 1U INTL Uninterruptible Power System | AF471A |
| R7000 | |



Additional Options

HP R7KVA 4U 50A High Voltage Uninterruptible Power System AF462A

R5000

HP R5KVA 3U L630 High Voltage Uninterruptible Power System

AF460A

NOTE: Please see the QuickSpecs for additional information:

http://www8.hp.com/h20195/v2/GetHtml.aspx?docname=c04154342 (Worldwide)

NOTE: For additional information on HP Uninterruptible Power Systems please go to: http://www.hp.com/servers/rackups.

NOTE: For additional information on sizing your HP UPS, please reference: http://www.upssizer.com

NOTE: Please see the UPS and PDU cable matrix's on the HP Power Protection and Management page. Under Power Cords, click on the "HP Power Cord Matrix" link. That link will list cable descriptions, requirements, and specifications for UPS and PDU units. Please see the following link: http://www.hp.com/products/powercords.

HP Basic Power Distribution Units (bPDU) HP 1 9kVA 120 Volt I 5-20 Input (12xNEMA 5-20R) NA/JP Basic PDU

HP Basic Power Distribution Unit: 1U/0U Version

| HP 1.9kVA 120 Volt L5-20 Input (12xNEMA 5-20R) NA/JP Basic PDU | H5M54A |
|---|--------|
| HP 3.6kVA 200-240 Volt Detachable C20 Input (12xC13) WW Basic PDU | H5M56A |
| HP Basic Power Distribution Unit: Half Height Version | |
| HP 2.8kVA 120 Volt L5-30 Input (18xNEMA 5-20R) NA/JP Basic PDU | H5M55A |
| HP 3.6kVA 200-240 Volt Detachable C20 Input (18xC13) WW Basic PDU | H5M57A |
| HP 4.9kVA 208 Volt L6-30 Input (20xC13) NA/JP Basic PDU | H5M58A |
| HP 7.3kVA 230 Volt IEC309 32A Input (20xC13) INTL Basic PDU | H5M68A |
| HP 8.6kVA 208 Volt L15-30 3-Phase Input (18xC13) NA/JP Basic PDU | H5M61A |
| HP Basic Power Distribution Unit: Mid Height Version | |
| HP 4.9kVA 208 Volt L6-30 Input (24xC13/6xC19) NA/JP Basic PDU | H5M59A |
| HP 7.3kVA 230 Volt IEC309 32A Input (24xC13/6xC19) INTL Basic PDU | H5M70A |
| HP 8.3kVA 208 Volt CS8265C Input (30xC13/6xC19) NA/JP Basic PDU | H5M60A |
| HP 11kVA 230 Volt IEC309 63A Input (30xC13/6xC19) INTL Basic PDU | H5M71A |
| HP Hardwired 200-240 Volt Input (30xC13/6xC19) WW Basic PDU | H5M75A |
| HP 5.7kVA 208 Volt L21-20 3-Phase Input (24xC13/3xNEMA 5-20R) NA/JP Basic PDU | H5M63A |
| HP 8.6kVA 208 Volt L21-30 3-Phase Input (24xC13/3xC19/3xNEMA 5-20R) NA/JP Basic PDU | H5M64A |
| HP 8.6kVA 208 Volt L15-30 3-Phase Input (24xC13/6xC19) NA/JP Basic PDU | H5M62A |
| HP 11kVA 400 Volt IEC309 16A 3-Phase Input (30xC13/6xC19) INTL Basic PDU | H5M72A |
| HP Basic Power Distribution Unit: Full Height Version | |
| HP 11kVA 400 Volt IEC309 16A 3-Phase Input (36xC13/6xC19) INTL Basic PDU | H5M73A |
| HP 11kVA 400 Volt IEC309 30A 3-Phase Input (36xC13/6xC19) NA Basic PDU | H5M67A |
| HP Basic Power Distribution Unit: 480/277 Volt Version | |
| HP 13.2kVA 480 Volt IEC309 30A 3-Phase Input (15 Outlet) NA Basic PDU | H3X07A |
| HP 19.9kVA 480 Volt IEC309 30A 3-Phase Input (30 Outlet) NA Basic PDU | H3X08A |
| HP 800VA - 277V Input / 230V Output NA Rack Mount Transformer | H3X09A |
| NOTE: Please see the QuickSpecs for additional information: http://h18000.www1.hp.com/products/quickspecs/14669_div/14669_div.html | |
| (Worldwide) | |

HP Remote Monitored

HP Remote Monitored Power Distribution Unit: 1U Version



| Additional Options | | |
|---------------------------|---|--------|
| Power Distribution Units | HP 2.8kVA 120 Volt L5-30 Input (12xNEMA 5-20R)NA/JP Monitored PDU | D9N43A |
| (mPDU) | HP 3.6kVA 200-240 Volt Detachable C20 Input (12xC13) WW Monitored PDU | D9N46A |
| | HP 4.9kVA 208 Volt L6-30 Input (12xC13) NA/JP Monitored PDU | D9N44A |
| | HP Remote Monitored Power Distribution Unit: Half Height Version | |
| | HP 3.6kVA 200-240 Volt Detachable C20 Input (16xC13) WW Monitored PDU | D9N45A |
| | HP 4.9kVA 208 Volt L6-30 Input (12xC13) NA/JP Monitored PDU | G9Z05A |
| | HP 7.3kVA 230 Volt IEC309 32A Input (12xC13) INTL Monitored PDU | G9Z06A |
| | HP Remote Monitored Power Distribution Unit: Mid Height Version | |
| | HP 4.9kVA 208 Volt L6-30 Input (20xC13/4xC19) NA/JP Monitored PDU | D9N47A |
| | HP 7.3kVA 230 Volt IEC309 32A Input (20xC13/4xC19) INTL Monitored PDU | D9N48A |
| | HP 8.6kVA 208 Volt L15-30 3-Phase Input (18xC13/3xC19) NA/JP Monitored PDU | D9N51A |
| | HP 5.7kVA 208 Volt L21-20 3-Phase Input (18xC13/3xNEMA 5-20R) NA/JP Monitored PDU | D9N52A |
| | HP 8.6kVA 208 Volt L21-30 3-Phase Input (20xC13/3xC19/3xNEMA 5-20R) NA/JP Monitored PDU | D9N53A |
| | HP 11kVA 400 Volt IEC309 16A 3-Phase Input (18xC13/3xC19) INTL Monitored PDU | D9N55A |
| | HP Remote Monitored Power Distribution Unit: Full Height Version | |
| | HP 8.3kVA 208 Volt CS8265C Input (30xC13/3xC19) NA Monitored PDU | D9N49A |
| | HP 7.3kVA 230 Volt IEC309 32A Input (32xC13/4xC19) INTL Monitored PDU | D9N50A |
| | HP 11kVA 400 Volt IEC309 16A 3-Phase Input (30xC13/3xC19) INTL Monitored PDU | D9N57A |
| | HP 14.4kVA 208 Volt CS8365C 3-Phase Input (12xC13/12xC19)NA Monitored PDU | D9N58A |
| | HP 16.6kVA 400 Volt IEC309 30A 3-Phase Input (30xC13/3xC19) NA Monitored PDU | D9N61A |
| | HP 17.3kVA 208 Volt IEC309 60A 3-Phase Input (24xC13/3xC19) NA/JP Monitored PDU | D9N54A |
| | HP 17.3kVA 208 Volt IEC309 60A 3-Phase Input (12xC13/12xC19) NA/JP Monitored PDU | D9N59A |
| | HP 22kVA 400 Volt IEC309 32A 3-Phase Input (12xC13/12xC19) INTL Monitored PDU | D9N60A |
| | HP 22kVA 400 Volt IEC309 32A 3-Phase Input (30xC13/3xC19) INTL Monitored PDU | D9N56A |
| | HP 16.6kVA 400 Volt IEC309 30A 3-Phase Input (12xC13/12xC19) NA Monitored PDU | D9N62A |
| | HP 19.9kVA 480 Volt 3-Phase (30 Outlet) NA Monitored PDU | D9N63A |
| | HP Environmental Sensor for Remote Monitored PDUs | |
| | HP Environmental Sensor for Remote Monitored PDUs | E2D53A |
| | NOTE: Please see the QuickSpecs for additional information: http://h18000.www1.hp.com/products/quickspecs/14669_div/14669_div.html (Worldwide) | |
| HP Intelligent Power | iPDU Core Units | |
| Distribution Units (iPDU) | HP 4.9kVA 24A Single Phase NA/JP Core Intelligent Modular Power Distribution Unit | AF520A |
| | HP 8.3kVA 40A Single Phase NA/JP Core Intelligent Modular Power Distribution Unit | AF521A |
| | HP 8.6kVA 24A Three Phase NA/JP Core Intelligent Modular Power Distribution Unit | AF522A |
| | HP 14.4kVA 40A Three Phase NA/JP Intelligent Modular Power Distribution Unit | AF533A |
| | HP 17.3kVA 48A Three Phase NA/JP Core Intelligent Modular Power Distribution Unit | AF523A |
| | HP 7.3kVA 32A Single Phase INTL Core Intelligent Modular Power Distribution Unit | AF525A |
| | HP 11kVA 16A Three Phase INTL Core Intelligent Modular Power Distribution Unit | AF526A |



HP 17.3kVA 48A 208V Three Phase 12 Outlet Core NA/JP Intelligent Power

HP 22kVA 32A Three Phase INTL Core Intelligent Modular Power Distribution Unit

AF527A

AF535A

Additional Options

| | Distribution Unit | |
|--------------------|--|--------|
| | HP 17.3kVA 24A 415V Three Phase 12 Outlet Core NA/JP Intelligent Power Distribution Unit | AF537A |
| | HP 22kVA 32A 400V Three Phase 12 Outlet Core INTL Intelligent Power Distribution Unit | AF538A |
| | iPDU Kits with Standard Extension Bars | |
| | HP 4.9kVA 24A Single Phase NA/JP Intelligent Modular Power Distribution Kit | AF531A |
| | HP 8.6kVA 24A Three Phase NA/JP Intelligent Modular Power Distribution Kit | AF532A |
| | HP 7.3kVA 32A Single Phase INTL Intelligent Modular Power Distribution Kit iPDU Extension Bars | AF534A |
| | HP 5xC13 Intelligent PDU Extension Bar G2 Kit | AF547A |
| | HP 5xC13 Outlets Power and UID LEDs Pair Standard Extension Bar | AF528A |
| | NOTE: Please see the QuickSpecs for Technical Specifications and additional information: http://h18000.www1.hp.com/products/quickspecs/13650_div/13650_div.html (Worldwide) | |
| HP Managed Power | Half Height Models | |
| Distribution Units | HP 3.6kVA 200-240 Volt Detachable C20 Input (7xC13/1xC19) WW Managed PDU | H8B49A |
| (maPDU) | Full Height Models | ПОВЧЭН |
| | HP 2.8kVA 120 Volt L5-30 Input (24x NEMA 5-20) NA/JP Managed PDU | H8B48A |
| | HP 4.9kVA 208 Volt L6-30 Input (20xC13/4xC19) NA/JP Managed PDU | H8B50A |
| | HP 7.3kVA 200-240 Volt IEC309 32A Input (20xC13/4xC19) INTL Managed PDU | H8B51A |
| | HP 8.6kVA 208 Volt L15-30 3 Phase Input (18xC13/6xC19) NA/JP Managed PDU | H8B52A |
| | HP 8.6kVA 208 Volt L21-30 3 Phase Input (20xC13/3xC19/1x NEMA 5-20) NA/JP Managed PDU | H8B53A |
| | HP 11kVA 400 Volt IEC309 16A 3 Phase Input (21xC13/3xC19) INTL Managed PDU | H8B54A |
| | HP 14.4kVA 208V CS8365C 3 Phase Input (12xC13/12xC19) NA/JP Managed PDU | H8B55A |
| | HP 17.3kVA 208V IEC309 60A 3 Phase Input (12xC13/12xC19) NA/JP Managed PDU | H8B56A |
| | NOTE: Please see the QuickSpecs for Technical Specifications and additional information: | |
| | http://www8.hp.com/h20195/v2/GetHtml.aspx?docname=c04376673 (Worldwide) | |
| HP Rack Series | HP Intelligent Series Racks | |
| | HP 636 1075mm Pallet Intelligent Series Rack | BW895A |
| | HP 636 1075mm Shock Intelligent Series Rack | BW896A |
| | HP 642 1075mm Pallet Intelligent Series Rack | BW903A |
| | HP 642 1075mm Shock Intelligent Series Rack | BW904A |
| | HP 647 1075mm Pallet Intelligent Series Rack | BW911A |
| | HP 647 1075mm Shock Intelligent Series Rack | BW912A |
| | NOTE: Please see the QuickSpecs for Technical Specifications such as height, width, depth, weight, and color: http://h18000.www1.hp.com/products/quickspecs/14223_div/14223_div.html (Worldwide) | |
| HP Rack Options | (Worldwide) HP LCD8500 1U Rackmount Console Kit Models | |



Additional Options

| HP LCD8500 1U US Rackmount Console Kit | AF630A |
|--|------------|
| HP LCD8500 1U UK Rackmount Console Kit | AF631A |
| HP LCD8500 1U DE Rackmount Console Kit | AF632A |
| HP LCD8500 1U FR Rackmount Console Kit | AF633A |
| HP LCD8500 1U JP Rackmount Console Kit | AF642A |
| HP LCD8500 1U RU Rackmount Console Kit | AF643A |
| HP LCD8500 1U INTL Rackmount Console Kit | AF644A |
| HP LCD8500 1U US TAA Rackmount Console Kit | AF645A |
| HP TFT7600 G2 KVM Console and Monitor Models | |
| HP TFT7600 G2 KVM Console Rackmount Keyboard US Monitor | AZ870A |
| HP TFT7600 G2 KVM Console Rackmount Keyboard UK Monitor | AZ871A |
| HP TFT7600 G2 KVM Console Rackmount Keyboard DE Monitor | AZ872A |
| HP TFT7600 G2 KVM Console Rackmount Keyboard FR Monitor | AZ873A |
| HP TFT7600 G2 KVM Console Rackmount Keyboard IT Monitor | AZ874A |
| HP TFT7600 G2 KVM Console Rackmount Keyboard ES Monitor | AZ875A |
| HP TFT7600 G2 KVM Console Rackmount Keyboard DK Monitor | AZ876A |
| HP TFT7600 G2 KVM Console Rackmount Keyboard NO Monitor | AZ877A |
| HP TFT7600 G2 KVM Console Rackmount Keyboard SE/FI Monitor | AZ878A |
| HP TFT7600 G2 KVM Console Rackmount Keyboard CH Monitor | AZ879A |
| HP TFT7600 G2 KVM Console Rackmount Keyboard PT Monitor | AZ880A |
| HP TFT7600 G2 KVM Console Rackmount Keyboard BE Monitor | AZ881A |
| HP TFT7600 G2 KVM Console Rackmount Keyboard JP Monitor | AZ882A |
| HP TFT7600 G2 KVM Console Rackmount Keyboard RU Monitor | AZ883A |
| HP TFT7600 G2 KVM Console Rackmount Keyboard Intl Monitor | AZ884A |
| HP TFT7600 G2 KVM Console Rackmount Keyboard US TAA Monitor | AZ885A |
| HP LCD8500 1U Rackmount Console Kit Options | |
| HP Kit LCD 1.83m Latch Display Port Cable | G7T29A |
| HP Location Discovery Services LCD8500 Kit | TL052A |
| NOTE: Please see the QuickSpecs for Technical Specifications and additional | |
| information: http://h18000.www1.hp.com/products/quickspecs/13731_div/13731_div.html | |
| (Worldwide) | |
| HP USB Keyboard and Mouse | |
| HP USB BFR with PVC Free US Keyboard/Mouse Kit | 631341-B21 |
| HP USB BFR with PVC Free UK Keyboard/Mouse Kit | 631344-B21 |
| HP USB BFR with PVC Free FR Keyboard/Mouse Kit | 631346-B21 |
| HP USB BFR with PVC Free ES Keyboard/Mouse Kit | 631348-B21 |
| HP USB BFR with PVC Free DE Keyboard/Mouse Kit | 631358-B21 |
| HP USB BFR with PVC Free JP Keyboard/Mouse Kit | 631360-B21 |
| HP USB BFR with PVC Free IT Keyboard/Mouse Kit | 631362-B21 |
| HP USB BFR with PVC Free CN Keyboard/Mouse Kit | 631364-B21 |
| HP USB BFR with PVC Free AE Keyboard/Mouse Kit | 638212-B21 |
| HP USB BFR with PVC Free RU Keyboard/Mouse Kit | 638214-B21 |
| | |



HP USB BFR with PVC Free IN Keyboard/Mouse Kit

HP USB BFR with PVC Free AP-Intl Keyboard/Mouse Kit

672097-D63

672097-373

Additional Options

| HP USB BFR with PVC Free Intl Keyboard/Mouse Kit | 672097-B33 |
|---|------------|
| HP USB BFR with PVC Free PT Keyboard/Mouse Kit | 672097-133 |
| HP USB BFR with PVC Free TR Keyboard/Mouse Kit | 672097-143 |
| HP USB BFR with PVC Free CZ Keyboard/Mouse Kit | 672097-223 |
| HP USB BFR with PVC Free FI Keyboard/Mouse Kit | 672097-353 |
| HP USB BFR with PVC Free SE Keyboard/Mouse Kit | 672097-103 |
| HP USB BFR with PVC Free CH Keyboard/Mouse Kit | 672097-113 |
| HP USB BFR with PVC Free KR Keyboard/Mouse Kit | 672097-KD3 |
| NOTE: Please see the QuickSpecs for Technical Specifications and additional information: | |
| http://h18000.www1.hp.com/products/quickspecs/13972_div/13972_div.html (Worldwide) | |
| HP Server Console Switches | |
| HP Server Console 0x2x8 Port Analog Switch | AF616A |
| HP Server Console 0x2x16 Port Analog Switch | AF617A |
| HP TAA 0x2x16xKVM Server Console G2 Switch | AF626A |
| HP 0x1x8 G3 KVM Console Switch | AF651A |
| HP 0x2x16 G3 KVM Console Switch | AF652A |
| HP TAA 0x2x16 G3 KVM Console Switch | AF653A |
| HP USB Remote Access Key for G3 KVM Console Switches | AF650A |
| NOTE: Please see the QuickSpecs for Technical Specifications and additional | |
| information: | |
| http://h18000.www1.hp.com/products/quickspecs/11834_div/11834_div.html (Worldwide) | |
| HP Server Console Switch G2 with Virtual Media & CAC | |
| HP 0x2x16 KVM Server Console Switch G2 with Virtual Media CAC Software | AF618A |
| HP 0x2x32 KVM Server Console Switch G2 with Virtual Media CAC Software | AF619A |
| HP KVM CAT5 1-pack USB Interface Adapter | 336047-B21 |
| NOTE: Please see the QuickSpecs for Technical Specifications and additional | |
| information: | |
| http://h18000.www1.hp.com/products/quickspecs/13475_div/13475_div.html (Worldwide) | |
| HP 1x4 USB/PS2 KVM Console Switch | |
| HP 1x4 USB/PS2 KVM Console Switch | AF611A |
| HP 1x1Ex8 KVM IP Console Switch G2 with Virtual Media CAC Software | AF620A |
| HP 2x1Ex16 KVM IP Console Switch G2 with Virtual Media CAC Software | AF621A |
| HP 4x1Ex32 KVM IP Console Switch G2 with Virtual Media CAC Software | AF622A |
| NOTE: Please see the QuickSpecs for Technical Specifications and additional | AFUZZA |
| information: | |
| http://h18000.www1.hp.com/products/quickspecs/13474_div/13474_div.html (Worldwide) | |
| Rail Kits | |
| HP 1U Friction Gen8 Rail Kit | 727604-B21 |
| HP 1U Short Friction Rail Kit | 775612-B21 |
| HP Flash Media Kits for USB Drives | |
| HP 8GB USB Enterprise Mainstream Flash Media Drive Key Kit | 737953-B21 |
| - | |



HP USB and SD Options

Additional Options

HP Enterprise Mainstream Flash Media Kits for Memory Cards

HP 3 year 4 hour 24x7 ProLiant DL320e Proactive Care Service

HP 8GB microSD Enterprise Mainstream Flash Media Kit

726116-B21

U6F03E

NOTE: Please see the QuickSpecs for Technical Specifications and additional information:

http://h18000.www1.hp.com/products/quickspecs/13971_div/13971_div.html (Worldwide)

HP Care Pack Services

Proactive Care

NOTE: Collaborative Support plus Proactive services delivered by the onshore, local language Advanced Solution Center (ASC), end-to-end case ownership from a Technical Solution Specialists and Technical Account Manager who remotely delivers firmware/software revision management, proactive scans and incident trend reports. Recommended for customers running a virtualized infrastructure and/or customers who desire an enhanced call support experience.

| HP 3 year 4 hour 24x7 with Defective Media Retention ProLiant DL320e Proactive Care Service | U6F04E |
|--|--------|
| HP 3 year 6 hour Call to Repair 24x7 ProLiant DL320e Proactive Care Service | U6F09E |
| HP 3 year 6 hour Call to Repair 24x7 w/Defective Media Retention ProLiant DL320e Proactive Care SVC | U6F10E |

HP 3 year Next business day ProLiant DL320e Proactive Care Service

HP 3 year Next business day with Defective Media Retention ProLiant DL320e

Proactive Care Service

U6E95E

U6E96E

Installation Services

NOTE: Reduce the time required to get your system up and running and help minimize disruptions to your business.

| HP Installation ProLiant DL320e Service | U6F51E |
|--|--------|
| HP Installation non Standard Hours ProLiant DL320e Service | U6F52E |
| HP Startup ProLiant DL320e Service | U6F53E |
| HP Startup non Standard Hours Proliant DL320e Service | U6F54E |

NOTE: For more information, customer/resellers can contact: http://www.hp.com/services/carepack



Memory

HP SmartMemory

New HP SmartMemory now provides additional protection for your servers. With HP Authentication it can verify that you have true HP Qualified Memory in your HP ProLiant Gen8 server. With HP SmartMemory your new HP ProLiant server can take advantage of additional Gen8 enhancements in performance, durability and future manageability support through HP Active Health System

For detailed memory configuration rules and guidelines, please use the Online DDR3 Memory Configuration Tool: http://www.hp.com/go/ddr3memory-configurator

Memory Subsystem Architecture

Intel Processor socket supports 2 channels and 2 DIMMs per channel. Total max. memory up to 32GB DDR3 PC3-12800E1600MHz.

Standard Memory Plus Optional Memory

Up to 32 GB memory is available with the optional installation of 4 x 8GB PC3-12800E UDIMM ECC DDR3 UDIMM Memory kits, operating at 1600MHz when fully populated at 2 DIMMs per Channel in 4 slots.

NOTE: The below chart does not represent all possible memory configurations.

NOTE: For best performance, it is recommended that customer installs memory in identical pairs

General Memory Population Rules and Guidelines:

- The HP ProLiant DL320e Gen8v2Server has four memory slots
- There are two channels per server with two DIMM slot per channel
- Memory channel A consists of the two (2) DIMMs that are closest to the processor
- Memory channel B consists of the two (2) DIMMs that are furthest from the processor
- Different types of processors have different types of memory support.
- Support for single/dual-rank 1333/1600 MT/s ECC UDIMM (unbuffered DIMMS)
- The server supports up to 32 GB (4 x 8-GB) for Unbuffered DIMMs
- No support for RDIMMs; Non-ECC UDIMMs
- Do not install DIMMs if the processor is not installed
- Populate DIMMs from heaviest load (double-rank) to lightest load (single-rank)
- Always use HP qualified DIMM

Farthest DIMM (either CHA or CHB) should always be populated first

| The UDIMM installing sequence: | | | | | |
|--------------------------------|-------|--------|--------|--------|--------|
| Memory | | Slot | | | |
| | | DIMM4C | DIMM3A | DIMM2D | DIMM1B |
| Standard | 4 GB | Empty | 4 GB | Empty | Empty |
| (Base Model) | | | | | |
| Standard | 8 GB | Empty | 8 GB | Empty | Empty |
| (Performance Model) | | | | | |
| Maximum | 32 GB | 8 GB | 8 GB | 8 GB | 8 GB |

| Memory Speed by Processor Model | |
|---|-------------------------|
| Processor Models | Supported Memory Speeds |
| E3-1220v3, E3-1230v3, E3-1230Lv3, E3-1240v3, E3-1270v3, E3-1280v3, E3-1265Lv3, i3-4130, i3-4130T, G3420, E3-1231v3, E3-1241v3, E3-1271v3, E3-1281v3, i3-4150, G3240 | 1600/1333MHz |
| G3220 | 1333MHz |

Following are memory options available from HP:



Memory

HP Memory

NOTE: To realize the performance memory capabilities listed in this document, HP SmartMemory is required. For additional information, please see the HP SmartMemory QuickSpecs at:

http://h18000.www1.hp.com/products/quickspecs/14225_div/14225_div.html (Worldwide)

NOTE: HP memory from previous generation servers are not fully compatible with the DL320e Gen8 Server.

Unbuffered with ECC DIMMs (UDIMMs)

| HP 2GB (1x2GB) Single Rank x8 PC3L-12800E (DDR3-1600) Unbuffered CAS-11 Low Voltage Memory Kit | 713975-B21 |
|---|------------|
| HP 4GB (1x4GB) Dual Rank x8 PC3L-12800E (DDR3-1600) Unbuffered CAS-11 Low Voltage Memory Kit | 713977-B21 |
| HP 8GB (1x8GB) Dual Rank x8 PC3L-12800E (DDR3-1600) Unbuffered CAS-11 Low Voltage Memory Kit | 713979-B21 |
| Unbuffered with ECC DIMMs (UDIMMs) | |
| HP 2GB (1x2GB) Single Rank x8 PC3-12800E (DDR3-1600) Unbuffered CAS-11 Memory Kit | 669320-B21 |

HP 2GB (1x2GB) Single Rank x8 PC3L-10600E (DDR3-1333) Unbuffered CAS-9 Low 647905-B21 Voltage Memory Kit

HP 4GB (1x4GB) Dual Rank x8 PC3-12800E (DDR3-1600) Unbuffered CAS-11 669322-B21

Memory Kit

HP 4GB (1x4GB) Dual Rank x8 PC3L-10600E (DDR3-1333) Unbuffered CAS-9 Low
Voltage Memory Kit

HP 8GB (1x8GB) Dual Rank x8 PC3-12800E (DDR3-1600) Unbuffered CAS-11 Memory 669324-B21

HP 8GB (1x8GB) Dual Rank x8 PC3L-10600E (DDR3-1333) Unbuffered CAS-9 Low Voltage Memory Kit

NOTE: All DDR3 memory option kits consist of one DIMM per kit. For detailed memory configuration rules and guidelines, please use the Online DDR3 Memory Configuration Tool: http://www.hp.com/go/ddr3memory-configurator. **NOTE:** Kits described as LP include Low Power DIMMs. For more information on ProLiant Energy Efficient Features, see: http://www.hp.com/go/proliant-energy-

NOTE: PC3L is a low voltage memory.

efficient.




647907-B21


647909-B21

Storage

- 1 2 2 x 3.5" (LFF) SAS/SATA hard drive bays
 - A Optical Drive Bay: Optional DVD-RW drive



- 1 4 4 x 2.5" (SFF) SAS/SATA hard drive bays
 - A Optical Drive Bay: Optional DVD-RW drive



Technical Specifications

| System Unit Dimensions (H x W x D) | 4 SFF | 1.7 x 17.11 x 15.07 inches (4.32 x 43.46 x 38.30 |
|---|-------|--|
|---|-------|--|

cm)

2 LFF 1.7 x 17.11 x 15.07 inches (4.32 x 43.46 x 38.30

cm)

Weight (approximate) Maximum 4 SFF - 8.0 kg, 17.64 lb

(Processor, HDD+ Common Slot power supply with 2 PCI cards)

Minimum 2 LFF NHP - 7.0 kg, 15.43 lb

(Processor, one NHP hard drive, ATX power supply, without any Power Supply)

Input Requirements Rated Input Voltage 90 to 264VAC

(HP ProLiant 250 W power

supply)

Maximum Input Current 6 Amps (at 100VAC) to 3 Amps (at 200 VAC)

Rated Input Frequency 47 to 63 Hz

Power Supply Output Rated Steady-State Power 250 W (at 100 VAC), (per power supply) 250 W (at 200 VAC)

NOTE: 250W Power Supplies have approximately 85% efficiency when operating at 230V,50 Hz (under 50% load conditions)

System Inlet Ope Temperature

Operating 10° to 35°C (50° to 95°F) at sea level with an

altitude derating of 1.0°C per every 304.8 m (1.8°F per every 1000 ft) above sea level to a maximum of 3048 m (10,000 ft), no direct sustained sunlight. Maximum rate of change is 10°C/hr (18°F/hr). The upper limit may be limited by the type and number of options

installed.

System performance may be reduced if operating with a fan fault or above 30°C (86°F).

Non-operating -30° to 60°C (-22° to 140°F). Maximum rate of

change is 20°C/hr (36°F/hr).

Relative Humidity Operating

(non-condensing)

10 to 90% relative humidity (Rh), 28°C (82.4°F)

maximum wet bulb temperature, non-

condensing.

Non-operating 5 to 95% relative humidity (Rh), 38.7°C

(101.7°F) maximum wet bulb temperature,

non-condensing.

Altitude Operating 3048 m (10,000 ft). This value may be limited

by the type and number of options installed. Maximum allowable altitude change rate is 457

m/min (1500 ft/min).

Non-operating 9144 m (30,000 ft). Maximum allowable

altitude change rate is 457 m/min (1500

ft/min).

Acoustic Noise Listed are the declared A-Weighted sound power levels (LWAd) and

declared average bystander position A-Weighted sound pressure levels



Technical Specifications

(LpAm) when the product is operating in a 23°C ambient environment. Noise emissions were measured in accordance with ISO 7779 (ECMA 74) and declared in accordance with ISO 9296 (ECMA 109).

Idle

4.8 B (Base Model) LWAd

4.9 B (Performance Model)

32 dBA (Base Model) LpAm

33 dBA (Performance Model)

Operating

LWAd 4.8 B (Base Model)

5.1 B (Performance Model)

LDAm 32 dBA (Base Model)

35 dBA (Performance Model)

NOTE: The Listed sound levels apply to standard shipping configurations.

Additional options may result in increased sound levels

NOTE: Values are subject to change without notification and are for

reference only.

NOTE: Performance of system, options, and ancillary equipment will vary

depending on the system configuration.

NOTE: Levels presented do not account for non-Hewlett-Packard installed

hardware.

Emissions Classification FCC Rating (EMC)

Class A

Normative Standards CISPR 22; EN55022; EN55024; FCC CFR 47, Pt

> 15; ICES-003; CNS13438; GB9254; K22;K24; EN 61000-3-2; EN 61000-3-3; EN 60950-1; IEC

60950-1

NOTE: Product conformance to cited product specifications is based on sample (type) testing, evaluation, or assessment. This product or family of

products is eligible to bear the appropriate compliance logos and

statements.

HP Dynamic Smart Array B120i Controller

Dimensions

Embedded

Disk Drive Interface -

Transfer rate

Up to 6Gb/s SATA (Serial ATA)

SATA Connectors 6 internal SATA connectors

Server Interface x4 PCIe 2.0 SATA Speed 6Gb/s SATA links

Cache Memory Zero Memory RAID has no cache memory **Logical Drives Supported** Up to 8 logical volumes (6 physical drives)

Host Memory Addressing 64-bit, supporting greater than 4GB server memory space

Hot Plug Support Yes

RAID Support RAID 0 (Striping), RAID 1 (Mirroring)

RAID 1+0 (Striping & Mirroring)

HP Ethernet 1Gb 2-port NC332i Adapter

Compatibility

IEEE 802.3 10Base-T IEEE 802.3u 100Base-T IEEE 802.3ab 1000Base-T

IEEE 802.3az 1000Base-T

NOTE: NC332i is also compliant with the IEEE standard 802.az-2010

Technical Specifications

Data Transfer Method PCI Express, one lanes (x1)

NOTE: Speed is 5GT/s

Controller BCM5720

Network Transfer Rate 10Base-T (Half and/or Full-Duplex)

> 100Base-T (Half and/or Full--Duplex) 1000Base-T (Half and/or Full-Duplex)

Connector RJ-45 Cable Support 10Base-T

> 100Base-TX 1000BaseTX

Environment-friendly Products and Approach and Recycling

End-of-life Management Hewlett-Packard offers end-of-life HP product return, trade-in, and recycling programs in many geographic areas. For trade-in information, please go to: http://www.hp.com/go/green. To recycle your product, please go to: http://www.hp.com/go/green or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.

> The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: http://www.hp.com/go/green. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.

Summary of Changes

| Date | Version History | Action | Description of Change: |
|-------------------------------------|--------------------------|--|--|
| 01-March-2015 From Version 16 to 17 | Changed | Common Slot Power and Power Supply information was revised | |
| | | in Standard Features, Pre-Configured Models, and Configuration | |
| | | Information – Factory Integrated Models sections. | |
| | | | Rail Kits was revised in Additional Options section. |
| | | | Technical Specifications section was revised. |
| | | Removed | HP Tower UPS SKUs were removed from Additional Options section. |
| 09-Feb-2015 From Version 15 to 16 | Added | New Hard Drives, DirectFlow UPS, Rack and Tower G4 Models, | |
| | | | LCD8500 1U Rackmount Models and Options were added to the |
| | | | Additional Options section. |
| | | Changed | Service and Support section was revised. |
| | | | HP Uninterruptible Power Systems, HP Rack Options, and HP |
| | | | Care Pack Services in Additional Options section were revised. |
| 01-Dec-2014 | From Version 14 to 15 | Added | HP 1.6TB 6G SATA Value Endurance SFF 2.5-in SC Enterprise |
| | | | Value 3yr Wty Solid State Drive and HP 1.6TB 6G SATA Value |
| | | | Endurance LFF 3.5-in SC Converter Enterprise Value 3yr Wty |
| | | 61 | Solid State Drive were added to HP Hard Drives. |
| 20.5 2014 | | Changed | HP Care Pack Services section has been revised. |
| 29-Sep-2014 From Version 13 to 14 | From Version 13 to 14 | Added | New Solid State Drives were added. |
| | | HP Managed Power Distribution Units (maPDU) was added to Additional Options. | |
| | | Changed | Service and Support section was revised. |
| | | | |
| | | | HP Hard Drives was revised in Core Options section. |
| 18-Aug-2014 | From Version 12 to 13 | Added | New Hard Drives were added. |
| | | | HP Remote mPDUs half height version were added. |
| | | Changed | Standard Features, Configuration Information - Factory |
| | | | Integrated Models, and Technical Specifications sections were |
| 08-July-2014 | From Version 11 to 12 | Changed | revised. Common Slot Power Supply in Standard Features was revised. |
| , | | | |
| | | | Pre-configured Models, and Technical Specifications were |
| | | | revised. |
| | | | HP Power Supplies, and HP Security were revised in |
| | | | Configuration Information – Factory Integrated Models. |
| | | Removed | HP 200GB 6G SAS Mainstream Endurance SFF 2.5-in SC |
| | | | Enterprise Mainstream 3yr Wty Solid State Drive, and 6G SAS |
| | | | SLC Hot Plug SFF (2.5-inch) Enterprise Performance Solid State |
| 10-Jun-2014 | From Version 10 to 11 | Added | Drives were removed from Core Options. 768645-xx1 was added to Performance Models. |
| 10-Juli-2014 | rioiii veisioii 10 to 11 | Changed | Entry and Based Models were revised. |
| | | changea | Zina y and based i lodels were revised. |
| | | | What's new, Standard Features, Configuration Information, |
| | | | Additional Options, Memory and Technical Specifications were |
| | | | revised. |
| 09-May-2014 | From Version 9 to 10 | Changed | Service and Support, Memory, Hard Drives, Storage Controllers, |



Summary of Changes

| | | | Disk Enclosures, and Basic and Remote Monitoring Power Distribution Units were revised. |
|-------------|---------------------|---------|--|
| 13-Dec-2013 | From Version 7 to 8 | Changed | HP Insight Control including 1yr 24x7 Support ProLiant MI/DL/BL-bundle FIO Electronic License was added to Step 3 in Configuration Information |
| | | | HP 1.2TB 6G SAS 10k rpm SFF SC Dual Port Enterprise 3yr Warranty Hard Drive was added to Hard Drives |
| | | | HP SmartCache and HP H221 PCIe 3.0 SAS Host Bus Adapter were added to Storage Controllers |
| | | | HP Basic Power Distribution Units and HP Remote Monitoring Power Distribution Units were revised in Additional Options |
| | | | HP Power Distribution Units was removed from Additional Options |
| 30-Sep-2013 | From Version 6 to 7 | Added | Entry and Base Processors were added |
| | | | Canonical Ubuntu Server was added to Operating Systems and Virtualization Software Support for ProLiant Servers |
| | | | Converged Infrastructure Management Software was added |
| | | | HP Disk Backup was added to Additional Options |
| | | | HP Remote Monitoring Power Distribution Units was added to Additional Options |
| 20-Sep-2013 | From Version 5 to 6 | Changed | HP Dynamic Smart Array B120i Controller in Technical Specifications was revised. |
| 10-Sep-2013 | From Version 4 to 5 | Changed | HP Insight Management, Memory, Hard Drives, Networking, High Performance Clusters, Storage Controllers, HP Power |
| 20-Aug-2013 | From Version 3 to 4 | Changed | Distribution Units, and HP Care Pack Services were revised. Changes made to correct the overview image. |
| 19-Aug-2013 | From Version 2 to 3 | Changed | Changes made in the North America and Canada versions only. |
| 26-Jul-2013 | From Version 1 to 2 | Changed | Corrected the second image in the Storage section. |

© Copyright 2015 Hewlett-Packard Development Company, L.P.

The information contained herein is subject to change without notice.

Microsoft and Windows NT are US registered trademarks of Microsoft Corporation.

AMD, the AMD Arrow logo, AMD Opteron™, and combinations thereof, are trademarks of Advanced Micro Devices, Inc.

The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

For hard drives, 1GB = 1 billion bytes. Actual formatted capacity is less.

