



Quick Search Hierarchy

Quick Search: 19829AR Search
Product Number : 19829AR
Description : HP 5400R 1100W POE+ ZL2 POWER SUPPLY

Updated SBOM available

Show Functional Equivalents

General(Product Family)Advanced(Unique Product S/N)

Customize your search results								
17 records found								
Category								
Keyword								
	Add to Cart	Click to Buy	Part Number	Part Description	Most Used	CSR	Tech Courier	RoHS
Power Supplies and Parts								
Power Cord	IMPORTANT NOTE! >>							
			8120-5338	Power cord (Black) - 3-wire, 2.5m (8.2ft) long - Has straight (F) C15 receptacle with a 'U' shaped channel above the ground pin to prevent use of a lower rated power cord (For 240VAC in Japan, the USA, and Canada)		N	-N/A-	COMPLY_2012
			8121-0914	Power cord - 3-wire, 2.5m (8.2ft) long - Has straight (F) C15 receptacle with a 'U' shaped channel above the ground pin to prevent use of a lower rated power cord (For 120VAC in the United States, Canada, and Mexico)		A	-N/A-	COMPLY_5012
			8121-1474	Power cord - 3-wire, 2.5m (8.2ft) long - Has straight (F) C15 receptacle with a 'U' shaped channel above the ground pin to prevent use of a lower rated power cord (For 127VAC in Brazil)		A	-N/A-	COMPLY_2012
			8121-1475	Power cord - 3-wire, 2.5m (8.2ft) long - Has straight (F) C15 receptacle with a 'U' shaped channel above the ground pin to prevent use of a lower rated power cord (For 220VAC to 240VAC in the United Kingdom, Hong Kong, Singapore, and Malaysia)		A	-N/A-	COMPLY_5012
			8121-1476	Power cord - 3-wire, 2.5m (8.2ft) long - Has straight (F) C15 receptacle with a 'U' shaped channel above the ground pin to prevent use of a lower rated power cord (For 230/240VAC in Australia and New Zealand)		A	-N/A-	COMPLY_2106
			8121-1477	Power cord - 3-wire, 2.5m (8.2ft) long - Has straight (F) C15 receptacle with a 'U' shaped channel above the ground pin to prevent use of a lower rated power cord (For 220VAC in Chile)		A	-N/A-	COMPLY_2106
			8121-1478	Power cord (Black) - 3-wire, 2.5m (8.2ft) long - Has straight (F) C15 receptacle with a 'U' shaped channel above the ground pin to prevent use of a lower rated power cord (For 220VAC in Israel)		A	-N/A-	COMPLY_5012
			8121-1479	Power cord - 3-wire, 2.5m (8.2ft) long - Has straight (F) C15 receptacle with a 'U' shaped channel above the ground pin to prevent use of a lower rated power cord (For 220VAC in Europe)		A	-N/A-	COMPLY_2106
			8121-1480	Power cord (Black) - 3-wire, 2.5m (8.2ft) long - Has straight (F) C15 receptacle with a 'U' shaped channel above the ground pin to prevent use of a lower rated power cord (For 230VAC in Switzerland)		A	-N/A-	COMPLY_5012
			8121-1481	Power cord - 3-wire, 2.5m (8.2ft) long - Has straight (F) C15 receptacle with a 'U' shaped channel above the ground pin to prevent use of a lower rated power cord (For 220VAC in Argentina)		A	-N/A-	COMPLY_5012
			8121-1483	Power cord (Black) - 3-wire, 2.5m (8.2ft) long - Has straight (F) C15 receptacle with a 'U' shaped channel above the ground pin to prevent use of a lower rated power cord (For 230VAC in India)		A	-N/A-	COMPLY_2106
			8121-1484	Power cord - 3-wire, 2.5m (8.2ft) long - Has straight (F) C15 receptacle with a 'U' shaped channel above the ground pin to prevent use of a lower rated power cord (For 220VAC in China)		A	-N/A-	COMPLY_5012
				Power cord - 3-wire, 2.5m (8.2ft)				

		8121-1485	long - Has straight (F) C15 receptacle with a "U" shaped channel above the ground pin to prevent use of a lower rated power cord (For 220VAC in Philippines and Thailand)		A	-N/A-	COMPLY_5012
		8121-1486	Power cord - 3-wire, 2.5m (8.2ft) long - Has straight (F) C15 receptacle with a "U" shaped channel above the ground pin to prevent use of a lower rated power cord (For 230VAC in Denmark)		A	-N/A-	COMPLY_2106
Power Supply							
		J9829-61001	5400R z12 1100W POE+ AC power supply - Installs in the switch chassis as primary or redundant supply for load sharing or POE power (up to 900W) - Requires 100-127VAC or 200-240VAC at 50-60Hz - Recommended to use the same model power supplies in a system		A	-N/A-	COMPLY_2106
Product							
		J9829A	5400R z12 1100W POE+ AC power supply - Installs in the switch chassis as primary or redundant supply for load sharing or POE power (up to 900W) - Requires 100-127VAC or 200-240VAC at 50-60Hz - Recommended to use the same model power supplies in a system		-N/A-	-N/A-	COMPLY_2106
		J9829AR	Refurbished 5400R z12 1100W POE+ AC power supply - Installs in the switch chassis as primary or redundant supply for load sharing or POE power (up to 900W) - Requires 100-127VAC or 200-240VAC at 50-60Hz - Recommended to use the same model power supplies		-N/A-	-N/A-	COMPLY_1405

[Feedback to HPE.PartSurfer](#)