

# **Honeywell Sensing and Control**

#### Search



#### 111-103EAJ-H01

( Home: Products: Sensors » Temperature Sensors » Discrete Thermistors » 111)

## narrow your search

#### **Products**

- Controls Monitoring and Lighting (352)
- ? Machine Safety (1727)
- ? Sensors (5910)
- Switches (9775)
- ? Wireless (39)

#### Technology

- ? Control and Instrumentation (1054)
- Electromechanical(9301)
- Magnetic (541)
- Microstructure (1495)
- ? More...
- Optical/Infrared (1042)

# new products

### **New Wireless Products**

Go farther. Work smarter. Explore new possibilities. Just by cutting the cord and making the switch.



Wireless Web Site WGI A and WPMM XYR6000™

white papers

find out more

Wireless Switches Offer Unlimited Benefit

Basic Switches Are Not Created Equal

Applying Precision Switches

Sensors for Medical Devices

New Ways to Measure Torque

Choosing Safety Switches

Specifying Hour Meters

### Need help?

Click here to contact us



Actual product appearance

Sales & Service 2

111 Series, small glass bead with axial leads, 10,000 Ohm

resistance, ±20.0% tolerance, 25/85 BETA = 3518

Distributor Inventory 2

**Application Notes** Overview **Specs Documentation** 

**Product Line Guide** 

**Application Note Library** 

## Description

may vary.

111 Series Thermistors are hermetically sealed in glass. They feature relatively uniform size, offer fast time response and are highly sensitive to electric power. They are often suited for use in low heat capacity applications and their micro size allows them to be used in extremely small assemblies such as catheters and hypodermic needles.

# **Features**

#### Features

- Hermetically sealed
- Rapid response times
- Excellent long-term stability
- Micro size
- ? Weldable platinum iridium leads

# **Potential Applications**

#### **Potential Applications**

- Gas analysis
- Gas flow measurement
- Thermal conductivity analysis
- Medical

# **Product Specifications**

Global
10,000 Ohm
±20.0%
25 °C [77 °F]
3518
-60 °C to 300 °C [76 °F to 572 °F]
0,36 mm [0.014 in]
Platinum iridium
9,6 mm [0.375 in]
0.5 s
0,1 m/W°C
111
duct Range Guide
umentation Page

#### contacts

Customer Service

**Technical Support** 

Global Sales & Service

View Site Demo

Site Comments?

#### meet dr. larry

VIDEO- Dr. Larry Goldstein explains our newest and best technologies.



Meet Dr. Larry

# my links

Login to iCOM Login to Rep/AD Portal Login to Digital University

#### **News Center**

HONEYWELL EXTENDS ITs TRUSTABILITY PRESSURE SENSOR PRODUCT LINE WITH A SINGLE SIDE LIQUID MEDIA **OPTION** 

HONEYWELL ADDS NEW 100° AND 180° ARC CONFIGURATIONS TO ITS SMART

POSITION SENSOR PORTFOLIO

HONEYWELL INTRODUCES ITS HAWK™ RESOLVERS 1-INCH SERIES, FULLY HOUSED CONFIGURATION

HONEYWELL INTRODUCES MICROPOWER OMNIPOLAR DIGITAL HALLEFFECT SENSOR ICS WITH LOW SUPPLY VOLTAGE AND ULTRA LOW TYPICAL CURRENT



**MICRO SWITCH Anniversary site**