



Home> Products > Discrete Thermistors > 140 > Product Page

Order Product and Get Support

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback

140-501FAG-A01



Actual product appearance may vary.

2,54 mm [0.1 in] Disc thermistor with leads

Features

- Cost effective
- PC board mountable
- Rugged design
- Versatile
- Solderable leads
- Available on tape and reel

Potential Applications

- Low -cost applications with a maximum temperature of 150 °C [302 °F]
- PCB temperature sensing
- Automotive

Description

140 Series, 142 Series and 143 Series Thermistors are available in a broad range of custom resistance values and R/T curves. Leads are uninsulated. Diameters range from 2,54 mm [0.1 in] to 10,16 mm [0.4 in]. They are available on tape and reel.

Supporting Documentation

None Available

Product Specifications	
Availability	Global
Nominal Resistance at 25 °C [77 ° F]	500 Ohm
Tolerance	± 10.0%
Accuracy	25 °C [77 °F]
R- T Curve	10
Operating Temperature Range	- 60 °C to 125 °C [- 76 °F to 257 ° F]
Maximum Diameter	2,54 mm [0.10 in]
Termination Material	Tinned copper
Lead length	38,1 mm [1.50 in]
Time Constant in Air	10.0 s
Dissipation Constant	3,0 m/W°C
Series Name	140

My Links

- Login to iCOM
- Login as Rep/AD
- Login as Guest
- Login to Digital University

Keyword Search

Search for product and support information.

All Sensing and Control

Product Search

Part number search:

Use (*) to expand search

Specification Search