loney				Honeywell.co	m → Automation & Control Sol	
HOME	ABOUT US	PRODUCTS & INFO	RMATION	NEWS & EVENTS	SALES & SUPPORT	LO
oneywell	Sensing an	d Control				
arch	Э	<b>140-501FAG-RB1</b> (Home : Products)	Discrete Ther	mistors		
narrow	your search					
<ul> <li>Products</li> <li>Controls Mon and Lighting (</li> <li>Machine Safe</li> <li>Sensors (701)</li> <li>Switches (967)</li> </ul>	(354) ety (1726) 6)			2,54 mm [0.1 in] disc ±10.0% tolerance, 25/	thermistor with leads, 500 Ohm 85 BETA = 3468	
<ul> <li>Control and Instrumentatii</li> <li>Electromecha (9237)</li> <li>Microstructuri</li> <li>Optical/Infrard</li> <li>Thick Film (17)</li> <li>More</li> </ul>	anical e (2298) ed (1077)	Actual product appearance may vary.	ce			
• More			Sales	& Service 🥹	Distributor Inventory 🥹	
leed Help?	-	Overview Specs	Documentation	Application Notes		
Click here to c	contact us 🌍	Product Specifications				
		Availability	Global			
		Resistance	500 Ohm			
		Tolerance	±10.0%			
		Accuracy	25 °C [77 °F]			
		Beta	3468			
		Operating Temperature	-60 °C to 125 °C [-	76 °F to 257 °F]		
		Diameter	2,54 mm [0.10 in]			
		Termination Material	Tinned copper			
		Lead Length	38,1 mm [1.50 in]			
		Time Constant in Air	10.0 s			
			0.0 0.0/00			
		Dissipation Constant	3,0 m/W°C			

Terms & Conditions | Privacy Statement | Site Map