

# **Honeywell Sensing and Control**

Home> Products > Discrete Thermistors > 192 > Product Page

## Order Product and **Get Support**

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback

### 192-303KET-A01



Actual product appearance may vary.

Uni-Curve with bare leads and epoxy

## **Features**

Resistance temperature curve interchangeability Accuracy High stability Long life Cost effective Small size Epoxy coated

Temperature measurement, indication and control Compensation of ambient temperature effects on copper coils, transistors, integrated circuits and other semiconductor devices Medical

# **Potential Applications**

# Part number search: Use (\*) to expand search **Specification Search**

My Links

Login to iCOM Login as Rep/AD

**Login as Guest** 

Login to Digital University

Search for product and

All Sensing and Contro

support information.

Keyword Search

Product Search

## **Description**

192 Series Thermistors are high quality, low-cost, resistance temperature-matched interchangeable units. They offer additional cost savings by eliminating the need for individual resistance temperature calibration, as well as standardization of circuit components and simplification of design and replacement problems.

## **Supporting Documentation**

None Available

| Product Specifications               |                                       |
|--------------------------------------|---------------------------------------|
| Availability                         | Global                                |
| Nominal Resistance at 25 °C [77 ° F] | 30,000 Ohm                            |
| Tolerance                            | ± 1,0 °C [1.8 °F]                     |
| Accuracy                             | 0 °C to 70 °C [32 °F to 158 °F]       |
| R-T Curve                            | 18                                    |
| Operating Temperature Range          | -60 °C to 150 °C [ -76 °F to 302 ° F] |
| Maximum Diameter                     | 2,413 mm [0.095 in]                   |
| Termination Material                 | 32 Gauge tinned copper, alloy 180     |
| Lead length                          | 38,1 mm [1.50 in]                     |
| Time Constant in Air                 | 15.0 s                                |
| Dissipation Constant                 | 0,75 m/W°C                            |
| Series Name                          | 192                                   |