

Honeywell Sensing and Control

Home> Products > Discrete Thermistors > 192 > Product Page

Order Product and **Get Support**

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback

192-503QET-A01



Actual product appearance may vary.

Uni-Curve with bare leads and epoxy

Features

Resistance temperature curve interchangeability Accuracy High stability Long life Cost effective Small size Epoxy coated

Potential Applications

and control Compensation of ambient temperature effects on copper coils, transistors, integrated circuits and other semiconductor devices Medical

Temperature measurement, indication

Product Search Part number search:

My Links

Login to iCOM Login as Rep/AD

Login as Guest

Login to Digital University

Search for product and

All Sensing and Contro

support information.

Keyword Search

Specification Search

Use (*) to expand search

Description

192 Series Thermistors are high quality, low-cost, resistance temperature-matched interchangeable units. They offer additional cost savings by eliminating the need for individual resistance temperature calibration, as well as standardization of circuit components and simplification of design and replacement problems.

Supporting Documentation

None Available

| Product Specifications | |
|--------------------------------------|---------------------------------------|
| Availability | Global |
| Nominal Resistance at 25 °C [77 ° F] | 50,000 Ohm |
| Tolerance | ± 0,2 °C [0.36 °F] |
| Accuracy | 0 °C to 70 °C [32 °F to 158 °F] |
| R-T Curve | 1 |
| Operating Temperature Range | -60 °C to 150 °C [-76 °F to 302 ° F] |
| Maximum Diameter | 2,413 mm [0.095 in] |
| Termination Material | 32 Gauge tinned copper, alloy 180 |
| Lead length | 38,1 mm [1.50 in] |
| Time Constant in Air | 15.0 s |
| Dissipation Constant | 0,75 m/W°C |
| Series Name | 192 |