



Home> Products > Discrete Thermistors > 197 > Product Page

Order Product and Get Support

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback

197-103LAG-A01



Actual product appearance may vary.

Chip thermistor with bare leads and epoxy

Features

- Accuracy
- High stability
- Long life
- Cost effective
- Small size
- Epoxy coated

Potential Applications

- Communications
- Medical
- Fire detection
- Computers
- Instrumentation test equipment

Description

197 Series Thermistors are available in a broad range of custom resistance values and R/T curves. They are also available with insulated or noninsulated leads.

Supporting Documentation

None Available

Product Specifications	
Availability	Global
Nominal Resistance at 25 °C [77 ° F]	10,000 Ohm
Tolerance	± 10.0%
Accuracy	25 °C [77 °F]
R - T Curve	16
Operating Temperature Range	- 60 °C to 125 °C [- 76 °F to 257 ° F]
Maximum Diameter	2,413 mm [0.095 in]
Termination Material	32 Gauge tinned copper, alloy 180
Lead length	38,1 mm [1.50 in]
Time Constant in Air	15.0 s
Dissipation Constant	0,75 m/W°C
Series Name	197

My Links

- Login to iCOM
- Login as Rep/AD
- Login as Guest
- Login to Digital University

Keyword Search

Search for product and support information.

All Sensing and Control

Product Search

Part number search:

Use (*) to expand search

Specification Search