

SPECIFICATION DATA	
PARAMETER	VALUE
OUTPUT VOLTAGE	190V Pk-Pk MIN
COIL RESISTANCE	1200 OHMS MAX
INDUCTANCE	450 mH MAX @ 1KHz
DIELECTRIC STRENGTH	500V RMS AT 60HZ FOR 1 MIN MAX NOT TO EXCEED 100V PER SECOND
LEAKAGE RESISTANCE	100 MEGOHMS MINIMUM
TEMPERATURE LIMITS	-67°F TO +250°F
CUSTOMER DWG NO	

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVAL
E	REVISED & REDRAWN CN14075	8/2/94	PEP
F	WAS -100°F TO +225°F CN14491	7/24/95	ØØØ

DWG. NO.	3030AN25	SH	REV
		1	F

- NOTES:
- TESTED AT 1000 I.P.S. WITH A 20 PITCH GEAR AT .005 INCH CLEARANCE AND A LOAD OF 100K OHMS.
 - POLARITY: WHEN FERROUS METAL IS INTRODUCED INTO MAGNETIC FIELD, PIN "B" WILL BE POSITIVE WITH RESPECT TO PIN "A".
 - CONNECTOR MATES WITH MS 3106A-10SL-4S

