Click here to not show this message again

PRODUCTS ▼

H ABOUTUS ▼

3100U 00031435

Products > Sensors > Humidity, Thermal & Flexible Heater Products > Thermostats/Thermal Switches > Precision > Preconfigured Redi-Temp > 3100U Series > **3100U 00031435**

Reset Type

Overview

3100 Series Hermetic Thermostats.

The 3100 Series consists of a single pole, single throw switch activated by a snap-action bimetal disc. Temperature

View More



view all 3100U 00031435 literature













email sales



Technical Specifications

Functional Properties	Open on rise
Operating Temperature	-29 °C to 260 °C [-20 °F to 500 °F]
Voltage	120 Vac
Open Tolerance	2.8 °C [5 °F]
Close Tolerance	2.8 °C [5 °F]

Open 26.7 °C [80 Temperature °F] Close 15.6 °C [60 Temperature °F] Environmental -62 °C to 288 Exposure °C [-80 °F to	Amperage	3 A resistive max.	
Temperature °F] Environmental -62 °C to 288	•	_	
Range 550 °F]	Exposure	°C [-80 °F to	

View documents in: English

Automatic

View More

Documents

TITLE	DOCUMENT TYPE	LANGUAGE	SIZE
Precision and High Reliability Thermostats	Datasheet		4MB
Thermostats Line Guide	Product Line Guide	English	444KB
Thermal Sensors	Product Range Guide	English	2MB

Product Features

- Hermetically sealed
- Tight tolerances
- Tight differentials

Applications

- Computers
- Medical electronics
- Power supplies
- Industrial controls
- Test equipment
- Infotech

NAVIGATION LINKS

HOME PAGE

PRODUCTS

DISTRIBUTOR INVENTORY

INDUSTRIES

SUPPORT

NEWS & EVENTS

ABOUT US

DISTRIBUTOR LINKS

ECOM LOGIN

LEARN CENTER

REQUEST ACCESS TO ECOM

SALES/AD PORTAL LOGIN

SALES/AD PORTAL ACCESS REQUEST

SAMPLE REQUEST

SUPPLIER MICROSITE

LANGUAGE

English

SOCIAL MEDIA

90

SITE INFORMATION
PRIVACY STATEMENT

SITEMAP

TERMS & CONDITIONS

COPYRIGHT © 2018 HONEYWELL INTERNATIONAL INC.