PRODUCTS ▼

■ SUPPORT **▼**

H ABOUTUS ▼

3156U 00960002

Products > Sensors > Humidity, Thermal & Flexible Heater Products > Thermostats/Thermal Switches > Precision > Hermetically Sealed > 3156 Series > **3156U 00960002**

Overview

3156 Series Low Silhouette Hermetic Thermostats.

The 3156 Series consists of a single pole, single throw switch activated by a snap-action bimetal disc. Temperature

View More



Technical Specifications

Functional Properties	Close on rise
Operating Temperature	-29 °C to 177 °C [-20 °F to 350 °F]
Voltage	120 Vac/50 Vdc
Open Tolerance	2.8 °C [5 °F]
Close Tolerance	2.8 °C [5 °F]

Reset Type	Automatic	
Amperage	100 mA/500 mA	
Open	100.0 °C [212	
Temperature	°F]	
Close	70.0 °C [158	
Temperature	°F]	
Environmental	-54 °C to 260	
Exposure	°C [-65 °F to	
Range	500 °F]	

View documents in: English





view all 3156U

00960002 literature

view distributor inventory

? sample request

email support

? get support

8 email sales

0

Documents

View More

TITLE	DOCUMENT TYPE	LANGUAGE	SIZE
Precision and High Reliability Thermostats	Datasheet		4MB
Thermostats Line Guide	Product Line Guide	English	444KB
Soldering Wire Leads on Precision Hermetic Thermostats	Installation Instructions	English	57KB
Thermal Sensors	Product Range Guide	English	2MB

Product Features

- Hermetically sealed
- Tight tolerances
- Tight differential
- Low profile

Applications

- Industrial
- Food service
- Telecom

- Medical
- Infotech

NAVIGATION LINKS

HOME PAGE

PRODUCTS

DISTRIBUTOR INVENTORY

INDUSTRIES

SUPPORT

NEWS & EVENTS

ABOUT US

DISTRIBUTOR LINKS

ECOM LOGIN

LEARN CENTER

REQUEST ACCESS TO ECOM

SALES/AD PORTAL LOGIN

SALES/AD PORTAL ACCESS REQUEST

SAMPLE REQUEST

SUPPLIER MICROSITE

LANGUAGE

English 🔻

SOCIAL MEDIA





SITE INFORMATION PRIVACY STATEMENT

SITEMAP

TERMS & CONDITIONS

COPYRIGHT © 2018 HONEYWELL INTERNATIONAL INC.