

Honeywell Sensing and ControlSearch **narrow your search****Products**

- Controls Monitoring and Lighting (352)
- Machine Safety (1727)
- Sensors (5910)
- Switches (9781)
- Wireless (45)

Technology

- Capacitive (26)
- Control and Instrumentation (1054)
- Electromechanical (9307)
- Microstructure (1495)
- Thick Film (1409)
- More...

new products**New Wireless Products**

Go farther. Work smarter. Explore new possibilities. Just by cutting the cord and making the switch.



Wireless Web Site
WGLA and WPMW
XYR6000™

[find out more](#) **white papers**

- ▶ Wireless Switches Offer Unlimited Benefit
- ▶ Basic Switches Are Not Created Equal
- ▶ Applying Precision Switches
- ▶ Sensors for Medical Devices
- ▶ New Ways to Measure Torque
- ▶ Choosing Safety Switches
- ▶ Specifying Hour Meters

Need help?[Click here to contact us](#) **3455RC 01000227**

(Home : Products : Sensors » Thermostats » 3455RC)



3455RC Redi-Temp Series Ceramic Automatic Reset Thermostats

Actual product appearance may vary.

[Sales & Service](#) [Distributor Inventory](#) [Overview](#)[Specs](#)[Documentation](#)[Application Notes](#)

Features

Features

- Cost effective
- Rivet sleeve construction
- High profile
- High temperature
- High current

Potential Applications

Potential Applications

- Copy machines
- Power supplies
- Telecommunications
- Office copy machines
- Ovens

Product Specifications

Functional Properties	Open on rise
Reset Type	Automatic
Amperage	15 A/10 A resistive max.
Voltage	120 Vac/240 Vac
Operating Temperature	0 °C to 260 °C [32 °F to 500 °F]
Environmental Exposure Range	-20 °C to 287 °C [0 °F to 550 °F]
Open Temperature	57.2 °C [135 °F]
Close Temperature	40.6 °C [105 °F]
Open Tolerance	2.8 °C [5 °F]
Close Tolerance	4.4 °C [8 °F]
Dielectric Strength	MIL-STD-202, Method 301; 2000 Vac 60 Hz - Terminal to Case
Insulation Resistance	MIL-STD-202, Method 302; 500 MOhm
Contact Resistance	MIL-STD-202, Method 307; 0.050 Ohm max.
Housing Material	Ceramic
Contact Material	Silver/ nickel alloy
Agency Approvals and Standards	UL, CSA, VDE
Mounting	B203S moveable bracket
Series Name	3455RC



[Product Range Guide](#)



[Documentation Page](#)



[Product Line Guide](#)



[Application Note Library](#)

contacts

[Terms & Conditions](#) | [Privacy Statement](#) | [Site Map](#)

[Customer Service](#)

[Technical Support](#)

[Global Sales & Service](#)

[View Site Demo](#)

[Site Comments?](#)

[meet dr. larry](#)

VIDEO - Dr.
Larry Goldstein
explains our
newest and best
technologies.



Meet Dr. Larry

my links

[Login to iCOM](#)

[Login to Rep/AD Portal](#)

[Login to Digital University](#)

News Center

HONEYWELL
INTRODUCES
MICROPOWER