

Honeywell Sensing and Control

Search



narrow your search

Products

- Controls Monitoring and Lighting (352)
- Machine Safety (1727)
- Sensors (5910)
- Switches (9781)
- Wireless (45)

Technology

- Capacitive (26)
- Control and Instrumentation (1054)
- Electromechanical (9307)
- Microstructure (1495)
- Thick Film (1409)
- More...

new products

New Wireless Products

Go farther. Work smarter. Explore new possibilities. Just by cutting the cord and making the switch.



Wireless Web Site
WGLA and WPMM
XYR6000™

[find out more](#)

white papers

Wireless Switches Offer
Unlimited Benefit

Basic Switches Are Not Created
Equal

Applying Precision Switches

Sensors for Medical Devices

New Ways to Measure Torque

Choosing Safety Switches

Specifying Hour Meters

Need help?

[Click here to contact us](#)

Description

Shipped from stock, the 3455RC Series thermostats are often suitable for applications such as copy machines, power supplies, telecommunications and ovens. UL, CSA and European approval agencies listings available.

Features

Features

- Cost effective
- Rivet sleeve construction
- High profile
- High temperature
- High current

3455RC 01000230

(Home : Products : Sensors » Thermostats » 3455RC)



3455RC Redi-Temp Series Ceramic Automatic Reset Thermostat

*Actual product appearance
may vary.*

[Sales & Service](#)
[Distributors](#)
[Overview](#)
[Specs](#)
[Documentation](#)
[Application Notes](#)

Potential Applications

Potential Applications

- Copy machines
- Power supplies
- Telecommunications
- Office copy machines
- Ovens

Product Specifications

Functional Properties	Open on rise
Reset Type	Automatic
Amperage	15 A/10 A resistive max.
Voltage	120 Vac/240 Vac
Operating Temperature	0 °C to 260 °C [32 °F to 500 °F]
Environmental Exposure Range	-20 °C to 287 °C [0 °F to 550 °F]
Open Temperature	73.9 °C [165 °F]
Close Temperature	57.2 °C [135 °F]
Open Tolerance	2.8 °C [5 °F]
Close Tolerance	4.4 °C [8 °F]
Dielectric Strength	MIL-STD-202, Method 301; 2000 Vac 60 Hz - Terminal to Case
Insulation Resistance	MIL-STD-202, Method 302; 500 MOhm
Contact Resistance	MIL-STD-202, Method 307; 0.050 Ohm max.
Housing Material	Ceramic
Contact Material	Silver/nickel alloy
Agency Approvals and Standards	UL, CSA, VDE
Mounting	B203S moveable bracket
Series Name	3455RC

[Product Range Guide](#)[Documentation Page](#)[Product Line Guide](#)[Application Note Library](#)

[contacts](#)

Customer Service
Technical Support
Global Sales & Service
View Site Demo
Site Comments?

[meet dr. larry](#)

VIDEO - Dr. Larry Goldstein explains our newest and best technologies.



Meet Dr. Larry

[my links](#)

Login to iCOM
Login to Rep/AD Portal
Login to Digital University

[News Center](#)

HONEYWELL INTRODUCES
MICROPOWER OMNIPOLAR
DIGITAL HALL-EFFECT
SENSOR ICS WITH LOW
SUPPLY VOLTAGE AND ULTRA
LOW TYPICAL CURRENT

HONEYWELL EXTENDS ITS
TRUSTABILITY® PRESSURE
SENSOR PRODUCT LINE WITH
A SINGLE SIDE LIQUID MEDIA
OPTION

HONEYWELL ADDS NEW 100°
AND 180° ARC
CONFIGURATIONS TO ITS
SMART POSITION SENSOR
PORTFOLIO

HONEYWELL INTRODUCES ITS
HAWK™ RESOLVERS 1-INCH
SERIES, FULLY HOUSED
CONFIGURATION

MICRO SWITCH
[Anniversary site](#)