ng and Control USTRES SERVED	PRODUCTS & INFO	Start	Here VS & EVENTS Dis Ing Na Modi Prod	Choose Language isite and product database Se arcl SALES & SUPPORT itributor Inventory put part number for stock a rrow Your Search fy Your Search lucts	h
USTRES SERVED	rostats : 3500)	Start	Here VS & EVENTS Dis Ing Na Modi Prod	siste and product database Search SALES & SUPPORT stributor Inventory put part number for stock a rrow Your Search	h Loo Loo availability
USTRES SERVED	rostats : 3500)	Start	Here VS & EVENTS Dis Ing Na Modi Prod	Search SALES & SUPPORT stributor Inventory put part number for stock . rrow Your Search	LOC availability
y 10-Oct-2006 : Sensors : Therm	rostats : 3500)		NS & EVENTS	SALES & SUFFORT stributor Inventory put part number for stock a rrow Your Sea fy Your Search	evailability
y 10-Oct-2006 : Sensors : Therm	rostats : 3500)	RVATION NE	Dis Ing Na Modi Prod	stributor Inventory put part number for stock a rrow Your Sea fy Your Search	a vailability
ies Military Thermostats			Ing Na Modi Prod	put part number for stock a	availability
ies Military Thermostats			Ing Na Modi Prod	put part number for stock a	availability
ies Military Thermostats			Ing Na Modi Prod	put part number for stock a	availability
	Distributor		Na Modi Prod	rrow Your Sea	
	Distributor		Modi Prod	fy Your Search	irch
	Distributor		Modi Prod	fy Your Search	rch
les & Service	Distributor		Prod		
les & Service	Distributor			ucts	
les & Service	Distributor			4013	
les & Service	Distributor		Selec	et Ontion	
les & Service	Distributor			ct Option	
les & Service	Distributor		Tech	nology	
les & Service	Distributor		Selec	ct Option	\$
		Inventory		stries Served	
			Selec	ct Option	
Documentation Appl	lication Notes				
	5				
Automatic					
5.0 A resistive					
28 Vac/Vdc					
]				
	Vac 60 Hz - Termin	al to Case			
, ,					
ML-STD-202, Method 213; 400 G	i				
ML-STD-202, Method 204; 20 G					
ML-STD-202, Method 212; 20 G					
, ,					
, , ,					
		al seal at terminal junction			
	ot MI-HRF-24236				
B208 fixed bracket					
	Open on rise Automatic 5.0 A resistive 28 Vac/Vdc -46 °C to 204 °C [-50 °F to 400 °F, -65 °C to 260 °C [-85 °F to 500 °F, 130.0 °C [266 °F] 117.8 °C [244 °F] 2.8 °C [5 °F] 2.8 °C [5 °F] 2.8 °C [5 °F] ML-STD-202, Method 301; 1250 ° ML-STD-202, Method 307; 0.050 ML-STD-202, Method 307; 0.050 ML-STD-202, Method 307; 0.050 ML-STD-202, Method 112; Cond. ML-STD-202, Method 112; Cond. ML-STD-202, Method 213; 400 G ML-STD-202, Method 213; 400 G ML-STD-202, Method 106 ML-STD-202, Method 107; Cond. ML-STD-202, Method 107; Cond. ML-STD-202, Method 107; Cond. ML-STD-202, Method 107; Cond. ML-STD-202, Method 101; Cond. Steel housing hermetically sealec Gold-plated Consil alloy MG/silver	Automatic 5.0 A resistive 28 Vac/Vdc -46 °C to 204 °C [-50 °F to 400 °F] -65 °C to 260 °C [-85 °F to 500 °F] 130.0 °C [266 °F] 117.8 °C [244 °F] 2.8 °C [5 °F] 2.8 °C [5 °F] ML-STD-202, Method 301; 1250 Vac 60 Hz - Termin ML-STD-202, Method 302; 500 MOhm ML-STD-202, Method 307; 0.050 Ohm max. ML-STD-202, Method 307; 0.050 Ohm max. ML-STD-202, Method 112; Cond. C ML-STD-202, Method 112; Cond. C ML-STD-202, Method 213; 400 G ML-STD-202, Method 213; 400 G ML-STD-202, Method 107; Cond. B ML-STD-202, Method 107; Cond. B ML-STD-202, Method 101; Cond. B Steel housing hermetically sealed with glass-to-meta Gold-plated Consil alloy MG/silver Meets or exceeds requirements of MI-FFF-24236	Open on rise Automatic 5.0 A resistive 28 Vac/Vdc -46 °C to 204 °C [-50 °F to 400 °F] -65 °C to 260 °C [-85 °F to 500 °F] 130.0 °C [266 °F] 117.8 °C [244 °F] 2.8 °C [5 °F] 2.8 °C [5 °F] ML-STD-202, Method 301; 1250 Vac 60 Hz - Terminal to Case ML-STD-202, Method 302; 500 MDhm ML-STD-202, Method 307; 0.050 Chmmax. ML-STD-202, Method 307; 0.050 Chmmax. ML-STD-202, Method 112; Cond. C ML-STD-202, Method 1213; 400 G ML-STD-202, Method 106 ML-STD-202, Method 107; Cond. B ML-STD-202, Method 107; Cond. B ML-STD-202, Method 101; Cond. B Steel housing hermetically sealed with glass-to-metal seal at terminal junction Gold-plated Consil alloy MG/silver Meets or exceeds requirements of MI-FRF-24236	Open on riseAutomatic5.0 A resistive28 Vac/Vdc-46 °C to 204 °C [-50 °F to 400 °F]-65 °C to 260 °C [-85 °F to 500 °F]130.0 °C [266 °F]117.8 °C [244 °F]2.8 °C [5 °F]2.8 °C [5 °F]ML-STD-202, Method 301; 1250 Vac 60 Hz - Terminal to CaseML-STD-202, Method 307; 0.050 Chmmax.ML-STD-202, Method 307; 0.050 Chmmax.ML-STD-202, Method 112; Cond. CML-STD-202, Method 112; Cond. CML-STD-202, Method 213; 400 GML-STD-202, Method 107; Cond. BML-STD-202, Method 107; Cond. BML-STD-202, Method 101; Cond. BSteel housing hermetically sealed with glass-to-metal seal at terminal junctionGold-plated Consil alloy M2/silverMeets or exceeds requirements of ML-FRF-24236	Open on rise Automatic 5.0 A resistive 28 Vac/Vdc -46 °C to 204 °C [-50 °F to 400 °F] -65 °C to 260 °C [-85 °F to 500 °F] 130.0 °C [266 °F] 117.8 °C [244 °F] 2.8 °C [5 °F] ML-STD-202, Method 301; 1250 Vac 60 Hz - Terminal to Case ML-STD-202, Method 302; 500 MDhm ML-STD-202, Method 307; 0.050 Chmmax. ML-STD-202, Method 112; Cond. C ML-STD-202, Method 213; 400 G ML-STD-202, Method 213; 400 G ML-STD-202, Method 213; 400 G ML-STD-202, Method 106 ML-STD-202, Method 106 ML-STD-202, Method 107; Cond. B ML-STD-202, Method 107; Cond. B ML-STD-202, Method 101; Cond. B Steel housing hermetically sealed with glass-to-metal seal at terminal junction Gold-plated Consil alloy MG/silver Mets or exceeds requirements of MI-FRF-24236

4/1/2014

Application Notes Application Demos	 Website Feedback
N	Application Notes
P	Application Demos
P	CAD Renderings