6655-97100901 Page 1 of 1



→ Honeywell.com → Automation & Control Solutions

ABOUT US

KEY INDUSTRIES SERVED

PRODUCTS & INFORMATION

NEWS & EVENTS

SALES & SUPPORT

Customer Service

Technical Support

View Site Demo

Site Comments?

Global Sales & Service

LOGIN

Honeywell Sensing and Control

Search



6655-97100901

(Home: Products: Sensors » Temperature Sensors » Packaged Temperature Probes » 6655)

narrow your search

Products

- Controls Monitoring and Lighting (286)
- Machine Safety (1727)Sensors (5910)
- Switches (9781) Wireless (45)

Technology

- Electromechanical (9307)
- Magnetic (541)Microstructure (1495)
- Optical/Infrared (1042) Thick Film (1409)

More.



Actual product appearance

may vary.

6655 Series on-surface temperature sensor, NTC, 10,000 Ohm, ± 10.0 % tolerance, 3976 BETA, 16 R-T curve, phenolic, bracket (20,6 mm diameter pipe clip), quick connect terminal [90°, 0.25 in]

Application Notes

Sales & Service Distributor Inventory Distributor

Quick connect terminal (90°, 0.25 in)

6655

meet dr. larry

VIDEO - Dr. Larry Goldstein explains our newest and best technologies.

Meet Dr. Larry



my links

new products

New Wireless Products

Go farther. Work smarter. Explore new possibilities. Just by cutting the cord and making the switch.



Wireless Web Site WGLA and WPMM XYR6000™

find out more

white papers

Wireless Switches Offer Unlimited Benefit

Basic Switches Are Not Created Equal

Applying Precision Switches Sensors for Medical Devices New Ways to Measure Torque Choosing Safety Switches Specifying Hour Meters

Specs Documentation Overview

Product Specifications

Thermistor Type NTC Air/Surface Temperature Sensing Type Resistance 10,000 Ohm Tolerance ±10.0 % BETA (25/85) 3670 (25/85)

R-T Curve 16 Operating Temperature -20 °C to 110 °C [-4 °F to 230 °F]

Housing Material Phenolic Bracket pipe clip (20,6 mm dia.)

Mounting Method/Mechanical Interface

Series Name

Electrical Interface/Connector Type

Time Constant on Metal Surface 1.5 s Dissipation Constant on Metal Surface Availability Global

6.5 mW/°C

Login to iCOM

Login to Rep/AD Portal Login to Digital University

News Center

HONEYWELL ADDS NEW 100° AND 180° ARC CONFIGURATIONS TO ITS SMART POSITION SENSOR PORTFOLIO HONEYWELL INTRODUCES ITS HAWKTM RESOLVERS 1-INCH SERIES, FULLY HOUSED CONFIGURATION HONEYWELL INTRODUCES MICROPOWER OMNIPOLAR DIGITAL HALL-EFFECT SENSOR ICS WITH LOW SUPPLY VOLTAGE AND ULTRA LOW TYPICAL CURRENT

HONEYWELL EXTENDS ITS TRUSTABILITY® PRESSURE SENSOR PRODUCT LINE WITH A SINGLE SIDE LIQUID MEDIA

MICRO SWITCH Anniversary site

Need help?

Click here to contact us

Terms & Conditions | Privacy Statement | Site Map