

Honeywell Sensing and Control

Home> Products > Non-contact Safety Switches > FF > Product Page

FF5-21-DC-10

Get Support

Order Product and

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback



FF Series, Safety Switch and Actuator
red ABS, 2NC/1NO, dc, 10 m pre-wired

Actual product appearance may vary.

Features Non-contact safety switches Switches can be magnetically actuated from almost any angle Compact, rugged design Tested to over 1,000,000 operations, full load 6 mm [0.24 in] operating distance Up to 300 mA at 24 Vdc switching capability IP67 sealing Stainless steel option UL and CE approvals

Potential Applications

Can forming and filling (aluminum, steel, and plastic) Pick and place packaging equipment Pick and place/assembly equipment Semicon equipment Plastic molding equipment Woodworking machinery Textile machinery

Printing machinery

My Links Login to iCOM Login as Rep/AD Login as Guest Login to Digital University Keyword Search Search for product and support information. All Sensing and Contre **Product Search** Part number search:

Use (*) to expand search

Specification Search

Description

Honeywell FF5 switches are magnetically operated, non-contact safety switches designed for use in many machine guarding applications. The FF5 is available in both ABS and 316 grade stainless steel and is capable of switching up to 300 mA at 24 Vdc. The switch and actuator are fully sealed and can often be used in wet or dusty environments. With correct installation, the FF5 safety switches comply with the guidelines given in EN1088.

Supporting Documer	ntation	
Mounting	Installation	Contact
Dimensions	Instructions and Approvals Documentation	Configurations
N Connections		

Connections

Product Specifications		
Product Type	Safety Limit Switch	
Actuator	Non - contact switch	
Lever Style	None	
Switch Type	Max: 2NC safety and 1NO auxiliary	
Cable Length	10 m prewired	
Voltage	24 Vdc/0.3 A inductive/resistive	
Housing Material	Red ABS resin filled	
Housing Type	Rectangular switch and actuator	
Series Name	FF	
Shock	10 g	
Vibration	50 Hz to 100 Hz	
Sealing	IP67	
Approvals	UL, CE	
Operating Temperature Range	- 10 °C to 55 °C [14 °F to 131 °F]	
Availability	Global	
UNSPSC Code	302119	
UNSPSC Commodity	302119 Switches and controls and relays	