


## Inductive sensor

IFC2004-ARKG/UP/6M



## Product characteristics

|                    |                  |
|--------------------|------------------|
| Electrical design  | PNP/NPN          |
| Output function    | normally open    |
| Sensing range [mm] | 4                |
| Housing            | threaded type    |
| Dimensions [mm]    | M12 x 1 / L = 40 |

## Electrical data

|                             |            |
|-----------------------------|------------|
| Operating voltage [V]       | 10...36 DC |
| Protection class            | II         |
| Reverse polarity protection | yes        |

## Outputs

|                                                      |               |
|------------------------------------------------------|---------------|
| Electrical design                                    | PNP/NPN       |
| Output function                                      | normally open |
| Max. voltage drop switching output DC [V]            | 4.6           |
| Minimum load current [mA]                            | 4             |
| Max. leakage current [mA]                            | 0.6           |
| Permanent current rating of switching output DC [mA] | 150           |
| Switching frequency DC [Hz]                          | 1500          |
| Short-circuit protection                             | yes           |
| Type of short-circuit protection                     | pulsed        |
| Overload protection                                  | yes           |

## Detection zone

|                            |          |
|----------------------------|----------|
| Sensing range [mm]         | 4        |
| Real sensing range Sr [mm] | 4 ± 10 % |
| Operating distance [mm]    | 0...3.25 |

## Accuracy / deviations

|                              |                                                                             |
|------------------------------|-----------------------------------------------------------------------------|
| Correction factor            | steel: 1 / stainless steel: 0.7 / brass: 0.4 / aluminium: 0.3 / copper: 0.2 |
| Hysteresis [% of Sr]         | 1...15                                                                      |
| Switch point drift [% of Sr] | -10...10                                                                    |

## Operating conditions

|                          |          |
|--------------------------|----------|
| Ambient temperature [°C] | -25...80 |
|--------------------------|----------|

# IF5908



## Inductive sensor

IFC2004-ARKG/UP/6M

|            |       |
|------------|-------|
| Protection | IP 67 |
|------------|-------|

### Tests / approvals

|              |              |
|--------------|--------------|
| EMC          | EN 60947-5-2 |
| MTTF [years] | 2680         |

### Mechanical data

|                    |                     |
|--------------------|---------------------|
| Weight [g]         | 195                 |
| Housing            | threaded type       |
| Mounting           | non-flush mountable |
| Dimensions [mm]    | M12 x 1 / L = 40    |
| Thread designation | M12 x 1             |
| Materials          | PBT                 |

### Displays / operating elements

|         |                  |                 |
|---------|------------------|-----------------|
| Display | switching status | 1 x LED, yellow |
|---------|------------------|-----------------|

### Accessories

|                |              |
|----------------|--------------|
| Items supplied | lock nuts: 2 |
|----------------|--------------|


### Remarks

|               |        |
|---------------|--------|
| Pack quantity | 1 pcs. |
|---------------|--------|

### Electrical connection

Cable: 6 m, PVC; 2 x 0.34 mm<sup>2</sup>

### Connection



BK = Core colours :  
black