

TUIJA-3 SERIES FOR OSRAM OSLOM LEDs



OSRAM
www.osram.com



- Lens material optical grade PMMA with high UV and temperature resistance (105°C/220°F)
- High optical efficiency, >85%
- No lens holder. Fastening to heat sink with droplets of glue. NOTE: legs go into the PCB by 1.2 mm only, do not go thru a normal MCPCB
- Please check fastening details from this link:
(http://www.ledil.com/datasheets/DataSheet_GLUES.pdf)
- Diameter 50 mm (MR16)
- Mechanical CAD models available upon request
- All 3 lens types have the same outer dimensions.

LENS TYPES

NAME	ORDERING CODE	FWHM Angle
Tuija-3 spot	C11192_Tuija-3-SS-OSL	Coming Soon
Tuija-3 medium	C11193_Tuija-3-M-OSL	Coming Soon
Tuija-3 wide	C11191_Tuija-3-W-OSL	Coming Soon

NAME	ORDERING CODE	FWHM Angle
Tuija-3 spot	C11192_Tuija-3-SS-OSL-SX	Coming Soon
Tuija-3 medium	C11193_Tuija-3-M-OSL-SX	Coming Soon
Tuija-3 wide	C11191_Tuija-3-W-OSL-SX	Coming Soon

MEASUREMENT DATA**COMING SOON**


© Ledil Oy – PRELIMINARY - Subject to change without prior notice

Ledil Oy
Tehdaskatu 13
FIN-24100 SALO, Finland

www.ledil.com
email: ledil@ledil.com
FAX: +358-2-733 8001

2010-12-31

DRAWINGS



© Ledil Oy – PRELIMINARY - Subject to change without prior notice