

CAT. N° 6 468 70



ZERO-U THREE PHASE PDU LCS³ - 18XC13 + 6XC19 - IEC 60320 STANDARD

| | |
|---------------------------|----------|
| Pack (number of units) | 1 |
| Volume (dm ³) | 22,344 |
| Weight (g) | 4 400,00 |

Product characteristics

PDU Basic

IEC 60320 standard

- 18 C13 outlets + 6 C19 outlets with cord locking system
- 3 m power supply cord with IEC60309 16 A 3P+N+E plug

General characteristics

Legrand cabling system LCS³ energy Distribution - three phase Zero-U Power Distribution Units

- To provide ~ electric power for IT equipment in 19" enclosures
- Three phase Zero-U PDUs for vertical mounting in the cabinet
- 400 V - 50/60 Hz power supply
- Each circuit is protected by 16 A single pole MCB in a support with projecting edges to avoid accidental breakdown. 1 circuit per phase, each with 6 IEC 60320 C13 outlets and 2 IEC 60320 C19 outlets
- 330° rotating cable input for a perfect orientation of the cable and no interference in the cabinet
- C13 and C19 standard outlets are equipped with cord locking system to avoid any accidental disconnection. Universal solution compatible with all the cords (C14 plugs for C13 and C20 plugs for C19)
- Delivered with 2 sets of metallic mounting brackets: button brackets (for quick fixing and variable pitch) and standard brackets (for screw fixing)
- Black modules (outlets and functions)
- Aluminium profile

Documentation



Catalogue pages & additional information

- [Description page \(p.770\)](#)
- [Technical page \(p.780\)](#)
- [Technical page \(p.781\)](#)



Installation & technical data

- [S000093176EN-12](#)



Installation instructions & related documents

- [LE09270AA-03](#)

CAT. N° 6 468 70

Spare parts

| CAT. NO. | DESCRIPTION | UNIT PRICE | MINIMUM ORDER QUANTITY |
|----------|---------------------------------------------------------|------------|------------------------|
| 980451 | SET OF THREE STRAIGHT FIXING BRACKETS FOR VERTICAL PDUS | | 1 |
| 980452 | TRANSPARENT COVER FOR MCB SUPPORT | | 1 |

Spare Parts Guarantee

Does not affect the guarantee for the finished product.

Spare parts guaranteed against defects if exchanged within 2 weeks.