
MAXIMUM POWER, 200W DC POWER DISTRIBUTION WITH 5V OUTPUTS

PD-DC-200-5V |



FEATURES & BENEFITS

Optimize any installation with the industry-leading power capacity of the fixed voltage, DC Power Distribution line. These solutions not only remove messy, space-consuming, unreliable wall warts and other power clutter from the design, but also provide maximum power to support a multitude of 5V devices. The 200W unit provides high current capacity to an extensive number of 5V outputs, maximizing the same voltage in the single unit. The multi-mount design can be installed in an available 1RU space or at the back or side of the rack for zero-U mounting, providing ultimate installation flexibility. Promoting enhanced design of system power demands, while still providing a seamless install experience, the 200W DC Power Distribution line is innovatively engineered for multiple applications spanning markets from North America to Europe.



- Industry-leading number of outputs with power distributed to as many as 24 devices
 - Maximum current capacity, up to 200W of power
 - 5V, 40A Max (200W)
 - Reliable multi-level protection on both AC input and DC outputs to ensure maximum uptime
 - MOV surge and overload protection on the AC input
 - Individual redundancy built in with auto-resetting PTC overload protection on each individual output
 - Greater mounting flexibility with multi-mount design that fits in 1 rackspace or can mount at the back or side of the rack simply by rotating mounting brackets
 - Color-coded screw terminal connectors with industry standard 5V and polarity labeling for easy identification
 - 120V-230V input supports both North American and European installations
 - LED indicator lights alerting maximum capacity on each voltage bank
 - Leads trimmed to suitable length leaves less cable to manage, enhancing aesthetics and increasing airflow
 - Ultra-quiet, thermostatic temperature controlled fan with automatic speed adjustment
 - Hardware kit includes flexible mounting hardware, color-coded screw terminal connectors to connect devices, and a 6ft IEC power cord
-

SPECIFICATIONS

GENERAL INFO

UL Standards Tested: 60950-1

LISTING AGENCIES/THIRD PARTY CERTIFICATIONS

RoHS: Yes

DIMENSIONS

Depth (US): 7.26

Height (US): 1.75

Width (US): 19