
RACKMOUNT POWER, 7 OUTLET, 15A, BASIC SURGE

RLNK-SW715R-NS |



FEATURES & BENEFITS

- Monitors and logs key power variables including temperature
- Only power management system to meet InfoComm standard
- Automatic notification of events outside of defined parameters
- Respond and control using mobile apps
- Automatic actions can improve system reliability
- Automatic notification to specific people for specific issues
- Easy setup does not require programming

Download the latest device firmware [here](#).

Videos

- System Overview
- System – Unit Overview 1
- System – Unit Overview 2
- Software Home Page
- Network Discovery utility
- Data logging
- Mobile Applications
- Basic System Setup
- Auto-ping Function
- Alert Thresholds

SPECIFICATIONS

GENERAL INFO

Cable Type: Corded

Category Performance Application: RackLink™ Power Management

Available Colors: {3262F1D3-1F8E-416F-AB0F-816CD1250A67}

Finish: Black Powder Coat

UL Standards Tested: 60950-1

Termination: 5-15P

Surge Protected: Basic
Wiring Method: Basic

ASSEMBLY/INSTALLATION INFORMATION

Mounting Points: 2

LISTING AGENCIES/THIRD PARTY CERTIFICATIONS

Greenguard: Yes
cUL Standard: J27JHgBFd_E
UN SPSC: 1

CONSTRUCTION INFORMATION

Component 4: 15
Finish Plating 5: 9
Installation Location: 60950-1

DIMENSIONS

CFM: Yes
Depth (Metric): 50
Depth (US): 9.625
Height (US): 1.75
Length (Metric): Black Powder Coat
Width (US): 19
Rack Units: 1

CORD INFORMATION

Connector Type End One: Yes
Cord Length US: 9

TECHNICAL INFORMATION

Seismic Load Capacity: Yes
Amps: 15
Bale Length US: Yes
Field Assembly Time: 5-15P
IP Rating: Yes
IR Range On Axis: Yes
Material: Steel
Minimum Depth Requirement (Metric): Steel
Mounting: Horizontal
NEMA Rating: Horizontal
Number Of Circuits: 1
Number Of Receptacles: 1
Outlet Control: 5
Grade Type: 5
Number Of Outlets: 7