



PREMIUM SERIES PDU WITH RACKLINK AND SERIES PROTECTION: RACKMOUNT POWER, 8 OUTLET, 20A, SERIES SURGE W/SEQUENCING

RLNK-SW820R-SP |

FEATURES & BENEFITS

- Monitors and logs key power variables including temperature
- Only power management system to meet InfoComm standard
- Automatic notification of events outside of defined parameters
- Respond and control using mobile apps
- Automatic actions can improve system reliability
- Automatic notification to specific people for specific issues
- Easy setup does not require programming
- Includes patented Series Protection™ functionality

Download the latest device firmware [here](#).

Videos

- [System Overview](#)
- [System – Unit Overview 1](#)
- [System – Unit Overview 2](#)
- [Software Home Page](#)
- [Network Discovery utility](#)
- [Data logging](#)
- [Mobile Applications](#)
- [Basic System Setup](#)
- [Auto-ping Function](#)
- [Alert Thresholds](#)

SPECIFICATIONS

GENERAL INFO

Cable Type: Corded

Category Performance Application: RackLink™ with Series Protection

Available Colors: {3262F1D3-1F8E-416F-AB0F-816CD1250A67}

Finish: Black Powder Coat

UL Standards Tested: 60950-1

Termination: 5-20P
Surge Protected: Series
Wiring Method: Series

ASSEMBLY/INSTALLATION INFORMATION

Mounting Points: 2

LISTING AGENCIES/THIRD PARTY CERTIFICATIONS

RoHS: Yes
Greenguard: Yes
cUL Standard: J27JHgBFd_E
UN SPSC: 1

CONSTRUCTION INFORMATION

Component 4: 20
Finish Plating 5: 9
Installation Location: 60950-1

DIMENSIONS

CFM: Yes
Depth (Metric): 30
Depth (US): 9.67
Height (US): 1.75
Length (Metric): Black Powder Coat
Width (US): 19
Rack Units: 1

CORD INFORMATION

Connector Type End One: Yes
Cord Length US: 9

TECHNICAL INFORMATION

Seismic Load Capacity: Yes
Amps: 20 Amps
Bale Length US: Yes
Field Assembly Time: 5-20P
IP Rating: Yes
IR Range On Axis: Yes
Material: Steel
Minimum Depth Requirement (Metric): Steel
Mounting: Horizontal
NEMA Rating: Horizontal
Number Of Circuits: 1
Number Of Receptacles: 1
Outlet Control: 8
Grade Type: 8
Number Of Outlets: 8