
LEGRAND UPS, LINE INTERACTIVE, 1100VA

UPS-LL-1100RT |



FEATURES & BENEFITS

Protect critical hardware in AV, security, networking and broadcast systems through automatic voltage regulation (AVR) to correct voltage irregularities without switching to battery. Multiply the reach and ability of system integrators and end-users through a single portal, providing visibility and control of power usage and available capacity by adding optional network capability with UPS-LIP-1.



- **Ultra Low Transfer Time:** Quick transfer of power from AC to battery
- **Automatic Voltage Regulation (AVR):** Corrects voltage irregularities without switching to battery
- **Pure Sinewave Output:** Provides the ideal waveform for the most sensitive equipment
- **Wide Input Voltage Range:** Enables stable wide range application usage
- **Input Power Factor 0.9:** Optimized and ideal efficiency at full load
- **Programmable Outlet Bank:** Power management outlets enable programmable control of load segments to extend battery time to mission critical equipment
- **Optional Remote Management Control:** Provides visibility and control of power usage and availability, both on-site or at a remote unmanned facility
- **4-Post Rack Mounting Kit:** Included for simplified rack mounting
- **Tower Mounting Option:** Includes feet for non-rack applications, enabling the UPS to stand up by providing stability

SPECIFICATIONS

GENERAL INFO

Available Internationally: No
Color: Black

LISTING AGENCIES/THIRD PARTY CERTIFICATIONS

RoHS: Yes
FCC Standard: Yes

DIMENSIONS

Depth (Metric): 406.40

Depth (US): 16
Height (Metric): 88.00
Height (US): 3.5
Width (Metric): 438.00
Width (US): 17.2
Rack Units: 2RU

TECHNICAL INFORMATION

AC Voltage Input: 120V
Amps: 12A
Minimum Depth Requirement (Metric): 193
Minimum Depth Requirement (US): 17.6
Mounting: 19" Rackmount
Receptacle Type: 5-15R
Network Monitoring: OPTIONAL VIA UPS-LIP-1 CARD
Outlet Control: BANK CONTROL
Number Of Outlets: 8