
LEGRAND UPS, DOUBLE-CONVERSION ONLINE, 2000VA

UPS-LO-2000RT |



FEATURES & BENEFITS

Protect mission critical hardware in AV, security, networking and broadcast systems through double-conversion online power protection. Multiply the reach and ability of system integrators and end-users through a single portal, providing visibility and control of power usage and available capacity by adding optional network capability with UPS-LIP-1.



- **Zero Transfer Time:** Seamless transfer of power from AC to battery and inverter to bypass
- **True Double-Conversion:** Provides the highest protection from raw input power (surges, spikes, and dips)
- **Pure Sinewave Output:** Provides the ideal waveform for the most sensitive equipment
- **Wide Input Voltage Range:** Enables stable wide range application usage
- **Input Power Factor Correction:** Optimized and ideal efficiency at full load
- **Programmable Outlet Bank:** Ensures efficient and timely powering down of attached non-critical equipment
- **Designed to Work in Tandem with a Generator:** Ensures smooth transition to generators during longer outages
- **Optional Remote Management Control:** Provides visibility and control of power usage and availability, both on-site or at a remote unmanned facility
- **4-Post Rack Mounting Kit:** Included for simplified rack mounting
- **Tower Mounting Option:** Includes feet for non-rack applications, enabling the UPS to stand up by providing stability

SPECIFICATIONS

GENERAL INFO

Available Internationally: No
Color: Black

LISTING AGENCIES/THIRD PARTY CERTIFICATIONS

RoHS: Yes
FCC Standard: Yes

DIMENSIONS

Depth (Metric): 508.00

Depth (US): 20
Height (Metric): 88.90
Height (US): 3.5
Width (Metric): 438.00
Width (US): 17.2
Rack Units: 2RU

TECHNICAL INFORMATION

AC Voltage Input: 120V
Amps: 16A
Minimum Depth Requirement (Metric): 193
Minimum Depth Requirement (US): 17.6
Mounting: 19" Rackmount
Receptacle Type: 5-20R
Network Monitoring: OPTIONAL VIA UPS-LIP-1 CARD
Outlet Control: BANK CONTROL
Number Of Outlets: 8