

LEGRAND UPS, DOUBLE-CONVERSION ONLINE, 3000VA

UPS-LO-3000RT |



FEATURES & BENEFITS

Protect mission critical hardware in AV, security, networking and broadcast systems through double-conversion online power protection. Multiply the reach and ability of system integrators and end-users through a single portal, providing visibility and control of power usage and available capacity by adding optional network capability with UPS-LIP-1.



- Zero Transfer Time: Seamless transfer of power from AC to battery and inverter to bypass
- True Double-Conversion: Provides the highest protection from raw input power (surges, spikes, and dips)
- Pure Sinewave Output: Provides the ideal waveform for the most sensitive equipment
- Wide Input Voltage Range: Enables stable wide range application usage
- Input Power Factor Correction: Optimized and ideal efficiency at full load
- Programmable Outlet Bank: Ensures efficient and timely powering down of attached non-critical equipment
- Designed to Work in Tandem with a Generator: Ensures smooth transition to generators during longer outages
- Optional Remote Management Control: Provides visibility and control of power usage and availability, both on-site or at a remote unmanned facility
- 4-Post Rack Mounting Kit: Included for simplified rack mounting
- Tower Mounting Option: Includes feet for non-rack applications, enabling the UPS to stand up by providing stability

SPECIFICATIONS

GENERAL INFO

Available Internationally: No

Color: Black

LISTING AGENCIES/THIRD PARTY CERTIFICATIONS

RoHS: Yes

FCC Standard: Yes

DIMENSIONS

Depth (Metric): 635.00

Depth (US): 25 Height (Metric): 88.90 Height (US): 3.5 Width (Metric): 438.00

Width (US): 17.2 Rack Units: 2RU

TECHNICAL INFORMATION

AC Voltage Input: 120V

Amps: 24A

Minimum Depth Requirement (Metric): 193 Minimum Depth Requirement (US): 17.6

Mounting: 19" Rackmount

Receptacle Type: 5-20R, L5-30R

Network Monitoring: OPTIONAL VIA UPS-LIP-1 CARD

Outlet Control: BANK CONTROL

Number Of Outlets: 9