



LI-VENUS-OX03F10-9295-075H



Address:

910 Auburn Ct
Fremont, CA 94538
USA



Phone:

+1 (408)263-0988

Fax:

+1 (408)217-1960



Sales:

sales@leopardimaging.com

Support:

support@leopardimaging.com

INTRODUCTION

The LI-VENUS-OX03F10-9295-075H is equipped with OmniVision CMOS high-definition high dynamic range CMOS sensor OX03F10 and Maxim GMSL2 serializer MAX9295A/B. This camera outputs 12-bit / 14-bit / 16-bit / 20-bit RAW data.

SPECIFICATIONS

Sensor	OmniVision high-definition high dynamic range sensor OX03F10
Optical Format	1/2.44"
Resolution	1920 (H) x 1536 (V) (active pixels)
Pixel Size	3.0 x 3.0 μm
Output Format	12-bit / 14-bit / 16-bit / 20-bit RAW
Color / Mono	Color sensor
Maximum Frame Rate	60 fps @ 1920 x 1536
HDR (High Dynamic Range)	Supported
LFM (LED Flicker Mitigation)	Supported
Serializer	Maxim MAX9295A/B
IP Rating	IP67
Power Supply Range	8 ~ 17 VDC
Connector	FAKRA Z TYPE
Power Consumption	87 mA @ 12 VDC (1920 x 1542 @ 38 fps)
Operating Temp	-40°C ~ +85°C
Storage Temp	-40°C ~ +85°C
Weight	~ 39 g
Part#	LI-VENUS-OX03F10-9295-075H

APPLICATIONS


- Automotive
 - ◆ SVS
 - ◆ Rear View Camera
 - ◆ Autonomous Driving

LENS SPECIFICATIONS

Effective Focal Length	4.528 mm $\pm$ 5%
Aperture, F/#	1.8 $\pm$ 5%
Field of View (FOV)	99.3° $\pm$ 4° diagonal
	75.4° $\pm$ 3° horizontal
	59.5° $\pm$ 3° vertical
Distortion	-30.85% $\pm$ 5.0 %
Relative Illumination	93.34%
IR Filter	700 nm IR cut filter
Lens Mount	M16 x P0.5



DIMENSIONS




NOTE:


- ⊗ marked are important sizes.
- Tolerances for others unmarked refer to the Tolerance table.

Unit: mm

SYSTEM BLOCK DIAGRAM



DEFAULT IMAGING DIRECTION




USB3.0 CAMERA KIT

LI-GMSL2-USB



Top View



Bottom View

LI-VENUS-OX03F10-9295-075H can connect to LI-GMSL2-USB as a USB 3.0 camera.

Part#: **LI-USB30-VENUS-OX03F10-9295-075H**

SPECIFICATIONS

- USB 3.0 Super Speed support
- UVC compliant
- Allows customization
- 12 VDC Power Supply for camera
- Weight: ~ 106 g
- Single Coax Cable transmits up to 12 meters PoC (Power over Cable)
- Resolution: 1920 x 1542 @ 38 fps
- Power consumption: 87 mA @ 12 VDC
- Compatible with Windows, Linux OS and other OS which have UVC drivers

BOM

#	Items	QTY
1	LI-VENUS-OX03F10-9295-075H	1
2	LI-GMSL2-USB	1
3	FAK-SMZSMZ-3M Cable	1
4	12 VDC Power Supply	1
5	USB3.0 Cable	1



SDK SUPPORTED

- Camera Tool Source Code in C#
- Capture & Display
- Register Access Function

• REVISION HISTORY

Revision	Description	Release Date
1.0	First release.	25 Apr 2023

910 Auburn Ct, Fremont, CA 94538, USA
Phone: +1 (408)263-0988
Fax: +1 (408)217-1960
Email: sales@leopardimaging.com
Website: www.leopardimaging.com

