



53C4M-1S7

15 Amp Medical Grade Power Strip with Load Monitoring Inform™ Technology, Surge Protected, 4-Outlet, 7' Cord

15 Amp (12 Amp Max Continuous Load) 125 VAC, Medical Grade Power Strip with Load Monitoring Inform™ Technology, Surge Protected, 4 Hospital Grade NEMA 5-15R Outlets With Locking Covers, 7' Power Cord with Standard Hospital Grade NEMA 5-15P Plug, Special Purpose Relocatable Power Tap (SPRPT), UL 1363A, UL 60601-1, UL 60950-1, and UL 1449

Leviton's medical grade power strips with load monitoring Inform™ technology provide a simple and efficient way to improve code compliance and electrical safety in health care facilities.

According to NFPA 99: Health Care Facilities Code Article 10.2.3.6, which both the Centers for Medicare and Medicaid Services (CMS) and The Joint Commission inspect and survey to, "The sum of the ampacity of all appliances connected to the outlets does not exceed 75 percent of the ampacity of the flexible cord supplying the outlets."

- These devices feature a real-time, line-of-sight LED indication when the NFPA 99 75% limit has been reached (this is an indication only - no power will be shut off to the outlets)
- Inform™ monitors the load of devices so you don't have to, eliminating the need for manual calculations
- Load monitoring LED will remain OFF until the 75% limit is reached
- Available in 4 and 6 outlets, surge protection and non-surge, and 7' cord and 15' cord configurations
- Operable in Isolated Power Applications
- According to Centers for Medicare & Medicaid Services (CMS):
"Power strips providing power to patient care-related electrical equipment must be Special-Purpose Relocatable Power Taps (SPRPT) listed as UL 1363A or UL 60601-1."

Technical Information

Electrical Specifications

Amperage : 15 A

Cord Length : 7 Foot

Frequency : 60 Hz

Grade : Medical

Number of Receptacles : 4

Voltage : 125 VAC

Environmental Specifications

Operating Temperature : 0°C to 40°C

Storage Temperature : -10°C to +50°C

Material Specifications

Enclosure Material : Powder Coated Steel

Mechanical Specifications

HG Outlet Configuration : NEMA 5-15R

UPC Code : 078477415344

Country Of Origin : Mexico

Line Cord : #14/3 SJT
Outlet Covers : Polypropylene

HG Plug Configuration :
NEMA 5-15P

Performance Data

Joules Rating : 644J

MCOV : 150V

Maximum Leakage Current :
<100µA

Maximum Surge Current :
27kA

Noise Filtering : -6dB to -29dB
(100kHz to 100MHz)

**Voltage Protection Rating
(VPR) L-N, L-G, N-G** : 600V,
600V, 500V

Standards and Certifications

Standards and Certifications
: UL 1363A, UL 60601-1, UL
60950-1, UL 1449

Product Features

Feature : LED Indication

Inform Feature : Load
Monitoring

Inform Technology : Yes

Surge Protection : Yes

Warranty

Warranty : 5-Year Limited

SPECIFICATION SUBMITTAL

JOB NAME: <input type="text"/>	CATALOG NUMBERS: <input type="text"/>	<input type="text"/>
JOB NUMBER: <input type="text"/>	<input type="text"/>	<input type="text"/>

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.
T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·
FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)
5386- 1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without
notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:
www.leviton.com/international/contacts

© 2024 Leviton Manufacturing Co., Inc.