



UPC Code: 078477415375

Country Of Origin: Mexico

53C4M-2N5

20 Amp Medical Grade Power Strip with Load Monitoring Inform™ Technology, 4-Outlet, 15' Cord

20 Amp (16 Amp Max Continuous Load) 125 VAC, Medical Grade Power Strip with Load Monitoring Inform™ Technology, Non-Surge, 4 Hospital Grade NEMA 5-20R Outlets With Locking Covers, 15' Power Cord with Standard Hospital Grade NEMA 5-20P Plug, Special Purpose Relocatable Power Tap (SPRPT), UL 1363A, UL 60601-1, and UL 60950-1

Leviton's medical grade power strips with load monitoring Inform™ technology provide a simple and efficient way to improve code compliance and electrical safety in health care facilities.

According to NFPA 99: Health Care Facilities Code Article 10.2.3.6, which both the Centers for Medicare and Medicaid Services (CMS) and The Joint Commission inspect and survey to, "The sum of the ampacity of all appliances connected to the outlets does not exceed 75 percent of the ampacity of the flexible cord supplying the outlets."

- These devices feature a real-time, line-of-sight LED indication when the NFPA 99 75% limit has been reached (this is an indication only no power will be shut off to the outlets)
- Inform[™] monitors the load of devices so you don't have to, eliminating the need for manual calculations
- Load monitoring LED will remain OFF until the 75% limit is reached
- Available in 4 and 6 outlets, surge protection and non-surge, and 7' cord and 15' cord configurations
- Operable in Isolated Power Applications
- According to Centers for Medicare & Medicaid Services (CMS):

"Power strips providing power to patient care-related electrical equipment must be Special-Purpose Relocatable Power Taps (SPRPT) listed as UL 1363A or UL 60601-1."

Technical Information

Cord Length: 15 Foot

Electrical Specifications Environmental Specifications

Amperage: 20 A Operating Temperature: 0°C

to 40°C

Frequency: 60 Hz Storage Temperature: -10°C

to +50°C

Grade: Medical

Number of Receptacles: 4

Voltage: 125 VAC

Coated Steel

<u>Material Specifications</u> <u>Mechanical Specifications</u>

Enclosure Material: Powder **HG Outlet Configuration**:

NEMA 5-20R

Line Cord: #14/3 SJT **HG Plug Configuration**:

Outlet Covers : Polypropylene

NEMA 5-20P

Performance Data Product Features

Maximum Leakage Current : Feature : LED Indication

<100µA

Inform Feature : Load

Monitoring

Inform Technology : Yes
Surge Protection : No

Standards and Certifications Warranty

Standards and Certifications

: UL 1363A, UL 60601-1, UL

60950-1

Warranty: 5-Year Limited

SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:
JOB NUMBER:	

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.

T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52) 5386- 1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts

© 2024 Leviton Manufacturing Co., Inc.