



**UPC Code :** 078477270325

**Country Of Origin :** Mexico

## 53C4M-2S5

20 Amp Medical Grade Power Strip with Load Monitoring Inform™ Technology, Surge Protected, 4-Outlet, 15' Cord

20 Amp (16 Amp Max Continuous Load) 125 VAC, Medical Grade Power Strip with Load Monitoring Inform™ Technology, Surge Protected, 4 Hospital Grade NEMA 5-20R Outlets With Locking Covers, 15' Power Cord with Standard Hospital Grade NEMA 5-20P Plug, Special Purpose Relocatable Power Tap (SPRPT), UL 1363A, UL 60601-1, UL 60950-1, and UL 1449

**Leviton's medical grade power strips with load monitoring Inform™ technology provide a simple and efficient way to improve code compliance and electrical safety in health care facilities.**

According to NFPA 99: Health Care Facilities Code Article 10.2.3.6, which both the Centers for Medicare and Medicaid Services (CMS) and The Joint Commission inspect and survey to, "The sum of the ampacity of all appliances connected to the outlets does not exceed 75 percent of the ampacity of the flexible cord supplying the outlets."

- These devices feature a real-time, line-of-sight LED indication when the NFPA 99 75% limit has been reached (this is an indication only - no power will be shut off to the outlets)
- Inform™ monitors the load of devices so you don't have to, eliminating the need for manual calculations
- Load monitoring LED will remain OFF until the 75% limit is reached
- Available in 4 and 6 outlets, surge protection and non-surge, and 7' cord and 15' cord configurations
- Operable in Isolated Power Applications
- According to Centers for Medicare & Medicaid Services (CMS):  
"Power strips providing power to patient care-related electrical equipment must be Special-Purpose Relocatable Power Taps (SPRPT) listed as UL 1363A or UL 60601-1."

### Technical Information

#### Electrical Specifications

**Amperage :** 20 A  
**Cord Length :** 15 Foot  
**Frequency :** 60 Hz  
**Grade :** Medical  
**Number of Receptacles :** 4  
**Voltage :** 125 VAC

#### Environmental Specifications

**Operating Temperature :** 0°C to 40°C  
**Storage Temperature :** -10°C to +50°C

#### Material Specifications

**Enclosure Material :** Powder Coated Steel  
**Line Cord :** #14/3 SJT  
**Outlet Covers :** Polypropylene

#### Mechanical Specifications

#### **HG Plug Configuration :** NEMA 5-20P

#### Performance Data

**Joules Rating :** 644J  
**MCOV :** 150V  
**Maximum Leakage Current :** <100µA  
**Maximum Surge Current :** 27kA  
**Noise Filtering :** -6dB to -29dB (100kHz to 100MHz)  
**Voltage Protection Rating (VPR) L-N, L-G, N-G :** 600V, 600V, 500V

#### Product Features

**Feature :** LED Indication  
**Inform Feature :** Load Monitoring  
**Inform Technology :** Yes  
**Surge Protection :** Yes

#### Standards and Certifications

**HG Outlet Configuration :** NEMA 5-20R

**Standards and Certifications :** UL 1363A, UL 60601-1, UL 60950-1, UL 1449

Warranty

**Warranty :** 5-Year Limited

## SPECIFICATION SUBMITTAL

JOB NAME: <input type="text"/>	CATALOG NUMBERS: <input type="text"/>	
JOB NUMBER: <input type="text"/>	<input type="text"/>	<input type="text"/>

**Leviton Manufacturing Co., Inc.**

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

**Leviton Manufacturing of Canada, Ltd.**

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·

FAX: +1-800-824-3005 · [www.leviton.com/canada](http://www.leviton.com/canada)

**Leviton S. de R.L. de C.V.**

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · [www.leviton.com.mx](http://www.leviton.com.mx)

**Visit our Website at:** [www.leviton.com](http://www.leviton.com)

© 2023 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

**Leviton has a global presence.**

If you would like to know where your local Leviton office is located please go to: [www.leviton.com/international/contacts/](http://www.leviton.com/international/contacts/)