


# 55100 Sensor

## Miniature Flange Mounting Proximity

RoHS



### Description

The 55100 is a miniature flange mounting hall effect sensor 25.5mm (1.004") x 11.00mm (0.433") and only 3.00mm (0.118") high with a choice of digital or programmable analog outputs. It is available as three-wire (voltage output) or two-wire (current output) versions. Its case design enables screw or adhesive mounting and capable of switching up to 24Vdc and 20mA. It comes with a range of sensitivity and cable length options.

### Features & Benefits

- Magnetically operated position sensor
- Digital or programmable analog types available
- Medium, high or programmable sensitivities
- Three-wire (voltage output) or two-wire (current output) versions
- Reverse/Over voltage protection
- Built in temperature compensation
- Vibration 50g max. @ 50-2,000Hz
- Shock 150g max. @ 11ms ½ Sine
- High switching speed up to 12kHz
- Long life - up to 20 billion operations
- Operates in static or dynamic magnetic field
- RoHS compliant
- IP67 rated

### Additional Information



Resources



Accessories




Samples

### Applications

- Position and limit sensing
- RPM measurement
- Flow metering
- Commutation of brushless DC motors
- Angle sensing
- Magnetic encoders

### Dimensions

mm (inch)




**Note:** Two-wire version illustrated

# 55100 Sensor


## Miniature Flange Mounting Proximity

### Block Diagram


Two-wire Version



Three-wire Version



Three-wire Analog Version



#### Notes:

1. Add capacitor Cn as shown, close to the sensor, for transient suppression if required.
2. Add pull-up resistor Rpu as shown for sinking output. The Rpu value should be calculated using your supply voltage while keeping the ON state current at a level below the maximum.  
 $R_{pu} = V_{DD}/I_o$ ;  $R_{pu} = 12V_{dc}/10mA = 1.2k\Omega$

### T1 - Electrical Ratings

2-Wire Hall Switch (2M)

| Hall Type                   |                        |           | Digital Switch 2-Wire (Current Output) |
|-----------------------------|------------------------|-----------|----------------------------------------|
| Supply Voltage <sup>1</sup> | Absolute Ratings       | Vdc       | -18 to +28                             |
|                             | Operate                | Vdc       | +3 to +24                              |
|                             | Overvoltage Protection | Vdc - max | 32                                     |
| Current Consumption         | Hall OFF               | mA        | 5.0 to 6.9                             |
|                             | Hall ON                | mA        | 12.0 to 17.0                           |
| Switching Speed             | -                      | kHz       | 12                                     |
| Temperature                 | Operating              | C         | -40 to +100                            |

#### Notes:

1. It is assumed the product will operate within the normal Supply Voltage of +24Vdc maximum.

### T2 - Electrical Ratings

3-Wire Hall Switch &amp; Analog Programmable (3H, 3M, &amp; AP)

| Hall Type                         |                        |           | Digital Switch 3 - Wire (Voltage Output) | AP - Analog (Programmable Only) <sup>2</sup> |
|-----------------------------------|------------------------|-----------|------------------------------------------|----------------------------------------------|
| Supply Voltage <sup>1</sup>       | Absolute Ratings       | Vdc       | -18 to +28                               | 8.5                                          |
|                                   | Operate                | Vdc       | 2.7 to 24                                | 4.5 - 5.5                                    |
|                                   | Overvoltage Protection | Vdc - max | 32                                       | 16.0                                         |
| Output High Voltage               | Min                    | Vdc       | Sinking Output                           | 0.2                                          |
| Output Low Voltage                | Max                    | Vdc       | 0.4 @ 20mA                               | 4.80                                         |
| Output Current (continuously on)  | Max                    | mA        | 25                                       | -1.0 to +1.0                                 |
| Current Consumption (from Supply) | -                      | mA        | 1.1 to 2.4                               | 5.0 to 10.0                                  |
| Switching Speed                   | -                      | kHz       | 12                                       | 2                                            |
| Temperature                       | Operating              | C         | -40 to +100                              | -40 to +100                                  |

#### Notes:

1. It is assumed the product will operate within the normal Supply Voltage of +24Vdc maximum.
2. Sensor Voltage Output can be reprogrammed to best fit customer application (see LF Application Note)

# 55100 Sensor

## Miniature Flange Mounting Proximity

### Hall Sensitivity Options

| Select Option | Hall Type     | Sensitivity (Gauss)                | Activate - D <sup>1</sup> mm (inch) |
|---------------|---------------|------------------------------------|-------------------------------------|
| 2M            | 2-Wire Switch | 94                                 | 15.0                                |
| 3M            | 3-Wire Switch | 120                                | 13.0                                |
| 3H            | 3-Wire Switch | 55                                 | 19.0                                |
| AP            | Analog        | Programmable Response <sup>2</sup> |                                     |


**Notes:**

1. Activation distances are approximate using NeFeB Magnet 21 x 7 x 4.7 (.827 x .276W x .185H)

Littelfuse P/N H-58

2. Sensor Voltage Output can be reprogrammed to best fit customer application (see LF Application Note)

### Activation Detail



### Cable Length Specification

| Cable<br>24 AWG 7/32 PVC 105°C UL1430/UL1569 |                        |
|----------------------------------------------|------------------------|
| Select Option                                | Cable Length mm (inch) |
| 02                                           | 300 (11.81)            |
| 05                                           | 1000 (39.37)           |


### Termination Detail

| Select Option | Description<br>(Two-wire versions illustrated)                                                                |
|---------------|---------------------------------------------------------------------------------------------------------------|
| A             | Tinned leads (6.4±0.76)mm  |

### Packaging Options

| Packaging Option | Packaging Specification | Quantity | Quantity & Packaging Code | Taping Width |
|------------------|-------------------------|----------|---------------------------|--------------|
| Bulk             | Bulk                    | 500      | N/A                       | N/A          |

### Part Numbering System



**Disclaimer Notice** - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at <http://www.littelfuse.com/disclaimer-electronics>.